

CONFIDENTIAL

Remington Arms Company Inc.  
RESEARCH & DEVELOPMENT TECHNICAL CENTER  
315 WEST RING ROAD

## ACCURACY TESTING:

### ACCURACY TESTING – :

#### TLW0683T - Group Size at 100 yards :

One hundred-yard accuracy testing will be completed utilizing standard factory ammunition. The test will consist of five, 5-shot groups. Guns will be cooled after every other group. Each firearm will be cleaned and fired with five fouling shots prior to beginning the accuracy work-up. Group sizes will be measured from actual targets and recorded. The same code of ammunition and same type of ammunition will be used for all group size test shots. Average group sizes must be less than or equal to the sizes per the attached schedule (as shown by the Gallery Specs.)

	<u>3 Shot Groups</u>	<u>4 Shot Groups</u>	<u>5 Shot Groups</u>
<b>.300 Win. Mag.</b> <b>180 grain. PSPCL</b> <b>(Gallery Specs.)</b>	2.5"	3.0"	3.5"
<b>.7mm Rem. Mag.</b> <b>175 grain PSPCL</b> <b>(Gallery Specs.)</b>	2.5"	3.0"	3.5"

#### Method:

- Certify the ammunition selected for muzzle velocity and pressure.
- Fire five, 5-shot groups at 100 yards, using a 36 power scope for each ammunition type selected. Prior to beginning of the test, clean the bore and shoot 5 "fouling" shots to seat in the rifle.
- Cycle the safety from fire to safe every 5 rounds.
- Accuracy should be shot from a recoiling rest. Shoulder shooting is acceptable but not the preferred way.

J.R.Snedeker  
TLW 0683

Page 29 of 41  
Remington Confidential

05/24/06

Revision # 1.1

Subject to Protective Order - Williams v. Remington

BARBER - 5.30.06R0001493

ETE00001492