

<b>CONFIDENTIAL</b>		<b>TLW0010</b>	
Remington Arms Company Inc. RESEARCH & DEVELOPMENT TECHNICAL CENTER 315 WEST RING ROAD ELIZABETHTOWN, KY 42701			
3.1.5.2 TLW0010T – Drop and Cast	Not Tested	Completed	Acceptable
3.1.5.3 TLW0010U – 40 lb. Trigger Pull Test	Not Tested	Completed	Passed
<b>3.1.6 Firearms Measurements</b>			
3.1.6.1 TLW0010V – Chamber Cast	Completed	Completed	Did not meet all Specifications
3.1.6.2 TLW0010W – Bore Diameter	Completed	Completed	Some bore diameters oversize
3.1.6.3 TLW0010X – Groove Diameter	Completed	Completed	Some groove diameters over max. dimension.
3.1.6.4 TLW0010Y – Twist Rate (.30-06)	Completed	Completed	Passed
3.1.6.5 TLW0010Z – Magazine Capacity Test	Completed	Completed	Passed
<b>3.2. FUNCTION &amp; ENDURANCE TESTING</b>			
<b>3.2.1 Function &amp; Endurance Testing</b>			
3.2.1.1 TLW0010AA – Basic Jack Function Test	Completed	Completed	Average Malf. Rate 1.35% - Passed
3.2.1.2 TLW0010AB – Basic Shoulder Function Test	Completed	Completed	Average Malf. Rate 0.17% - Passed
3.2.1.3 TLW0010AC – Extended Function & Endurance Test	Completed	Completed	Acceptable
3.2.1.4 TLW0010AD – Clean Rifles and Inspect	Completed	Completed	For Information
3.2.1.5 TLW0010AE – Dry Cycle to 5000 Cycles	Completed	Completed	Acceptable
<b>3.3. ACCURACY</b>			
<b>3.3.1 Accuracy &amp; POI Testing</b>			
3.3.1.1 TLW0010AF – Point of Impact	Not Done	Completed	Acceptable
3.3.1.2 TLW0010AG – Group Size at 100 Yards	Completed	Completed	Acceptable
Jan.2001 Design Acceptance Test Remington M/710 Centerfire Rifle; R & D Technical Center Project No. 241039; TLW 0010 file: F:\Test Reports \Firearms Tests \M710_DAT_REPORT_JAN01_Rev1.doc <b>Page 11</b> <b>CONFIDENTIAL</b> <small>REV. 1 - 09/24/00 WJS/AM</small>			