

FIRING PIN HEAD TO SEAR ENGAGEMENT: TLW0407N, ALL GUNS		ISS FUNCTION TEST, TLW0407P	
MAGAZINE SPRING FORCE		BOLT STOP & RELEASE FUNCTION TEST	
TLW0407M, GUNS A11-A20	measurement method	TLW0407O, GUNS A11-A20	
WITH TEST STAND	produces a dimension range	STOP FUNCTION	RELEASE DETENT
	.064 .075		
	.069 .080		
	.063 .074		
	.067 .078		
	.067 .078		
	.068 .079		
	.071 .082		
	.072 .083		
	.068 .079		
	.068 .079		
	.066 .078	PASS	4.21
	.066 .077	PASS	4.62
	.066 .077	PASS	5.22
	.066 .077	PASS	4.64
	.067 .078	PASS	4.66
	.068 .079	PASS	4.71
	.067 .078	PASS	5.18
	.068 .080	PASS	4.64
	.067 .078	PASS	4.61
	.065 .078	PASS	4.58
	.067 .078		
	.068 .079		
	.068 .079		
	.067 .078		
	.069 .080		
	.061 .073		
	.067 .079		
	.066 .077		
	.069 .080		
	.070 .081		

Subject to Protective Order - Williams v. Remington

BARBER - 5.30.06R0001969

ETE00001968