

CONFIDENTIAL

Remington Arms Company Inc.
RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

- The graduated headspace gauges based on Remington chamber dimensions (Ref.: Remington Gauge Drawing # 41560 ...A (min.), ...B (+ .005), ...C (+ .007), & ...D (+ .009)) will again be used and the headspace measurements will be recorded to the nearest .001" increment as indicated by the gauge. The .270 Remington chamber drawing LB-154 will be used for chamber.
- The headspace measurement taken prior to the proof test should be less than min. + .005". If, after proof, the growth of the headspace is more than + .002" from the pre-proof condition, then stop and review the results with the test manager before continuing to the next phase of the test.
- In no case should the measurement for headspace after initial proof test be greater than min.+007" for a new firearm.
- If at any time during the test program the headspace exceeds a maximum of Min. + .009" do not continue to fire the rifle, tag the gun with a label reading "Do Not Shoot This Firearm – Exceeds Maximum Allowable Headspace" and return the firearm to the Test Manager for disposition.

Data Required:

- Rifle serial number
- Record and note any headspace growth and round level.

FORCES – TLW0407H THROUGH TLW0407Q AND TLW0407T:**TLW0407H - Measure Firing Pin Indent:**

The firing pin indent will be measured for each of the sample rifles using SAAMI qualified copper crushers. The average of three trials per sample rifle will be calculated. The Average of three indents must be equal to or greater than 0.017"

Method:

J.R.Snedeker

05/24/06

Page 11 of 32

9:47 AM

TLW0407

Remington Confidential

Revision # 2