

Remington Arms Company Ins Research & Development Technical Center 315 West Ring Road Elizabethtown, KY 42701

This test simulates the effect of a rifle leaning vertically against a walk free or other surface and unintentionally falling on one side or the other. There are two orientations used for this test. The rifle is allowed to fall from a vertical position first on one side of the stock then on the other side.

	B-24	B-25	B-26	B-27	B -28	B-29	B-3 0		
	OPEN	OPEN	OPEN	SCOPE	SCOPE	SCOPE	SCOPE		
	SIGHTS	SIGHTS	SECHTS						
Barrel Vertical; Drop with Left	PASS	PASS	PASS	PASS	PASS	PASS	PASS		
Side Up.		1.00		l. 					
Barrel Vertical; Drop with	PASS	PASS	PASS	PASS	PASS	PASS	PASS		
Right Side Up.									

3.5.1.4 TLW9010AT - Extended SAAMI Jar-Off Test (for Information only)

This test is similar to the standard SAAMF far-Off fest but is strictly an internal Remington test and is conducted for information only. The individual rifles are designated at "passing" or "failing" each individual drop and the status recorded. The test guns are dropped from heights of 6", 18": 24" and 48". The purpose of this test is to gauge the "sensitivity" of the product.

		20000000	NO.	555555	
	6"	18"	24"	48**	Comments
B-24	PASS	PASS	PASS	FAIL	1 Orientation – Barrel Horizontal; Bottom Down
B-25	PASS	PASS	PASS	PASS	
B-26	PASS	PASS	FAIL	PASS	1 Orientation – Barrel Horizontal; Bottom Up
B-27	PASS	PASS	PASS	PASS	
B-28	PASS	PASS	PASS	FAIL	1 Orientation – Barrel Horizontal; Bottom Down
B-29	PASS	PASS	PASS	PASS	
B-30	PASS	PASS	PASS	PASS	

3.5.4.5 TLW0010AU - Extended SAAMI Rotation Test (for Information only)

an 2001 Design Acceptance Test Remington M/710 Centerfire Rifle; R & D Technical Center Project No. 241039; TLW 0100 file: E.\Test Reports \ Firearms Tests \ M710_DAT_REPORT_JAN01_Rev1.doc

Page 48
CONFIDENTIAL

KL1.2-6524466 9:59.851