

PROJECT# 241095		D.A.T.(2)
SAAMI DROP TEST. TLW 0010AQ		
SAAMI JAR-OFF TEST. TLW 0010AR		
SAAMI ROTATION TEST. TLW 0010AS		
JAR-OFF TEST		POSITION
12 IN / SAFE OFF	BARREL HORIZONTAL, BOTTOM OF STOCK DOWN	
12 IN / SAFE OFF	BARREL HORIZONTAL, BOTTOM OF STOCK UP	
12 IN / SAFE OFF	BARREL HORIZONTAL, LEFT SIDE OF STOCK UP	
12 IN / SAFE OFF	BARREL HORIZONTAL, RIGHT SIDE OF STOCK UP	
12 IN / SAFE OFF	BARREL VERTICAL, MUZZEL UP	
12 IN / SAFE OFF	BARREL VERTICAL, MUZZEL DOWN	
DROP TEST		POSITION
48 IN / SAFE ON	BARREL HORIZONTAL, BOTTOM OF STOCK DOWN	
48 IN / SAFE ON	BARREL HORIZONTAL, BOTTOM OF STOCK UP	
48 IN / SAFE ON	BARREL HORIZONTAL, LEFT SIDE OF STOCK UP	
48 IN / SAFE ON	BARREL HORIZONTAL, RIGHT SIDE OF STOCK UP	
48 IN / SAFE ON	BARREL VERTICAL, MUZZEL UP	
48 IN / SAFE ON	BARREL VERTICAL, MUZZEL DOWN	
ROTATION TEST		POSITION, SAFE ON
FIREARM VERTICAL DROP SO LEFT SIDE OF STOCK IS UP		
FIREARM VERTICAL DROP SO RIGHT SIDE OF STOCK IS UP		
EXT JAR-OFF		POSITION

Subject to Protective Order - Williams v. Remington

BARBER - 5.30.06R0002927

ETE00002926