

CONFIDENTIAL

Remington Arms Company Inc.
RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

3.2 FUNCTION & ENDURANCE TESTING**3.2.1 Function and Endurance Testing****3.2.1.1 TLW0300Y - Ten (10) Round Safety Function Test with Lanyard**

Test completed without incident.

3.2.1.2 LW0300Z - Basic Jack Function Test (100 Rounds with Remington Ammunition.)

MALFUNCTIONS - BY AMMO TYPE - SERIES "C" - RIFLES C1 - C24,																								
Ammo Types	C 1	C 2	C 3	C 4	C 5	C 6	C 7	C 8	C 9	C 10	C 11	C 12	C 13	C 14	C 15	C 16	C 17	C 18	C 19	C 20	C 21	C 22	C 23	C 24
REM, L30062, 150 gr. MC																								
REM, PRT3006B, 165 gr. NBT																								
REM, R30064, 180 gr. SP					3C																			
REM, R30065, 180 gr. PSP			1A		3D																			
REM, R30067, 220 gr. SP				1B	3E																4F			

1A - Rifle C3 - Magazine Box Bottom came off @ 74 rounds into test.
1B - Rifle C4 - Magazine Box Bottom came off @ 90 rounds into test.
3C - Rifle C5 - Magazine Box Bottom came off @ 49, 54 & 58 rounds into test.
3D - Rifle C5 - Magazine Box Bottom came off @ 62, 71 & 78 rounds into test.
3E - Rifle C5 - Magazine Box Bottom came off @ 86, 91 & 97 rounds into test.
4F - Rifle C21 - Magazine Box Bottom came off @ 82, 90, 94 and 98 rounds into test.

Jan. '01 Trial & Pilot Test - Remington M710 Centerfire Rifle;
R & D Technical Center Project No. 241039; TLW 0300
File: E:\Test Reports\Firearms Tests\710 T&P_3006\M710_T&P_REPORT_JAN01_Rev0.doc

Page 28

CONFIDENTIAL

Rev'd 05/09/06 04:10