Remington Confidential

- When the scale settles down, record the weight in lb. to the nearest 0.1 lb. (Note that the scale has three decimal points displayed.)
- Re-assemble the bolt on its corresponding barreled action

Data Required:

- · Rifle serial number
- Weight to the nearest 0.1-lb.
- Serial number of the Mettler PB8000 balance (it should be SN 2114475246)

LENGTHS OF MAJOR COMPONENTS - TLW0010P TERQUGE TLW0010R:

TLW0010P - Overall Length:

Phase II measurement of Overall Length of the firearm. For information only.

Method:

- Set butt of gun on the floor near a walk
- Bring the top of the barrel to the wall so that the top of the barrel lies even with the wall surface
- Measure the distance from the floor to the end of the muzzle using a tape measure.

Data required:

- · Rifle Serial number
- · Measurements for each sample rifle

TLW0010Q - Barrel Length:

Measure the length of the barrel. For the .30-06 and .270 caliber, the barrel length should be

Method:

Check firearm for live ammunition

22" ± .125" measured from the best face to the end of the muzzle.

- Close bolt over and empty chamber
- With the built of the rifle on the floor and the muzzle pointing up, carefully and gently, so as to not scratch
 the bore or nick the rifling insert a brass rod (not steel) into the muzzle of the rifle until it stops on the bolt

Page 20 of 55

03/07/00

Remington Confidential

DRAFT Revision #1