

Remington Confidential

ACCURACY TESTING:**ACCURACY AND POI TESTING – TLW0010AF THROUGH TLW0010AG****TLW0010AF - Point of Impact:**

The point of impact test involves the verification of the firearms sighting system adjustment and the potential to hit the point of aim. The open sights must have sufficient adjustment in either direction when the rifle is sighted in at 100 yards. Random variation and/or extreme difference in shot to shot point of impact (as well as group size) typically indicate improper barrel processing and is used as a final inspection flag in production. This test will be shot from the bench with open sights. Shoot five, 5-shot groups from each test rifle. Use the same code of ammunition for all point of impact test shots.

Method:

- Certify the ammunition selected for muzzle velocity and pressure.
- Pick the point of aim on the target
- Adjust point of aim to the bullseye at 100 yards.
- Slide must be adjusted to between the second line from the rear to third line from the front.
- The aperture must have the width of the screw retaining shoulder visible to either side.
- Shoot five “warmer” shots
- Shot five, 5-shot groups

Data Required:

- Measure the center of the impact groups to the point of aim in terms of “x” and “y” positions.
- Record takedown screw torque
- Record position of slide when shot
- Record ammunition lot number used during the test
- Record and label any fail-to-fire ammunition

Page 35 of 55

03/07/00

Remington Confidential

DRAFT Revision #1

Subject to Protective Order - Williams v. Remington

BARBER - 5.30.06R0003641

ETE00003640