

CONFIDENTIAL

Remington Arms Company Inc.
RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

3.1.3.7 TLW0300N – Measure Firing Pin Head to Scar Engagement

(T&P, Series “C”); Specification: Minimum Vertical Engagement to be $\geq .049$ ”.

Note that the measurement method produces a dimensional range.

Variable	N	Mean (Range)	Std. Dev.	95% Confidence Interval
Firing Pin Head to Scar Engagement - range	30	0.065 – 0.076	0.0029	0.064, 0.077

3.1.3.8 TLW0300O – Bolt Stop Function Check

(T&P, Series “C”)

Variable	Good	Marginal / Loose
Stop Function	10	0
Release Detent	8	2

3.1.3.9 TLW0300P – Function Check of ISS System

(T&P, Series “C”)

All ten samples, C-11 to C-20, passed the ISS Function Test without incident.

Jan. '01 Trial & Pilot Test – Remington M/710 Centerfire Rifle;
R & D Technical Center Project No. 241039; TLW 0300
file: F:\Test Reports\Firearms Tests\710 T&P_3006\M710_T&P_REPORT_JAN01_Rev0.doc

Page 19

CONFIDENTIAL

REV. 0-052916-1001 JAN

Subject to Protective Order - Williams v. Remington

BARBER 5.30.06R00038590

ETE00001929