

CONFIDENTIAL

Remington Arms Company Inc.
RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

3.1.3.7 *TLW0300N – Measure Firing Pin Head to Scar Engagement*

(T&P, Series "C"); Specification: Minimum Vertical Engagement to be $\geq .049$ ".

Note that the measurement method produces a dimensional range.

Variable	N	Mean (Range)	Std. Dev.	95% Confidence Interval
Firing Pin Head to Scar Engagement - range	30	0.065 – 0.076	0.0029	0.064, 0.077

3.1.3.8 *TLW0300O – Bolt Stop Function Check*

(T&P, Series "C")

Variable	Good	Marginal / Loose
Stop Function	10	0
Release Detent	8	2

3.1.3.9 *TLW0300P – Function Check of ISS System*

(T&P, Series "C")

All ten samples, C-11 to C-20, passed the ISS Function Test without incident.

Jan. '01 Trial & Pilot Test - Remington M710 Centerfire Rifle;
R & D Technical Center Project No. 241039; TLW 0300
File: F:\Test Reports\Firearms Tests\710 T&P_3006\M710_T&P_REPORT_JAN01_Rev0.doc

Page 19

CONFIDENTIAL

Rev. 0-052916-1001 JAN

Subject to Protective Order - Williams v. Remington