

DE 23

COMPOSITE SAFETY RECOMMENDATIONS  
OF REMINGTON RESEARCH DEPT.

1. REDUNDANT BLOCKING FEATURE TO PROTECT AGAINST ACCIDENTAL DISCHARGE. E.G., SIMULTANEOUSLY BLOCK: (1) FIRING PIN AND TRIGGER; OR (2) TRIGGER AND SEAR; OR (3) INTERCEPTOR BAR ADDED.
2. ALWAYS PROVIDE ABILITY TO LOAD AND UNLOAD WHILE IN "ON SAFE" POSITION. BOLT LOCK INDEPENDENT OF SAFETY FOR MAXIMUM PROTECTION IS PREFERRED DESIGN.
3. ELIMINATE TRIGGER CONNECTOR VIA USE OF ONE PIECE TRIGGER.
4. ELIMINATE ENCLOSED HOUSING FOR EASIER CLEANING AND LUBRICATION.
5. ELIMINATE CLOSE MANUFACTURING TOLERANCES SUCH AS THOSE FOUND IN MODEL 700 WHEREVER POSSIBLE.
6. EXTERNALLY ADJUSTABLE TRIGGER THAT WILL NOT FUNCTION WHEN ADJUSTED OUT OF SPEC.
7. ABILITY TO PLACE "ON SAFE" AT ANY POINT IN CYCLE.

PLAINTIFF'S  
EXHIBIT

19-32