

FIRING PIN HEAD TO SEAR ENGAGEMENT: TLW0407N, ALL GUNS		BOLT STOP & RELEASE FUNCTION TEST TLW0407O, GUNS A11-A20		ISS FUNCTION TEST, TLW0407P GUNS A11-A20
MAGAZINE SPRING FORCE	measurement method	TLW0407O, GUNS A11-A20		PASS/ FAIL
WITH TEST STAND	produces a dimension range	STOP FUNCTION	RELEASE DETENT	
	.064 .075			
	.069 .080			
	.063 .074			
	.067 .078			
	.067 .078			
	.068 .079			
	.071 .082			
	.072 .083			
	.068 .079			
	.068 .079			
	.066 .078	PASS	4.21	
	.066 .077	PASS	4.62	
	.066 .077	PASS	5.22	
	.066 .077	PASS	4.64	
	.067 .078	PASS	4.66	
	.068 .079	PASS	4.71	
	.067 .078	PASS	5.18	
	.068 .080	PASS	4.64	
	.067 .078	PASS	4.61	
	.065 .078	PASS	4.58	
	.067 .078			
	.068 .079			
	.068 .079			
	.067 .078			
	.069 .080			
	.061 .073			
	.067 .079			
	.066 .077			
	.069 .080			
	.070 .081			

Subject to Protective Order - Williams v. Remington