

710, 270 TRAIL & PILOT SERIES- A																	
PRELIMINARY MEASUREMENTS & CHECKS																	
PROOF TEST & MAGNAFLUX COMPLETED AT MAYFIELD																	
TEST LAB TRACKING NUMBER: TLW0407																	
GUN ID #	SERIAL NUMBER	HEADSPACE, REM. SPEC GAUGES	FIRING PIN INDENT W/ COPPER CRUSHERS				SEAR TO TRIGGER ENGAGEMENT				SEAR LIFT				TRIGGER PULL WITH SP		
			TLW0407H GUNS A11-A20				TLW0407I out of stock @ 20X, ALL GUNS				TLW0300I out of stock @ 20X, ALL GUNS				TLW0407J IN STOCK, ALL		
			1	2	3	AVERAGE	1	2	3	AVERAGE	1	2	3	AVERAGE	1	2	
A-1	7100	MIN.+.00					0.0246	0.0251	0.0244	0.0247	0.0163	0.0158	0.0162	0.0161	4	4.25	
A-2	7100	MIN.+.00					0.0294	0.0301	0.0297	0.0297	0.0155	0.0148	0.0159	0.0154	4.25	4.25	
A-3	7100	MIN.+.00					0.0277	0.0269	0.0285	0.0271	0.0148	0.0152	0.0146	0.0149	4.5	4	
A-4	7100	MIN.+.00					0.0271	0.0277	0.0272	0.0273	0.0163	0.0155	0.0169	0.0162	4.25	4.25	
A-5	7100	MIN.+.00					0.0253	0.0249	0.0252	0.0251	0.0152	0.0146	0.0143	0.0147	4.5	4.5	
A-6	7100	MIN.+.00					0.0298	0.0252	0.0288	0.0289	0.0169	0.0167	0.0168	0.0168	5	5.25	
A-7	7100	MIN.+.00					0.0277	0.0286	0.0286	0.0283	0.0142	0.0146	0.0141	0.0143	4.75	4.75	
A-8	7100	MIN.+.00					0.0268	0.0271	0.0269	0.0269	0.0153	0.0162	0.0156	0.0157	4.5	4.25	
A-9	7100	MIN.+.00					0.0239	0.0241	0.0242	0.0241	0.0138	0.0136	0.0135	0.0136	5.25	4.75	
A-10	7100	MIN.+.00					0.0252	0.0249	0.0251	0.0251	0.0162	0.0159	0.0164	0.0162	4	4.5	
A-11	7100	MIN.+.00	0.016	0.017	0.016	0.0163	0.0266	0.0258	0.026	0.0261	0.0155	0.0161	0.0164	0.0160	3.75	4.25	
A-12	7100	MIN.+.00	0.017	0.017	0.017	0.0170	0.0271	0.0268	0.0275	0.0271	0.0164	0.017	0.0163	0.0166	4.25	4.75	
A-13	7100	MIN.+.00	0.018	0.018	0.018	0.0180	0.0301	0.0299	0.0303	0.0301	0.0177	0.0171	0.017	0.0170	4	4	
A-14	7100	MIN.+.00	0.016	0.016	0.016	0.0160	0.0269	0.0271	0.0278	0.0273	0.0161	0.0162	0.0157	0.0161	4.25	4.75	
A-15	7100	MIN.+.00	0.017	0.016	0.016	0.0163	0.0252	0.0242	0.0244	0.0246	0.0146	0.015	0.0141	0.0146	4	4	
A-16	7100	MIN.+.00	0.018	0.017	0.018	0.0177	0.0264	0.0262	0.026	0.0262	0.0172	0.0181	0.0177	0.0177	4.25	4.5	
A-17	7100	MIN.+.00	0.018	0.017	0.017	0.0173	0.0291	0.0287	0.0295	0.0291	0.0159	0.0161	0.016	0.0160	4.25	4	
A-18	7100	MIN.+.00	0.017	0.017	0.016	0.0167	0.0263	0.0262	0.0268	0.0264	0.0149	0.0156	0.0152	0.0151	4	4	
A-19	7100	MIN.+.00	0.018	0.018	0.018	0.0180	0.0306	0.0317	0.0309	0.0311	0.0169	0.0166	0.0168	0.0168	4.25	4.5	
A-20	7100	MIN.+.00	0.018	0.017	0.017	0.0173	0.0301	0.0297	0.0299	0.0299	0.0158	0.0161	0.016	0.0160	5	5	
A-21	7100	MIN.+.00					0.0302	0.0299	0.0306	0.0302	0.0135	0.0134	0.013	0.0133	4.5	4.75	
A-22	7100	MIN.+.00					0.0286	0.028	0.0287	0.0284	0.0158	0.0158	0.0161	0.0159	4.25	4.75	
A-23	7100	MIN.+.00					0.0301	0.0299	0.0307	0.0302	0.0149	0.0144	0.0147	0.0147	4	3.75	
A-24	7100	MIN.+.00					0.0289	0.0297	0.0293	0.0293	0.0142	0.0144	0.0141	0.0142	4	5	
A-25	7100	MIN.+.00					0.0301	0.0306	0.0309	0.0305	0.0133	0.0141	0.0137	0.0137	4.5	4	
A-26	7100	MIN.+.00					0.0273	0.0274	0.0272	0.0273	0.0175	0.0182	0.0186	0.0181	4.25	4.5	
A-27	7100	MIN.+.00					0.0262	0.0269	0.0261	0.0264	0.0155	0.0161	0.0157	0.0158	4	4.75	
A-28	7100	MIN.+.00					0.0315	0.0317	0.0301	0.0311	0.0183	0.0174	0.0171	0.0176	4	4	
A-29	7100	MIN.+.00					0.0299	0.0297	0.0299	0.0298	0.0185	0.0179	0.0182	0.0182	5	4.75	
A-30	7100	MIN.+.00					0.0286	0.0279	0.0284	0.0283	0.0167	0.0166	0.0167	0.0167	4	4	
TEST AVERAGE						0.0171	TEST AVERAGE				0.02780	TEST AVERAGE				0.0164	TES
SAAMI MIN = .017							SPEC = .020 TO .025					SPEC.= .006 TO .018					SPEC.= 4.0