

C6498805

MODEL 700™ M24

Model **SMS**™

Action

Barrel Length

Capacity

Order No. **5716**

*Includes 1 in chamber.



CONTRACT # DAAA21-87-C-0086

GUN SERIAL # C6498806

OP. #	OP. NAME	READINGS	DATE	INIT
575 & 580	Assemble Action and Stock	6 29	90	RW
600	Proof	6 29	90	RW
607	Check Headspace	6 29	90	RW
610	Dis-assemble Gun	6 29	90	RW
612	Magnaflux Barrel Action		7-12-90	KR
	Magnaflux Bolt		7-12-90	KR
615	Rollmark Caliber		7-12-90	G.S.
617	Drill and Tap Sight Holes		7/13/90	LB
618	Polish Barrel RB		7/16/90	WB
620	Apply Coatings (Barrel Action)		7-23-90	TA
	Apply Coating (Bolt)			
625	Final Assembly A) Clean inside of Bolt Assembly		7/25/90	RW
	B) Inspect Rear Firing Pin Hole for Chamfer in Bolt Head		7/25/90	RW
	C) Inspect Ejector Hole for Chamfer		7/25/90	RW
	D) Oil Firing Pin Ass'y		7/25/90	RW
	E) Adjust Trigger Pull to Min Setting and Stake		8/18/90	WB

op. #	OP. NAME	READINGS					DATE	INIT
625 cont.	F) Safety On Force	4 1/2	4 1/2	4 1/2			8/18/90	WB
	G) Safety Off Force	2 1/2	2 1/2	2 1/2			8/18/90	WB
	H) Trigger Pull Test & Retainability						8/18/90	WB
	I) Firing Pin Indent	.023	.023	.023			8/18/90	WB
	J) Assemble Stock						8/24/90	RW
	K) Assemble Swivel Studs						8/31/90	928
	L) Attach Front and Rear Sight Assemblies						8/24/90	RW
	M) Iron Sight Alignment						8/24/90	RW
	N) Detach Front & Rear Sights & place in numbered container						8/24/90	RW
	O) Attach Scope to Rifle						8/24/90	WB
	P) Detach & Attach Scope 20 Times						8/24/90	WB
640	Gallery Target & Test						8-24-90	A
	A) Time						8-24-90	A
	B) Malfunctions						8-24-90	A
	C) Pierced Primers						8-24-90	A
	D) Optical Clarity of Scope						8-24-90	A
645	Inspect for Live Ammo						8-24-90	A
655	Final Inspection							
	A) Headspace						8/31/90	928
	B) Trigger Pull	2.42	2.37	2.50	2.50	2.50	8/31/90	941
	C) Function						8/31/90	928
660	Pack						9/20/90	15

SWS TRIGGER PULL TEST

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# ± .50#

3.00# ± .75#

4.00# ± 1.00#

SERIAL NO. C6498806

DATE Aug 18 / 1990

TESTER WB

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.55	2.50	2.44	2.42	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.61	2.44	2.50	2.37	
PULL #3	2.56	2.46	2.43	2.50	
PULL #4	2.48	2.48	2.51	2.50	
PULL #5	2.43	2.47	2.45	2.50	
TOTAL	12.63	12.35	12.33	12.29	
AVG.	2.52	2.47	2.46	2.458	

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.18	3.07		
PULL #2	3.19	3.07		
PULL #3	3.18	3.05		
PULL #4	3.13	3.25		
PULL #5	3.11	3.20		
TOTAL	15.79	15.64		
AVG.	3.18	3.13		

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.16	4.25		4.29
PULL #2	4.17	4.20		4.20
PULL #3	4.11	4.15		4.25
PULL #4	4.21	4.22		4.20
PULL #5	4.16	4.14		4.08
TOTAL	20.81	20.96		21.02
AVG.	4.16	4.19		4.20

CENTROIDAL DISTANCE CALCULATIONS
FOR RIFLE # C6498806
24 Aug 1990

CENTROIDAL DISTANCES

0 TO	1	.516902
1 TO	2	.266908
1 TO	3	.364936
1 TO	4	.785525
1 TO	5	.585212

1
4
4


<----POR

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: -.0876
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: .1328
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .15989
THE AMR FOR THIS RIFLE IS: .9792

24 Aug 1988

FILE:/PATTERNING/CENTERFIRE_PATT/C6498806

CENTERFIRE PATTERNS # 1



OF SHOTS = 10

IN CIR

1in = 4

2in = 5

3in = 9

HS = 2.8000

VS = 2.244


GS = 2.885

PATTERN #	:	1		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.102	.914	.817
MINIMUM X	:	-1.698	-.771	-.721
MAXIMUM Y	:	1.008	1.073	.927
MINIMUM Y	:	-1.236	-1.171	-1.024
CENTROID X	:	-.268	-.080	.017
CENTROID Y	:	.442	.377	.523
POA TO CENTROID in.	:	.517	.385	.523
MIN RADIUS	:	.264	.099	.179
MEAN RADIUS	:	.894	.753	.669
MAX RADIUS	:	1.797	1.402	1.050
HORIZONTAL SPREAD	:	2.800	1.685	1.538
VERTICAL SPREAD	:	2.244	2.244	1.951
EXTREME SPREAD	:	2.885	2.430	1.952
NUMBER IN ONE INCH CIRCLE	=		4	
NUMBER IN TWO INCH CIRCLE	=		5	
NUMBER IN THREE INCH CIRCLE	=		9	

24 Aug 1998

FILE:/PATTERNING/CENTERFIRE_PATT/C649B886

CENTERFIRE PATTERNS # 2



OF SHOTS - 10

IN CIR

1in = 2

2in = 4

3in = 8

HS= 2.153

VS= 4.243

GS= 4.330


CENTROID #

PATTERN #	:	2		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	.859	.800	.835
MINIMUM X	:	-1.294	-1.353	-1.318
MAXIMUM Y	:	2.403	1.337	1.141
MINIMUM Y	:	-1.840	-1.573	-1.008
CENTROID X	:	-.002	.057	.022
CENTROID Y	:	.464	.197	.393
POA TO CENTROID in.	:	.464	.205	.394
MIN RADIUS	:	.285	.095	.277
MEAN RADIUS	:	1.128	.932	.858
MAX RADIUS	:	2.461	1.597	1.382
HORIZONTAL SPREAD	:	2.153	2.153	2.153
VERTICAL SPREAD	:	4.243	2.910	2.149
EXTREME SPREAD	:	4.330	2.947	2.543
NUMBER IN ONE INCH CIRCLE	=		2	
NUMBER IN TWO INCH CIRCLE	=		4	
NUMBER IN THREE INCH CIRCLE	=		8	

24 Aug 1998

FILE:/PATTERNING/CENTERFIRE_PATT/C6498886

CENTERFIRE PATTERNS # 3



OF SHOTS= 10

IN CIR

1in = 1

2in = 4

3in = 9

HS= 2.127

VS= 2.917

GS= 2.941


CENTROID #

PATTERN #	:	3		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.176	1.171	.996
MINIMUM X	:	-.951	-.956	-.809
MAXIMUM Y	:	1.611	1.130	1.265
MINIMUM Y	:	-1.306	-1.127	-.992
CENTROID X	:	-.005	-.000	-.147
CENTROID Y	:	.189	.010	-.125
POA TO CENTROID in.	:	.189	.010	.193
MIN RADIUS	:	.119	.121	.319
MEAN RADIUS	:	1.050	.962	.868
MAX RADIUS	:	1.611	1.595	1.610
HORIZONTAL SPREAD	:	2.127	2.127	1.885
VERTICAL SPREAD	:	2.917	2.257	2.257
EXTREME SPREAD	:	2.941	2.855	2.658
NUMBER IN ONE INCH CIRCLE	=		1	
NUMBER IN TWO INCH CIRCLE	=		4	
NUMBER IN THREE INCH CIRCLE	=		9	

24 Aug 1998

FILE:/PATTERNING/CENTERFIRE_PATT/C6498806

CENTERFIRE PATTERNS # 4



OF SHOTS = 10

IN CIR

1 in = 3

2 in = 7

3 in = 8

HS = 2.689

VS = 1.619


GS = 2.734

PATTERN #	:	4		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.191	1.025	1.039
MINIMUM X	:	-1.498	-1.033	-.905
MAXIMUM Y	:	.649	.597	.469
MINIMUM Y	:	-.970	-1.022	-.525
CENTROID X	:	-.103	.063	-.065
CENTROID Y	:	-.326	-.274	-.146
POA TO CENTROID in.	:	.342	.281	.160
MIN RADIUS	:	.332	.261	.153
MEAN RADIUS	:	.877	.781	.653
MAX RADIUS	:	1.571	1.447	1.056
HORIZONTAL SPREAD	:	2.689	2.058	1.944
VERTICAL SPREAD	:	1.619	1.619	.994
EXTREME SPREAD	:	2.734	2.527	1.945
NUMBER IN ONE INCH CIRCLE	=		3	
NUMBER IN TWO INCH CIRCLE	=		7	
NUMBER IN THREE INCH CIRCLE	=		8	

24 Aug 1998

FILE:/PATTERNING/CENTERFIRE_PATT/0649B806

CENTERFIRE PATTERNS # 5



OF SHOTS - 10

IN CIR

1 in - 2

2 in - 6

3 in - 8

HS= 2.545

VS= 2.715

GS= 2.773

CENTROID #

PATTERN #	:	5		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	.831	.641	.649
MINIMUM X	:	-1.714	-1.243	-1.235
MAXIMUM Y	:	1.090	1.038	.828
MINIMUM Y	:	-1.625	-1.677	-.703
CENTROID X	:	-.060	.130	.122
CENTROID Y	:	-.105	-.053	.157
POR TO CENTROID in.	:	.121	.141	.199
MIN RADIUS	:	.203	.200	.146
MEAN RADIUS	:	.947	.803	.670
MAX RADIUS	:	1.777	1.678	1.268
HORIZONTAL SPREAD	:	2.545	1.884	1.884
VERTICAL SPREAD	:	2.715	2.715	1.531
EXTREME SPREAD	:	2.773	2.773	1.975
NUMBER IN ONE INCH CIRCLE	=		2	
NUMBER IN TWO INCH CIRCLE	=		6	
NUMBER IN THREE INCH CIRCLE	=		8	

Remington



VERY IMPORTANT:
Instruction Book
enclosed to assure
safe use of this
firearm.

MODEL 700TM H24

SERIAL NO.
C6498806

ORDER NO.
5716


MADE IN ILION, N.Y. U.S.A. Reg. U.S. Pat & Tm. Off, Marca Registrada Marque Deposee.

01



5716 C6498806

UPC



0 47700 25716 7

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER
KINZER V. REMINGTON

M2400008095