

G6801447

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker




ORDER NO. **86470**

BARREL LENGTH 24"

CAPACITY 6

G6801447

UPC



BM FORM

M-24
INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL # C6801447

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		5-21-09	SP
430	ASSEMBLE TO STOCK		5-21-09	SP
440	PROOF		5-21-09	SP
460	CHECK HEADSPACE	MAGNA - FLUX	5-21-09	SP
470	DIS-ASSEMBLE ACTION		5-21-09	SP
472	SERIALIZE BOLT HANDLE		5-22-09	SP
480	MAGNAFLUX BBL ACTION	OPERATOR <u>(N)</u>	5/29/09	(N)
490	MAGNAFLUX BOLT			
500	ROLLMARK CALIBER		5/29/09	RT
510	DRILL AND TAP SIGHT HOLES		5-22-09	SP
520	GOFF BLAST BBL / REC		5/29/09	gml
540	APPLY COATINGS (BARREL ACTION)		6/9	—
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		6-9-09	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		6-9-09	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER	INSPECT FOR LIVE AMMO	6-9-09	SP
	D) OIL FIRING PIN ASSEMBLY		6-15-09	SP
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

F004 REV 5/2006


OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>4.0</u> <u>4.0</u> <u>4.0</u>	6-26-09	LN
CONT.	G) SAFETY OFF FORCE 2 LBS MIN	<u>6.0</u> <u>6.0</u> <u>6.0</u>	6-26-09	LN
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.034</u> <u>.034</u> <u>.034</u>	6-26-09	LN
	J) ASSEMBLE STOCK		6-25-09	RP
	K) ASSEMBLE SWIVEL STUDS		6-26-09	LN
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	6-25-09	RP
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		6-25-09	LN
670	FINAL INSPECTION A) HEADSPACE		6-26-09	LN
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.64</u> <u>2.68</u> <u>2.65</u> <u>2.67</u> <u>2.68</u>	6-26-09	LN
	C) FUNCTION		6-26-09	LN
690	PACK		7/21/09	Fm

F004 REV 5/2006

Trigger Profile [lbs,inch]

Profile SWS
GunType: Rifle
Make: Remington
Note: R.P. 5/20/09

Model: M/24
Serial No: Form #F005
Trigger: 2.5 lbs. ini. +/- .50 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	2.635	0.019	0.00	0.034	0.037		Set Trigger
2	2.636	0.017	0.00	0.035	0.035		Set Trigger
3	2.593	0.017	0.00	0.035	0.034		Set Trigger
4	2.620	0.017	0.00	0.034	0.034		Set Trigger
5	2.598	0.018	0.00	0.034	0.035		Set Trigger

Avg 2.61

Trigger Profile [lbs,inch]

Profile SWS
GunType: Rifle
Make: Remington
Note: R.P. 5/20/09

Model: M/24
Serial No: Form #F005
Trigger: 2.5 lbs. after 50 cycles +/- .50 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	2.428	0.021	0.00	0.034	0.037		Set Trigger
2	2.450	0.019	0.00	0.034	0.036		Set Trigger
3	2.504	0.020	0.00	0.034	0.038		Set Trigger
4	2.503	0.020	0.00	0.034	0.038		Set Trigger
5	2.501	0.019	0.00	0.035	0.035		Set Trigger

Aug 2.47

Trigger Profile [lbs,inch]

Profile SWS
GunType: Rifle
Make: Remington
Note: R.P. 5/20/09

Model: M/24
Serial No: Form #F005
Trigger: 3.0 lbs. ini. +/- .75 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	3.098	0.019	0.00	0.031	0.045		Set Trigger
2	3.049	0.019	0.00	0.031	0.045		Set Trigger
3	3.080	0.019	0.00	0.032	0.044		Set Trigger
4	3.055	0.020	0.00	0.032	0.045		Set Trigger
5	3.053	0.020	0.00	0.032	0.045		Set Trigger

Avg 3.06

Trigger Profile [lbs,inch]

Profile: SWS
GunType: Rifle
Make: Remington
Note: R.P. 5/20/09

Model: M/24
Serial No: Form #F005
Trigger: 3.0 lbs. after 20 cycles +/- .75 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	2.964	0.020	0.00	0.033	0.042		Set Trigger
2	2.969	0.018	0.00	0.032	0.040		Set Trigger
3	2.985	0.018	0.00	0.032	0.041		Set Trigger
4	2.984	0.018	0.00	0.032	0.041		Set Trigger
5	2.953	0.019	0.00	0.032	0.041		Set Trigger

Aug 2.97

Trigger Profile [lbs,inch]

Profile SWS
GunType: Rifle
Make: Remington
Note: R.P. 5/20/09

Model: M/24
Serial No: Form #F005
Trigger: 4.0 lbs. ini. +/- 1.0 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	4.186	0.022	0.00	0.030	0.061		Set Trigger
2	4.115	0.020	0.00	0.030	0.059		Set Trigger
3	4.059	0.022	0.00	0.030	0.061		Set Trigger
4	4.025	0.020	0.00	0.030	0.057		Set Trigger
5	4.056	0.020	0.00	0.030	0.058		Set Trigger

Avg 4.08

Trigger Profile [lbs,inch]

Profile SWS
GunType: Rifle
Make: Remington
Note: R.P. 5/20/09

Model: M/24
Serial No: Form #F005
Trigger: 4.0 lbs. after 20 cycles +/- 1.0 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	4.013	0.020	0.00	0.030	0.058		Set Trigger
2	3.995	0.020	0.00	0.030	0.057		Set Trigger
3	3.990	0.019	0.00	0.030	0.056		Set Trigger
4	4.004	0.020	0.00	0.030	0.057		Set Trigger
5	3.957	0.020	0.00	0.030	0.056		Set Trigger

Avg 3.98

Trigger Profile [lbs,inch]

Profile SWS
GunType: Rifle
Make: Remington
Note: R.P. 5/20/09

Model: M/24
Serial No: Form #F005
Trigger: reset to 2.5 lbs. +/- .560 lbs. for final test




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	2.512	0.019	0.00	0.035	0.036		Set Trigger
2	2.495	0.018	0.00	0.034	0.034		Set Trigger
3	2.520	0.017	0.00	0.034	0.033		Set Trigger
4	2.487	0.017	0.00	0.035	0.033		Set Trigger
5	2.520	0.018	0.00	0.034	0.034		Set Trigger

Avg 2.50

Trigger Profile [lbs,inch]

Profile: SWS
GunType: Rifle
Make: Remington
Note: R.P. 5/20/09

Model: M/24
Serial No: Form #F005
Trigger: set to 4.0 lbs. +/- 1.0 lbs. for target & accuracy



#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	4.163	0.022	0.00	0.030	0.063		Set Trigger
2	4.120	0.020	0.00	0.030	0.060		Set Trigger
3	4.113	0.020	0.00	0.030	0.060		Set Trigger
4	4.112	0.021	0.00	0.030	0.062		Set Trigger
5	4.426	0.022	0.00	0.030	0.071		Set Trigger

Aug 4.18