

UPC



C66666077

ORDER NO. 25705

BARREL LENGTH 24"

CAPACITY * 6

*INCLUDES 1 IN CHAMBER

Do Not Use

Remington®

VERY IMPORTANT:
Instruction Book
enclosed to assure
safe use of this
firearm.

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

SERIAL NO.
C6666077

46 ORDER NO.
25705

Reg. U.S. Pat. & Tm. Off. Marca Registrada Marque Deposee.



5705 C6666077

23PR

Do Not Use

ORDER 25705

MODEL 700™ M24

UPC



ORDER 25705

MODEL 700™ M24

UPC



SERIAL NO.



C6666077

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

GREEN ENVELOPE CONTAINS:

- INSTRUCTION BOOK
- PRODUCT OWNER'S CARD
- MUSEUM/COUNTRY STORE FLIER
- REMINGTON AUTHORIZED GUNSMITHS

46 FORM



ISRAELI GUNS

IS-B-YLS

GUN SERIAL # C6666077

OP. #	OP. NAME	READINGS	DATE	INITIA
575 & 580	Assemble Action and Stock		3/4/97	A
600	Proof		3-5-97	A.M.M.
607	Check Headspace		3/5/97	A
610	Dis-assemble Gun		3/6/97	A
612	Magnaflux Barrel Action			
	Magnaflux Bolt			
615	Rollmark Caliber			
617	Drill and Tap Sight Holes		3/3/97	WJT
618	Polish Barrel		3/3/97	WJT
620	Apply Coatings (Barrel Action)			
	Apply Coating (Bolt)			
625	Final Assembly A) Clean inside of Bolt Assembly			
	B) Inspect Rear Firing Pin Hole for Chamfer in Bolt Head			
	C) Inspect Ejector Hole for Chamfer			
	D) Oil Firing Pin Ass'y			
	E) Adjust Trigger Pull to Min Setting and Stake			

OP. #	OP. NAME	READINGS	DATE	INITIAL
625 CONT.	F) SAFETY ON FORCE	<u>3</u> <u>3</u> <u>3</u>	5-5-97	JW
	G) SAFETY OFF FORCE	<u>2</u> <u>2</u> <u>2</u>	5-5-97	JW
	H) TRIGGER PULL TEST & RETAINABILITY		4-16-97	RW
	I) FIRING PIN INDENT	<u>21</u> <u>20.5</u> <u>21</u>	5-5-97	JW
	J) ASSEMBLE STOCK		4/24/97	RW
	K) ASSEMBLE SWIVEL STUDS		6-12-97	RP
	L) ATTACH FRONT AND REAR SIGHT ASSEMBLIES		5-28-97	JW
	M) IRON SIGHT ALIGNMENT		5-28-97	JW
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERER CONTAINER		5-28-97	JW
640	GALLERY TEST AND TARGET	Right 79 Left 71	6-7-97	WJ
	A) MALFUNCTIONS		6-7-97	WJ
	B) PIERCED PRIMERS		6-7-97	WJ
645	INSPECT FOR LIVE AMMO		6-7-97	JW
655	FINAL INSPECTION			
	A) HEADSPACE		6-13-97	RP
	B) TRIGGER PULL	<u>2.65</u> <u>2.76</u> <u>2.77</u> <u>2.81</u> <u>2.80</u>	6-11-97	CR
	FUNCTION		6-12-97	RP
660	PACK			

Remington Test Lab, Ilion, N.Y.

Centroidal distance calculations for Rifle # C6666077
9 Jun 1997

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: .0336667
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: -.158333
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .161873

THE AMR FOR THIS RIFLE IS: .9903

CENTROIDAL DISTANCES

0 TO	1	.151845
1 TO	2	.213771
1 TO	3	.319038


2+ <----POA
1
3

PATTERN #: ☐ 1 ☐
 POA TO CENTROID: .151
 MIN RADIUS : .287
 MEAN RADIUS : .577
 MAX RADIUS : .920
 CENTROID X : -.016
 CENTROID Y : -.151

9 Jun 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/C66666077

CENTERFIRE PATTERN # 1



OF SHOTS= 5

IN CIRCLE

HS= 1.24

2

VS= 1.23

5

GS= 1.43


5

PATTERN #: ☐ 2 ☐
 POA TO CENTROID: .109
 MIN RADIUS : 1.022
 MEAN RADIUS : 1.324
 MAX RADIUS : 1.965
 CENTROID X : -.099
 CENTROID Y : .046

9 Jun 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/C66666077

CENTERFIRE PATTERN # 2



OF SHOTS= 5

IN CIRCLE

HS= 3.13

0

VS= 1.80

0

GS= 3.20


4

PATTERN #: ☐ 3 ☐
POA TO CENTROID: .428
MIN RADIUS : .297
MEAN RADIUS : 1.070
MAX RADIUS : 1.918
CENTROID X : .216
CENTROID Y : -.370

9 Jun 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/C66666077

CENTERFIRE PATTERN # 3



OF SHOTS= 5

IN CIRCLE

HS= 3.35

1

VS= 1.51

3

GS= 3.50

3

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# + .50#

3.00# + .75#

4.00# + 1.00#

SERIAL NO. C6666077DATE 4-16-97

TESTER _____

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.67	2.43	2.52		MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.61	2.41	2.54		
PULL #3	2.50	2.41	2.54		
PULL #4	2.55	2.60	2.32		
PULL #5	2.65	2.54	2.50		
TOTAL	12.98	12.39	12.42		
AVG.	2.60	2.48	2.48		

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.26	3.31		
PULL #2	3.47	3.48		
PULL #3	3.45	2.88		
PULL #4	3.39	3.51		
PULL #5	3.17	3.32		
TOTAL	16.74	16.50		
AVG.	3.35	3.30		

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.09	4.06		4.11
PULL #2	3.98	4.13		3.91
PULL #3	4.05	4.11		3.96
PULL #4	3.95	4.06		3.97
PULL #5	4.14	3.92		4.01
TOTAL	20.21	20.28		19.96
AVG.	4.04	4.06		3.99