

UPC



C6666138

ORDER NO. 25705

BARREL LENGTH 24"

CAPACITY * 6

*INCLUDES 1 IN CHAMBER

ISRAELI GUNS

IS-B-YLS

GUN SERIAL # C6666138

OP. #	OP. NAME	READINGS	DATE	INITIAL
575 & 580	Assemble Action and Stock			
600	Proof			
607	Check Headspace			
610	Dis-assemble Gun			
612	Magnaflux Barrel Action			
	Magnaflux Bolt			
615	Rollmark Caliber			
617	Drill and Tap Sight Holes		3/20/87	WJT
618	Polish Barrel		3/20/87	WJD
620	Apply Coatings (Barrel Action)			
	Apply Coating (Bolt)			
625	Final Assembly A) Clean inside of Bolt Assembly			
	B) Inspect Rear Firing Pin Hole for Chamfer in Bolt Head			
	C) Inspect Ejector Hole for Chamfer			
	D) Oil Firing Pin Ass'y			
	E) Adjust Trigger Pull to Min Setting and Stake			

OP. #	OP. NAME	READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE	<u>4</u> <u>4</u> <u>4</u>	<u>5-8-97</u>	<u>GW</u>
CONT.				
	G) SAFETY OFF FORCE	<u>13</u> <u>3</u> <u>3</u>	<u>5-8-97</u>	<u>GW</u>
	H) TRIGGER PULL TEST & RETAINABILITY			
	I) FIRING PIN INDENT	<u>22</u> <u>22.5</u> <u>23</u>	<u>5-8-97</u>	<u>GW</u>
	J) ASSEMBLE STOCK			
	K) ASSEMBLE SWIVEL STUDS		<u>6-25-97</u>	<u>RP</u>
	L) ATTACH FRONT AND REAR SIGHT ASSEMBLIES		<u>5-27-97</u>	<u>GW</u>
	M) IRON SIGHT ALIGNMENT		<u>5-27-97</u>	<u>GW</u>
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERER CONTAINER		<u>5-27-97</u>	<u>GW</u>
640	GALLERY TEST AND TARGET	<u>L-96</u> <u>R-54</u>	<u>6-23-97</u>	<u>KT</u>
	A) MALFUNCTIONS		<u>"</u>	<u>KT</u>
	B) PIERCED PRIMERS		<u>"</u>	<u>KT</u>
645	INSPECT FOR LIVE AMMO		<u>6-23-97</u>	<u>DES</u>
655	FINAL INSPECTION			
	A) HEADSPACE		<u>6-25-97</u>	<u>RP</u>
	B) TRIGGER PULL	<u>2.79</u> <u>2.82</u> <u>2.86</u> <u>2.61</u> <u>2.71</u>	<u>6-25-97</u>	<u>CR</u>
	FUNCTION		<u>6-25-97</u>	<u>RP</u>
660	PACK			

Remington Test Lab, Ilion, N.Y.

Centroidal distance calculations for Rifle # C6666138
23 Jun 1997

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: $-.343333$
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: $.013$
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: $.343579$

THE AMR FOR THIS RIFLE IS: $.7897$

CENTROIDAL DISTANCES

0 TO 1	.438092
1 TO 2	.334646
1 TO 3	.118186


3 2+ <----POA

PATTERN #: ☐ 1 ☐
 POA TO CENTROID: .438
 MIN RADIUS : .283
 MEAN RADIUS : .639
 MAX RADIUS : 1.005
 CENTROID X : -.438
 CENTROID Y : -.009

23 Jun 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/c6666138

CENTERFIRE PATTERN # 1



OF SHOTS= 5

IN CIRCLE

HS= 1.01
 VS= 1.70
 GS= 1.98


2
 4
 5

PATTERN #: ☐ 2 ☐
 POA TO CENTROID: .117
 MIN RADIUS : .127
 MEAN RADIUS : .932
 MAX RADIUS : 1.831
 CENTROID X : -.106
 CENTROID Y : -.051

23 Jun 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/c66666138

CENTERFIRE PATTERN # 2



OF SHOTS= 5

IN CIRCLE

HS= 1.39

1

VS= 2.67

3

GS= 2.67


4

PATTERN #: 3
 POA TO CENTROID: .496
 MIN RADIUS : .449
 MEAN RADIUS : .798
 MAX RADIUS : 1.230
 CENTROID X : -.486
 CENTROID Y : .099

23 Jun 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/c66666138

CENTERFIRE PATTERN # 3



OF SHOTS= 5

IN CIRCLE

HS= 2.38

1

VS= .70

3

GS= 2.38

5

SWS TRIGGER PULL TEST

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# ± .50#

3.00# ± .75#

4.00# ± 1.00#

SERIAL NO. C6666/38

DATE _____

TESTER C.F.

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#	COMMENTS
PULL #1	2.53	2.58	2.62	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.69	2.48	2.43	
PULL #3	2.62	2.56	2.61	
PULL #4	2.71	2.60	2.59	
PULL #5	2.43	2.58	2.56	
TOTAL	12.98	12.80	12.81	
AVG.	2.60	2.56	2.56	

	3.00# INITIAL	3.00# AFTER 20 CYCLES	COMMENTS
PULL #1	3.20	3.07	
PULL #2	3.21	3.17	
PULL #3	3.17	3.00	
PULL #4	3.08	3.19	
PULL #5	3.14	3.31	
TOTAL	15.80	15.74	
AVG.	3.16	3.15	

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.17	4.15		4.07
PULL #2	3.98	4.08		4.04
PULL #3	4.13	4.12		4.08
PULL #4	4.03	3.83		4.06
PULL #5	3.99	4.05		4.05
TOTAL	20.30	20.23		20.30
AVG.	4.06	4.05		4.06

Do Not Use

VERY IMPORTANT: Instruction Book enclosed to assure safe use of this firearm.

Remington®

MODEL 700™ M24

BOLT ACTION CENTERFIRE RIFLE

24" BARREL 7.62 NATO 6*

Reg. U.S. Pat. & Tm. Off. Marca Registrada. Marque Déposée.

C6666138

40 ORDER NO.

25705

26PR



5705 C6666138

ORDER 25705

MODEL 700™ M24

UPC



ORDER 25705

MODEL 700™ M24

UPC



SERIAL NO.



C6666138

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

GREEN ENVELOPE CONTAINING:

- INSTRUCTION BOOK
- PRODUCT OWNER'S CARD
- MUSEUM/COUNTRY STORE FLIER
- REMINGTON AUTHORIZED GUNSMITHS

46 FORM

