

UPC



C6702927

ORDER NO. 25705

BARREL LENGTH 24"

CAPACITY * 6

*INCLUDES 1 IN CHAMBER

Remington Test Lab, Ilion, N.Y.

Centroidal distance calculations for Rifle # C6702927
3 Nov 1997

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: -.215333
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: -.0236667
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .21663

THE AMR FOR THIS RIFLE IS: 1.036

CENTROIDAL DISTANCES

0 TO 1	.0970824
1 TO 2	.190539
1 TO 3	.403714

3 2 † <----POA


PATTERN #: ☐ 1 ☐

POA TO CENTROID: .097
MIN RADIUS : .407
MEAN RADIUS : .970
MAX RADIUS : 1.407
CENTROID X : -.031
CENTROID Y : -.092

3 Nov 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/C6702927

CENTERFIRE PATTERN # 1



OF SHOTS= 5

IN CIRCLE

HS= 1.94
VS= 2.27
GS= 2.58

1
2
5

PATTERN #: ☐ 2 ☐

POA TO CENTROID: .195

MIN RADIUS : .552

MEAN RADIUS : 1.182

MAX RADIUS : 1.407


CENTROID X : -.195

CENTROID Y : .005

3 Nov 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/C6702927

CENTERFIRE PATTERN # 2



OF SHOTS= 5

IN CIRCLE

HS= 2.54

0

VS= 1.33

1

GS= 2.69

5


PATTERN #: ☐ 3 ☐

POA TO CENTROID: .420
MIN RADIUS : .309
MEAN RADIUS : .955
MAX RADIUS : 1.950
CENTROID X : -.420
CENTROID Y : .016

3 Nov 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/C6702927

CENTERFIRE PATTERN # 3



OF SHOTS= 5

IN CIRCLE

HS= 3.04

2

VS= 1.18

3

GS= 3.18

4

GUN SERIAL # C 6702927

OP. #	OPERATION NAME	READINGS	DATE	INITI
575 & 580	ASSEMBLE ACTION AND STOCK			
600	PROOF			
607	CHECK HEADSPACE			
610	DIS-ASSEMBLE GUN			
612	MAGNAFLUX BARREL ACTION			
	MAGNAFLUX BOLT			
615	ROLLMARK CALIBER			
617	DRILL AND TAP SIGHT HOLES			
618	POLISH BARREL			
620	APPLY COATINGS (BARREL ACTION)			
	(BOLT)			
625	FINAL ASSEMBLY A) CLEAN INSIDE OF BOLT ASSEMBLY			
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD			
	C) INSPECT EJECTOR HOLE FOR CHAMFER			
	D) OIL FIRING PIN ASSEMBLY			
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE			

625	F) SAFETY ON FORCE	<u>6</u> <u>6</u> <u>7</u>	10-29-97	C/C
CONT.	G) SAFETY OFF FORCE	<u>2</u> <u>3</u> <u>2</u>	10-29-97	C/C
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT	<u>.021</u> <u>.021</u> <u>.022</u>	10-29-97	C/C
	J) ASSEMBLE STOCK		10-28-97	RW
	K) ASSEMBLE SWIVEL STUDS		11/7/97	RP
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		10-28-97	RW
	M) IRON SIGHT ALIGNMENT		10-28-97	RW
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		10-28-97	RW
640	GALLERY TEST AND TARGET	L81 R69	11/3/97	PB
	A) MALFUNCTIONS		11/3/97	PB
	B) PIERCED PRIMERS		11/3/97	PB
645	INSPECT FOR LIVE AMMO		11/3/97	1A
655	FINAL INSPECTION A) HEADSPACE		11/7/97	RP
	B) TRIGGER PULL	<u>2.55</u> <u>2.58</u> <u>2.61</u> <u>2.62</u> <u>2.44</u>	11-5-97	CR
	C) FUNCTION		11/7/97	RP
660	PACK			

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# ± .50#

3.00# ± .75#

4.00# ± 1.00#

SERIAL NO. C6702927

DATE 10-22-97

TESTER Tm

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#	COMMENTS
PULL #1	2.60	2.69	2.60	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.62	2.67	2.58	
PULL #3	2.67	2.52	2.50	
PULL #4	2.75	2.65	2.51	
PULL #5	2.65	2.70	2.45	
TOTAL	13.29	13.23	12.64	
AVG.	2.65	2.64	2.52	

	3.00# INITIAL	3.00# AFTER 20 CYCLES	COMMENTS
PULL #1	3.03	3.05	
PULL #2	3.04	3.07	
PULL #3	3.10	3.12	
PULL #4	3.12	3.08	
PULL #5	3.07	2.99	
TOTAL	15.36	15.31	
AVG.	3.07	3.06	

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.06	3.94		3.99
PULL #2	4.09	3.95		3.98
PULL #3	4.13	4.14		4.03
PULL #4	3.97	4.01		4.01
PULL #5	3.99	3.98		3.98
TOTAL	20.24	20.01		19.99
AVG.	4.04	4.00		3.99

Do Not Use

Do Not Use

SERIAL NO.



C6702927

ORDER 25705
MODEL 700™ M24

UPC



ORDER 25705
MODEL 700™ M24

UPC



Remington®

MODEL 700™ M24

BOLT ACTION CENTERFIRE RIFLE

24" BARREL 7.62 NATO 6*

Reg. U.S. Pat. & Tm. Off. Marca Registrada. Marque Deposee.



5705 C6702927

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

GREEN ENVELOPE CONTAINING:

- INSTRUCTION BOOK
- PRODUCT OWNER'S CARD
- MUSEUM/COUNTRY STORE FLIER
- REMINGTON AUTHORIZED GUNSMITHS

46 FORM

