

C6225561

MODEL 700TM M24

Model **SMS** TM

Action

Barrel Length

Capacity

Order No. **5716**

*Includes 1 in chamber.

Remington[®]

Serial Number: C622556 1

Model: 700



RE00052605

SNIPER WEAPON SYSTEM - UNIQUE STATISTICAL INFORMATION

FIREARM SERIAL NUMBER / DATASET NAME: C6225561.___0
FILE DATE AND TIME: 10/15/2002 14:04


THE FOLLOWING DATA IS ALL REPORTED IN UNITS OF INCHES

The Average X Centroid of the Five Target Set:	-0.125
The Average Y Centroid of the Five Target Set:	0.013
The Average Point of Impact of the Five Target Set:	0.126
The Average Mean Radius of the Five Target Set:	0.763
The Distance from POA to Centroid Target #1:	0.032
The Distance from Centroid Target #2 to Centroid Target #1:	0.092
The Distance from Centroid Target #3 to Centroid Target #1:	0.426
The Distance from Centroid Target #4 to Centroid Target #1:	0.248
The Distance from Centroid Target #5 to Centroid Target #1:	0.172

SERIAL NUMBER: C6225561. __0
TARGET NUMBER: 1
FILE DATE: 10/15/2002
FILE TIME: 14:04

POINT#	X	Y
1:	-0.213	-1.050
2:	0.111	-0.808
3:	0.874	-0.449
4:	0.768	-0.379
5:	0.167	-0.400
6:	0.144	0.031
7:	-0.442	0.127
8:	-0.854	0.868
9:	-0.184	0.972
10:	-0.053	1.062

X CENTROID: 0.032
Y CENTROID: -0.003
POA TO CENTROID: 0.032
HORZ SPREAD: 1.728
VERT SPREAD: 2.112
GROUP SPREAD: 2.173
MIN RADIUS: 0.117
MAX RADIUS: 1.242
MEAN RADIUS: 0.800
IN 1 IN DIAMETER: 3
IN 2 IN DIAMETER: 7
in 3 IN DIAMETER: 10




TARGET APPROX 1/2 SCALE

SERIAL NUMBER: C6225561.____0
TARGET NUMBER: 2
FILE DATE: 10/15/2002
FILE TIME: 14:04

X CENTROID: -0.042
Y CENTROID: 0.051
POA TO CENTROID: 0.066
HORZ SPREAD: 1.884
VERT SPREAD: 3.050
GROUP SPREAD: 3.585
MIN RADIUS: 0.052
MAX RADIUS: 2.084
MEAN RADIUS: 0.735
IN 1 IN DIAMETER: 4
IN 2 IN DIAMETER: 8
in 3 IN DIAMETER: 8

POINT#	X	Y
1:	0.878	-1.151
2:	0.053	0.998
3:	-1.006	1.899
4:	-0.362	0.195
5:	0.274	0.046
6:	0.173	-0.624
7:	-0.577	-0.229
8:	-0.040	-0.001
9:	0.059	-0.195
10:	0.126	-0.425




TARGET APPROX 1/2 SCALE

SERIAL NUMBER: C6225561.____0
TARGET NUMBER: 3
FILE DATE: 10/15/2002
FILE TIME: 14:04

POINT#	X	Y
1:	0.204	-1.200
2:	0.015	-0.682
3:	-0.077	-0.337
4:	0.586	-0.280
5:	0.584	0.208
6:	-0.192	0.702
7:	-0.519	0.660
8:	-0.816	0.882
9:	-1.534	0.765
10:	-1.739	1.167

X CENTROID: -0.349
Y CENTROID: 0.188
POA TO CENTROID: 0.396
HORZ SPREAD: 2.325
VERT SPREAD: 2.367
GROUP SPREAD: 3.062
MIN RADIUS: 0.501
MAX RADIUS: 1.700
MEAN RADIUS: 0.990
IN 1 IN DIAMETER: 0
IN 2 IN DIAMETER: 6
in 3 IN DIAMETER: 9




TARGET APPROX 1/2 SCALE

SERIAL NUMBER: C6225561.____0
TARGET NUMBER: 4
FILE DATE: 10/15/2002
FILE TIME: 14:04


POINT#	X	Y
1:	0.489	-0.739
2:	0.304	-0.401
3:	0.043	-0.079
4:	-0.064	-0.884
5:	-0.146	-0.513
6:	-0.829	-0.591
7:	-0.328	0.034
8:	0.021	0.781
9:	-0.845	0.929
10:	0.065	-0.450

X CENTROID: -0.129
Y CENTROID: -0.191
POA TO CENTROID: 0.231
HORZ SPREAD: 1.334
VERT SPREAD: 1.813
GROUP SPREAD: 2.136
MIN RADIUS: 0.205
MAX RADIUS: 1.330
MEAN RADIUS: 0.627
IN 1 IN DIAMETER: 5
IN 2 IN DIAMETER: 9
in 3 IN DIAMETER: 10



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: C6225561.____0	POINT#	X	Y
TARGET NUMBER: 5	1:	-0.151	-1.574
FILE DATE: 10/15/2002	2:	0.402	-0.646
FILE TIME: 14:04	3:	-0.065	-0.434
	4:	0.297	0.139
X CENTROID: -0.139	5:	-0.286	0.141
Y CENTROID: 0.019	6:	-0.116	0.365
POA TO CENTROID: 0.140	7:	-0.256	0.745
HORZ SPREAD: 1.240	8:	-0.414	1.007
VERT SPREAD: 2.581	9:	-0.838	0.277
GROUP SPREAD: 2.594	10:	0.039	0.167
MIN RADIUS: 0.191			
MAX RADIUS: 1.593			
MEAN RADIUS: 0.664			
# IN 1 IN DIAMETER: 5			
# IN 2 IN DIAMETER: 8			
# in 3 IN DIAMETER: 9			



TARGET APPROX 1/2 SCALE

Final Inspection

In: C6225.564

DATE REC'D: 9/19/82

DATE RET'D:

EDITOR: RW

Item:

BARREL ASSY.

- ☒ BARREL
- ☒ RECEIVER
- ☒ FRONT SIGHT BLOCK
- ☒ REAR SIGHT BLOCK
- ☒ SCREWS
- ☒ FINISH

Scope Assy.

- ☐ Scope
- ☐ Scope Rings
- ☐ Mounting Screws
- ☒ Mounting Base
- ☒ Screws
- ☐ Finish
- ☐ Looseness
- ☐ CLARITY

Misc.

- ☐ DD-250
- ☐ BAR CODE
- ☐ PACKAGING

Item:

STOCK ASSY.

- ☒ STOCK
- ☒ SLING SWIVEL STUDS
- ☐ ADJUSTABLE BUTT PLATE
- ☒ LOCK NUTS
- ☒ BARREL CLEARANCE
- ☒ COLOR/FINISH

Systems Case

- ☐ Scope Case
- ☐ IRON SIGHTS
- ☐ Deployment Kit

Trigger

- ☒ SAFETY OPERATION
- ☒ SET

Comments:

M-24 INSPECTION CHECKLIST
CONTRACT #: DAAE-20-97-C-242

R & E NUMBER	52605		
SERIAL NUMBER	C6225561		
LOG-IN DATE	9/19/02		
INSPECT AND VERIFY:			
OPERATION #	OPERATION NAME	DATE	INITIAL
550	DIS-ASSEMBLE GUN	9/20/02	RL
560 A	RE-BARREL	9/20/02	RA
B	DRILL AND TAP	9-21-02	AC
575	ASSEMBLE	9/24/02	RL
600	PROOF	9-24-02	AC
605	CHECK HEADSPACE	9-24-02	AC
610	DIS-ASSEMBLE GUN	9/24/02	RL
612	MAGNAFLUX	RL	
615	ROLLMARK CALIBER	9/27/02	TRW
618	ROTO-BLAST	9/30/02	RO
620	APPLY COATINGS	10-5	TA
625 A	FINAL ASSEMBLY	10/10/02	RL
B	TRIGGER PULL TEST		
C	SAFETY "ON" FORCE		
D	SAFETY "OFF" FORCE		
E	FIRING PIN INDENT		
640	TARGET	10-14-02	TRW
655	FINAL INSPECT	10-14-02	RL
660	PACK	10-16-02	RA
		SHIP DATE	
	QAR INSPECTION DATE		

CONTRACT # DAAA21-87-C-0086

GUN SERIAL # C6225561

OP. #	OP. NAME	READINGS	DATE	INIT
575 & 580	Assemble Action and Stock	QUALITY AUDIT	4 12 89	RW
600	Proof		4 12 89	RW
607	Check Headspace		4 12 89	RW
610	Dis-assemble Gun		4 12 89	RW
612	Magnaflux Barrel Action		4/13/89	KCR
	Magnaflux Bolt		4/14/89	KCR
615	Rollmark Caliber		4/10/89	DS
617	Drill and Tap Sight Holes		4 14 89	LB
618	Polish Barrel RB		4 14 89	BT
620	Apply Coatings (Barrel Action)		4/19/89	TJA
	Apply Coating (Bolt)			
625	Final Assembly A) Clean inside of Bolt Assembly		5/4/89	RW
	B) Inspect Rear Firing Pin Hole for Chamfer in Bolt Head		5/4/89	RW
	C) Inspect Ejector Hole for Chamfer		5/4/89	RW
	D) Oil Firing Pin Ass'y		5/4/89	RW
	E) Adjust Trigger Pull to Min Setting and Stake		5/9/89	WB

op. #	OP. NAME	READINGS					DATE	INIT
625 cont.	F) Safety On Force	5	5	5			5/10/89	9U
	G) Safety Off Force	3	3	3			5/10/89	8U
	H) Trigger Pull Test & Retainability						5/9/89	W3
	I) Firing Pin Indent	.020	.020	.020			5/10/89	9U
	J) Assemble Stock						5/11/89	RLW
	K) Assemble Swivel Studs						15 May 89	98
	L) Attach Front and Rear Sight Assemblies						5/11/89	RLW
	M) Iron Sight Alignment						5/11/89	RLW
	N) Detach Front & Rear Sights & place in numbered container						5/11/89	RLW
	O) Attach Scope to Rifle						5/11/89	9U
	P) Detach & Attach Scope 20 Times						5/11/89	9U
640	Gallery Target & Test	62R	91L				5/11/89	DH
	A) Time						5/11/89	DH
	B) Malfunctions						5/11/89	DH
	C) Pierced Primers						5/11/89	DH
	D) Optical Clarity of Scope						5/11/89	DH
645	Inspect for Live Ammo						5/11/89	DH
655	Final Inspection							
	A) Headspace						15 May 89	98
	B) Trigger Pull	2.38	2.35	2.34	2.31	2.50	15 May 89	98
	C) Function						15 May 89	98
660	Pack						27 June 89	98

SWS TRIGGER PULL TEST

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS
2.50# + .50#
3.00# + .75#
4.00# + 1.00#

C6225561
SERIAL NO. _____
DATE 5/9/89
TESTER WB

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.33	2.44	2.29	2.38	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.46	2.36	2.36	2.35	
PULL #3	2.46	2.25	2.25	2.34	
PULL #4	2.35	2.41	2.45	2.31	
PULL #5	2.33	2.46	2.29	2.50	
TOTAL	12.13	11.92	11.64	11.88	
AVG.	2.42	2.38	2.33	2.376	

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.02	3.07		
PULL #2	3.09	3.04		
PULL #3	3.10	3.14		
PULL #4	3.04	3.18		
PULL #5	3.10	3.18		
TOTAL	15.35	15.61		
AVG.	3.07	3.12		

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.36	4.07		4.34
PULL #2	4.06	3.95		4.38
PULL #3	4.27	4.14		4.34
PULL #4	4.24	4.07		4.31
PULL #5	4.24	4.17		4.15
TOTAL	21.17	20.40		21.52
AVG.	4.23	4.08		4.31

CENTROIDAL DISTANCE CALCULATIONS
FOR RIFLE # C6225561
15 May 1989

CENTROIDAL DISTANCES

0 TO	1	.676764
1 TO	2	.270852
1 TO	3	.793738
1 TO	4	.321801
1 TO	5	.375826


$\frac{AL}{3} +$ <----POA

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: -.398
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: .255
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .472683
THE AMR FOR THIS RIFLE IS: .7838

11 May 1989

FILE:/PATTERNING/CENTERFIRE_PATT/08225561

CENTERFIRE PATTERNS # 1



OF SHOTS- 10

IN CIR

1 in = 4

2 in = 8

3 in = 10

HS= 1.700

VS= 1.910


GS= 2.500

PATTERN #	1	2	3
SHOTS (BEST OF)	10	9	8
MAXIMUM X	.774	.511	.416
MINIMUM X	-.926	-.840	-.935
MAXIMUM Y	.996	.776	.676
MINIMUM Y	-.914	-.803	-.532
CENTROID X	-.485	-.571	-.476
CENTROID Y	.472	.361	.461
POA TO CENTROID in.	.676	.675	.663
MIN RADIUS	.128	.074	.120
MEAN RADIUS	.672	.599	.524
MAX RADIUS	1.261	1.101	.938
HORIZONTAL SPREAD	1.700	1.351	1.351
VERTICAL SPREAD	1.910	1.579	1.208
EXTREME SPREAD	2.500	1.982	1.490
NUMBER IN ONE INCH CIRCLE =	4		
NUMBER IN TWO INCH CIRCLE =	8		
NUMBER IN THREE INCH CIRCLE =	10		

11 May 1989

FILE:/PATTERNING/CENTERFIRE_PATT/08225561

CENTERFIRE PATTERNS # 2



OF SHOTS= 10

IN CIR

1 in = 3

2 in = 6

3 in = 10

HE= 1.977

VB= 2.234

GB= 2.314

CENTROID *


PATTERN #	:	2		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.366	.864	.867
MINIMUM X	:	-.611	-.459	-.456
MAXIMUM Y	:	.967	1.023	.872
MINIMUM Y	:	-1.267	-1.211	-1.080
CENTROID X	:	-.541	-.693	-.696
CENTROID Y	:	.207	.151	.302
POA TO CENTROID in.	:	.579	.709	.759
MIN RADIUS	:	.349	.323	.194
MEAN RADIUS	:	.886	.788	.700
MAX RADIUS	:	1.455	1.211	1.306
HORIZONTAL SPREAD	:	1.977	1.323	1.323
VERTICAL SPREAD	:	2.234	2.234	1.952
EXTREME SPREAD	:	2.314	2.249	2.099
NUMBER IN ONE INCH CIRCLE	=		3	
NUMBER IN TWO INCH CIRCLE	=		6	
NUMBER IN THREE INCH CIRCLE	=		10	

11 May 1985

FILE:/PATTERNING/CENTERFIRE_PATT/06225561

CENTERFIRE PATTERNS # 3

POB



OF SHOTS = 10

IN CIR

1 in = 3

2 in = 7

3 in = 10

HS = 1.559

VS = 2.217

GS = 2.283


CENTROID *

PATTERN #	:	3		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	.971	.891	.792
MINIMUM X	:	-.728	-.792	-.783
MAXIMUM Y	:	.971	.833	.908
MINIMUM Y	:	-1.246	-.452	-.377
CENTROID X	:	-.237	-.157	-.058
CENTROID Y	:	-.282	-.144	-.219
POB TO CENTROID in.	:	.369	.213	.226
MIN RADIUS	:	.112	.269	.266
MEAN RADIUS	:	.777	.713	.684
MAX RADIUS	:	1.443	.999	.963
HORIZONTAL SPREAD	:	1.699	1.683	1.575
VERTICAL SPREAD	:	2.217	1.285	1.285
EXTREME SPREAD	:	2.293	1.985	1.699
NUMBER IN ONE INCH CIRCLE	=		3	
NUMBER IN TWO INCH CIRCLE	=		7	
NUMBER IN THREE INCH CIRCLE	=		10	

11 May 1989

FILE:/PATTERNING/CENTERFIRE_PATT/C6225561

CENTERFIRE PATTERNS # 4



OF SHOTS = 10

IN CIR

1 in = 3

2 in = 6

3 in = 9

MOI = 0.248

VS = 2.248


GS = 2.884

PATTERN #	:	4		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.077	.947	1.025
MINIMUM X	:	-1.172	-.677	-.599
MAXIMUM Y	:	1.066	.946	.809
MINIMUM Y	:	-1.182	-1.302	-1.183
CENTROID X	:	-.519	-.389	-.467
CENTROID Y	:	.152	.272	.153
POA TO CENTROID in.	:	.541	.475	.492
MIN RADIUS	:	.081	.254	.115
MEAN RADIUS	:	.848	.787	.707
MAX RADIUS	:	1.594	1.309	1.254
HORIZONTAL SPREAD	:	2.249	1.624	1.624
VERTICAL SPREAD	:	2.248	2.248	1.993
EXTREME SPREAD	:	2.884	2.300	2.070
NUMBER IN ONE INCH CIRCLE	=		3	
NUMBER IN TWO INCH CIRCLE	=		6	
NUMBER IN THREE INCH CIRCLE	=		9	

11 May 1989

FILE:/PATTERNING/CENTERFIRE_PATT/08225561

CENTERFIRE PATTERNS # 5



* OF SHOTS- 12

IN CIR

1 in = 4

2 in = 8

3 in = 8

ME= 2.778

MS= 2.176

GS= 2.782

CENTROID *

PATTERN #	:	5		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	.946	.742	.682
MINIMUM X	:	-1.832	-.504	-.564
MAXIMUM Y	:	.619	.660	.471
MINIMUM Y	:	-1.557	-1.516	-.282
CENTROID X	:	-.208	-.004	.056
CENTROID Y	:	.726	.685	.874
POA TO CENTROID in.	:	.755	.685	.876
MIN RADIUS	:	.187	.185	.237
MEAN RADIUS	:	.736	.589	.438
MAX RADIUS	:	1.870	1.591	.684
HORIZONTAL SPREAD	:	2.778	1.246	1.246
VERTICAL SPREAD	:	2.176	2.176	.753
EXTREME SPREAD	:	2.792	2.177	1.270
NUMBER IN ONE INCH CIRCLE	=		4	
NUMBER IN TWO INCH CIRCLE	=		8	
NUMBER IN THREE INCH CIRCLE	=		8	

RECEIVING AND ESTIMATING REPORT

COMMENTS

ORDER
R 96-09648

INITIAL CUSTOMER ORDER NO.

JJM

M-24 SNIPER

DATE RECEIVED 04/08/96	DATE OPENED 04/08/96	DATE CODE 0J 7-89	SERIAL NUMBER C6225561	NEW SERIAL NUMBER	MODEL AND GRADE 700 7.62 NATO
ACCESSORIES W/STUDS			SCOPE BASE		

FROM:

SHIP TO:

COMMANDER
B CO 1ST SPECIAL FORCES
COMMAND 3RD BN - BOX 339502
FT LEWIS WA 98433

COMMANDER
B CO 1ST SPECIAL FORCES
COMMAND 3RD BN - BOX 339502
FT LEWIS WA 98433

CUST NO: 141138 C.O.D.L

ACCOUNT NUMBER	ACCOUNT NUMBER N/C	WRITE ☐	PROM. DATE	ESTIMATED	VIA UPS
----------------	--------------------	--------------------------------	------------	-----------	------------

GUN CONDITION

- ☐ NEW
- ☐ LIGHTLY WORN
- ☐ WORN
- ☐ VERY WORN
- ☐ UNREPAIRABLE
- ☐ MARRED

REPAIR CHARGE

EXCISE

TAX

INSURANCE

UPS

PARCEL POST

TOTAL

CUSTOMER CONCERN	AMMO	FUNCTION	FINISH	ACCURACY	FIT	INSPECT
CYCLE	A1	B1				
TRIGGER GROUP		B2			E1	F1
BOLT ASSY.		B3			E2	F2
BARREL ASSY.		B4		D1	E3	F3
REC. ASSY.		B5		D2	E4	F4
WOOD			C1	D3	E5	F5
METAL			C2			

MAIN FAULT

PARTS

Barrel - 96003

COMMENTS

Repower Coat Trigger Guard
Assy, Front & Rear Sight Bases
Refine Scope Based Swivel
Studs

REPAIRMAN RM	PROOF ✓	CLEAN ✓	TEST ✓	TARGET ✓	PATTERN
GALLERY TESTER RM	DATE 4/15/96	DATE 4/23/96	DATE 4/23/96	DATE 4/23/96	DATE

OFFICE COPY

RD6925 REV. 1/94

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER
KINZER V. REMINGTON

M2400051563

CONTRACT # DAAA21-87-C-0086

Barrel

GUN SERIAL # C6225561

OP. #	OP. NAME	READINGS	DATE	INITIAL
575 & 580	Assemble Action and Stock		4/13/96	RW
600	Proof		4/15/96	RW
607	Check Headspace		4/15/96	RW
610	Dis-assemble Gun		4/15/96	RW
612	Magnaflux Barrel Action			
	Magnaflux Bolt			
615	Rollmark Caliber			
617	Drill and Tap Sight Holes			
618	Polish Barrel			
620	Apply Coatings (Barrel Action)			
	Apply Coating (Bolt)			
625	Final Assembly A) Clean inside of Bolt Assembly		4/23/96	RW
	B) Inspect Rear Firing Pin Hole for Chamfer in Bolt Head		4/23/96	RW
	C) Inspect Ejector Hole for Chamfer		4/23/96	RW
	D) Oil Firing Pin Ass'y		4/23/96	RW
	E) Adjust Trigger Pull to Min Setting and Stake			

op. #	OP. NAME	READINGS			DATE	INIT
625 cont.	F) Safety On Force					
	G) Safety Off Force					
	H) Trigger Pull Test & Retainability					
	I) Firing Pin Indent					
	J) Assemble Stock					
	K) Assemble Swivel Studs					
	L) Attach Front and Rear Sight Assemblies					
	M) Iron Sight Alignment					
	N) Detach Front & Rear Sights & place in numbered container					
	O) Attach Scope to Rifle					
	P) Detach & Attach Scope 20 Times					
640	Gallery Target & Test				4/23/96	Ru
	A) Time					
	B) Malfunctions					
	C) Pierced Primers					
	D) Optical Clarity of Scope					
645	Inspect for Live Ammo				4/23/96	Ru
655	Final Inspection					
	A) Headspace				4/24/96	Ru
	B) Trigger Pull				4/24/96	Ru
	C) Function				4/24/96	Ru
660	Pack					

Final Inspection

Sn: C6225561

DATE REC'D: 4/8/96

DATE RET'D:

AUDITOR: RW

Item:

Barrel Assy.

☒ BARREL☒ RECEIVER☒ FRONT SIGHT BLOCK☒ REAR SIGHT BLOCK☒ SCREWS☒ FINISH

Scope Assy.

☐ Scope☐ Scope Rings☐ Mounting Screws☒ Mounting Base☒ Screws☐ Finish☐ Looseness☐ CLARITY

Misc.

☐ DD-250☐ BAR CODE☐ PACKAGING

Item:

Stock Assy.

☒ Stock☒ Sling Swivel Studs☒ ADJUSTABLE BUTT PLATE☒ LOCK NUTS☒ BARREL CLEARANCE☒ COLOR/FINISH

Systems Case

☐ Scope Case☐ Iron SIGHTS☐ Deployment Kit

Trigger

☒ SAFETY OPERATION☒ SET

Comments:

CENTROIDAL DISTANCE CALCULATIONS
FOR RIFLE # 06225561
22 Feb 1988

CENTROIDAL DISTANCES

0 TO 1	.672887
1 TO 2	.299107
1 TO 3	.439281
1 TO 4	.0642806
1 TO 5	.293019


3
+ 3rd <----POA

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: .474
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: .3596
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .594969
THE AMR FOR THIS RIFLE IS: 1.058

22 Feb 1988

FILE:/PATTERNING/CENTERFIRE_PATT/06225561.1

CENTERFIRE PATTERNS # 1



OF SHOTS= 10

IN CIR

1 in = 1

2 in = 5

3 in = 7

HS= 2.561

VS= 2.992


GS= 3.029

PATTERN #	:	1		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.042	.968	.768
MINIMUM X	:	-1.519	-1.593	-1.376
MAXIMUM Y	:	1.523	1.360	1.390
MINIMUM Y	:	-1.469	-1.081	-1.051
CENTROID X	:	.571	.645	.845
CENTROID Y	:	.356	.519	.489
POB TO CENTROID in.	:	.673	.828	.976
MIN RADIUS	:	.391	.353	.173
MEAN RADIUS	:	1.041	.932	.763
MAX RADIUS	:	1.614	1.612	1.731
HORIZONTAL SPREAD	:	2.561	2.561	2.144
VERTICAL SPREAD	:	2.992	2.441	2.441
EXTREME SPREAD	:	3.029	2.786	2.602
NUMBER IN ONE INCH CIRCLE	=		1	
NUMBER IN TWO INCH CIRCLE	=		5	
NUMBER IN THREE INCH CIRCLE	=		7	

22 Feb 1988

FILE:/PATTERNING/CENTERFIRE_PATT/062255B1.1

CENTERFIRE PATTERNS # 2




OF SHOTS = 10
IN CIR
1 in = 1
2 in = 2
3 in = 7
HS = 2.663
VS = 3.867
GS = 3.878

PATTERN #	2	9	8
SHOTS (BEST OF)	10	9	8
MAXIMUM X	1.243	1.223	1.236
MINIMUM X	-1.420	-1.440	-1.427
MAXIMUM Y	1.693	1.451	1.266
MINIMUM Y	-2.174	-1.477	-1.295
CENTROID X	.360	.380	.367
CENTROID Y	.144	.386	.204
POA TO CENTROID in.	.388	.541	.420
MIN RADIUS	.197	.101	.142
MEAN RADIUS	1.311	1.174	1.145
MAX RADIUS	2.181	1.576	1.539
HORIZONTAL SPREAD	2.663	2.663	2.663
VERTICAL SPREAD	3.867	2.928	2.561
EXTREME SPREAD	3.878	3.003	3.003
NUMBER IN ONE INCH CIRCLE =	1		
NUMBER IN TWO INCH CIRCLE =	2		
NUMBER IN THREE INCH CIRCLE =	7		

22 Feb 1988

FILE:/PATTERNING/CENTERFIRE_PATT/08225581.1

CENTERFIRE PATTERNS # 3



OF SHOTS= 10

IN CIR

1 in = 3

2 in = 10

3 in = 10

HS= 1.212

VS= 1.335

GS= 1.335


CENTROID #

PATTERN #	3	9	8
SHOTS (BEST OF)	10	9	8
MAXIMUM X	.672	.654	.481
MINIMUM X	-.539	-.558	-.476
MAXIMUM Y	.747	.739	.757
MINIMUM Y	-.588	-.505	-.487
CENTROID X	.449	.467	.385
CENTROID Y	.778	.695	.677
POA TO CENTROID in.	.898	.837	.779
MIN RADIUS	.249	.329	.146
MEAN RADIUS	.515	.481	.449
MAX RADIUS	.764	.740	.767
HORIZONTAL SPREAD	1.212	1.212	.957
VERTICAL SPREAD	1.335	1.244	1.244
EXTREME SPREAD	1.335	1.259	1.259
NUMBER IN ONE INCH CIRCLE =	3		
NUMBER IN TWO INCH CIRCLE =	10		
NUMBER IN THREE INCH CIRCLE =	10		

22 Feb 1900

FILE:/PATTERNING/CENTERFIRE_PATT/C8225581.1

CENTERFIRE PATTERNS # 4



OF SHOTS- 10

IN CIR

1 in = 1

2 in = 3

3 in = 7

HS= 2.806

VS= 2.834


GS= 3.139

PATTERN #	:	4		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.628	1.433	1.386
MINIMUM X	:	-1.178	-1.997	-1.044
MAXIMUM Y	:	1.197	1.265	1.069
MINIMUM Y	:	-1.637	-1.569	-1.400
CENTROID X	:	.635	.534	.501
CENTROID Y	:	.362	.490	.490
POA TO CENTROID in.	:	.731	* .584	.701
MIN RADIUS	:	.298		.420
MEAN RADIUS	:	1.294		1.091
MAX RADIUS	:	1.742	1.632	1.696
HORIZONTAL SPREAD	:	2.806	2.430	2.430
VERTICAL SPREAD	:	2.834	2.834	2.469
EXTREME SPREAD	:	3.139	2.984	2.771
NUMBER IN ONE INCH CIRCLE	=		1	
NUMBER IN TWO INCH CIRCLE	=		3	
NUMBER IN THREE INCH CIRCLE	=		7	

22 Feb 1988

FILE:/PATTERNING/CENTERFIRE_PATT/C8225561.J

CENTERFIRE PATTERNS # 5



OF SHOTS= 10

IN CIR

1 in = 1

2 in = 4

3 in = 6

HS= 1.375

VS= 3.260

GS= 3.265

PATTERN #	5	5	5
SHOTS (BEST OF)	10	9	8
MAXIMUM X	.593	.604	.632
MINIMUM X	-.781	-.716	-.688
MAXIMUM Y	1.722	1.736	1.736
MINIMUM Y	-1.538	-1.115	-1.115
CENTROID X	.355	.262	.262
CENTROID Y	.158	-.265	-.265
POA TO CENTROID in.	.389	.373	.373
MIN RADIUS	.435	.277	.277
MEAN RADIUS	1.190	.965	.965
MAX RADIUS	1.768	1.763	1.763
HORIZONTAL SPREAD	1.375	1.320	1.320
VERTICAL SPREAD	3.260	3.260	2.851
EXTREME SPREAD	3.265	3.265	2.939
NUMBER IN ONE INCH CIRCLE =	1	1	1
NUMBER IN TWO INCH CIRCLE =	4	4	4
NUMBER IN THREE INCH CIRCLE =	6	6	6

VERY IMPORTANT:
Instruction Book
enclosed to assure
safe use of this
firearm.



Remington®

MODEL 700™ H24

SERIAL NO.
C6225561

ORDER NO.
5716

Ø1

MADE IN ILION, N.Y. U.S.A. Reg. U.S. Pat. & Tm. Off. Marca Registrada Marque Deposee.



5716 C6225561

UPC



0 47700 25716 7