

66771226

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker




ORDER NO. **86470**

BARREL LENGTH **24"**

CAPACITY **6**

G6771226

UPC



BM FORM

INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL # G 6771226

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		7-14-08	PSW
430	ASSEMBLE TO STOCK		7-14-08	PSW
440	PROOF		7-14-08	J.P.D.
460	CHECK HEADSPACE		7-14-08	J.P.D.
470	DIS-ASSEMBLE ACTION		7-15-08	RTZ
472	SERIALIZE BOLT HANDLE		7-15-08	RTZ
475	DRILL AND TAP SIGHT HOLES		7-16-08	TRW
480	MAGNAFLUX BBL ACTION		7-21-08	BT
490	MAGNAFLUX BOLT			
500	ROLLMARK CALIBER		7/21/08	RT
520	GOFF BLAST BBL / REC			
542	APPLY COATINGS (BARREL ACTION)		7/22	CS
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY			
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD.			
	C) INSPECT EJECTOR HOLE FOR CHAMFER			
	D) OIL FIRING PIN ASSEMBLY		7-26-08	PSW
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE			

F004 REV 5/2006

560	F) SAFETY ON FORCE	2 LBS MIN 10 LBS MAX	<u>7</u>	<u>7</u>	<u>6.5</u>	7-30	TK		
CONT.									
	G) SAFETY OFF FORCE	2 LBS MIN	<u>6.5</u>	<u>7</u>	<u>7</u>	7-30	TK		
	H) TRIGGER PULL TEST AND RETAINABILITY								
	I) FIRING PIN INDENT	.020 MIN	<u>.021</u>	<u>.022</u>	<u>.022</u>				
	J) ASSEMBLE STOCK					7-26-08	PSN		
	K) ASSEMBLE SWIVEL STUDS					8-1-08	RZ		
	L) ATTACH FRONT AND REAR SIGHT ASSY'S					—			
	M) IRON SIGHT ALIGNMENT					—			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER					—			
640 & 650	FUNCTION TEST AND TARGET		(PASS)	FAIL					
			(PASS)	FAIL		7-28-08	TRW		
	MALFUNCTION		N/A						
		CORRECTION							
	MALFUNCTION								
	MALFUNCTION								
	MALFUNCTION		N/A						
		CORRECTION							
	MALFUNCTION								
	MALFUNCTION								
660	INSPECT FOR LIVE AMMO					7-28-08	TK		
670	FINAL INSPECTION A) HEADSPACE					8-1-08	RZ		
	B) TRIGGER PULL	+/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.62</u>	<u>2.63</u>	<u>2.69</u>	<u>2.58</u>	<u>2.58</u>	7-29-08	TRW
	C) FUNCTION					8-1-08	RZ		
690	PACK					8/2/08	Fm		

F004 REV 5/2006

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)
3.00 LBS (plus or minus 0.75 LBS)
4.00 LBS (plus or minus 1.00 LBS)

DATE July 16, 2008

TESTER S. Day

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	2.78	2.87		2.66	
PULL #2	2.81	2.82		2.71	
PULL #3	2.74	2.77		2.70	
PULL #4	2.74	2.80		2.63	
PULL #5	2.72	2.72		2.65	
TOTAL	1379	1398		1335	
AVERAGE	2.75	2.79		2.67	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	3.22	3.30		
PULL #2	3.18	3.22		
PULL #3	3.17	3.15		
PULL #4	3.18	3.15		
PULL #5	3.12	3.05		
TOTAL	1587	1622		
AVERAGE	3.17	3.24		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	4.12	4.47		4.08
PULL #2	4.19	4.32		4.05
PULL #3	4.06	4.26		4.02
PULL #4	4.00	4.20		4.02
PULL #5	4.05	4.23		4.06
TOTAL	2042	2148		2023
AVERAGE	4.08	4.29		4.04