

6778916

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker



BM FORM


ORDER NO. 86470

BARREL LENGTH 24"

CAPACITY 6

G6778916

UPC



INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL #

G 6778916

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		8-20-08	J.P.D.
430	ASSEMBLE TO STOCK		8-20-08	JP
440	PROOF		8-20-08	J.P.D.
460	CHECK HEADSPACE		8-20-08	J.P.D.
470	DIS-ASSEMBLE ACTION		8-20-08	J.P.D.
472	SERIALIZE BOLT HANDLE	MAGNA - FLUX	8-21-08	RSW
475	DRILL AND TAP SIGHT HOLES	AUG 22 2008	8-21-08	JP
480	MAGNAFLUX BBL ACTION	OPERATOR B.H.	8-22-08	BH
490	MAGNAFLUX BOLT		8-22-08	MR
500	ROLLMARK CALIBER		8/22/08	RT
520	GOFF BLAST BBL / REC		8-22-08	RG
542	APPLY COATINGS (BARREL ACTION)		8-26	
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		9-15-08	JP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		9-15-08	JP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		9-25-08	JP
	D) OIL FIRING PIN ASSEMBLY		1-22-09	J.P.D.
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		

F004 REV 5/2006


OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>4.0</u> <u>4.0</u> <u>4.0</u>	1-27-09	LN
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>6.0</u> <u>6.0</u> <u>6.0</u>	1-27-09	LN
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.024</u> <u>.024</u> <u>.024</u>	1-27-09	LN
	J) ASSEMBLE STOCK		1-22-09	LN
	K) ASSEMBLE SWIVEL STUDS		1-27-09	LN
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	1-26-09	TC
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		1-26-09	WV
670	FINAL INSPECTION A) HEADSPACE		1-27-09	LN
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.39</u> <u>2.48</u> <u>2.40</u> <u>2.55</u> <u>2.39</u>	1-26-09	LN
	C) FUNCTION		1-27-09	LN
690	PACK		2/12/09	Fm

F004 REV 5/2006

Trigger Profile [lbs,inch]

Profile: SWS
 GunType: Rifle
 Make: Remington
 Note: C Schults 1/22/2009

Model: M/24
 Serial No: Form #F005
 Trigger: 2.5 lbs ini +/- .50 lb




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	2.607	0.056	0.037	0.032	0.060		Set Trigger
2	2.499	0.056	0.036	0.032	0.059		Set Trigger
3	2.504	0.055	0.036	0.032	0.058		Set Trigger
4	2.500	0.055	0.036	0.032	0.059		Set Trigger
5	2.412	0.055	0.035	0.033	0.057		Set Trigger

A-250

Trigger Profile [lbs,inch]

Profile: SWS
 GunType: Rifle
 Make: Remington
 Note: C Schults 1/22/2009

Model: M/24
 Serial No: Form #F005
 Trigger: 2.5 lbs after 50 cycles+/- .50 lb




Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
2.404	0.057	0.037	0.031	0.059		Set Trigger
2.421	0.057	0.036	0.031	0.061		Set Trigger
2.391	0.056	0.036	0.032	0.059		Set Trigger
2.513	0.055	0.035	0.031	0.061		Set Trigger
2.469	0.054	0.034	0.032	0.059		Set Trigger

A-2.44

Trigger Profile [lbs,inch]

Profile SWS
 GunType: Rifle
 Make: Remington
 Note: C Schults 1/22/2009

Model: M/24
 Serial No: Form #F005
 Trigger: 3.0 lbs ini +/- .75 lb




Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
3.282	0.052	0.031	0.030	0.075		Set Trigger
3.290	0.053	0.031	0.030	0.076		Set Trigger
3.155	0.052	0.031	0.030	0.073		Set Trigger
3.180	0.051	0.030	0.030	0.072		Set Trigger
3.219	0.051	0.029	0.029	0.074		Set Trigger

A-3-22

Trigger Profile [lbs,inch]

Profile SWS
 GunType: Rifle
 Make: Remington
 Note: C Schults 1/22/2009

Model: M/24
 Serial No: Form #F005
 Trigger: 3.0 lbs after 20 cycles+/- .75 lb




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	3.232	0.056	0.035	0.030	0.075		Set Trigger
2	3.231	0.055	0.034	0.031	0.075		Set Trigger
3	3.201	0.055	0.034	0.031	0.074		Set Trigger
4	3.218	0.056	0.034	0.030	0.076		Set Trigger
5	3.288	0.056	0.034	0.030	0.076		Set Trigger

A.3.23

Trigger Profile [lbs,inch]

Profile SWS
 GunType: Rifle
 Make: Remington
 Note: C Schults 1/22/2009

Model: M/24
 Serial No: Form #F005
 Trigger: 4.0 lbs ini +/- 1.0 lb




Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
4.385	0.056	0.032	0.028	0.099		Set Trigger
4.390	0.057	0.032	0.027	0.103		Set Trigger
4.354	0.056	0.032	0.028	0.099		Set Trigger
4.323	0.057	0.032	0.028	0.101		Set Trigger
4.377	0.056	0.032	0.028	0.102		Set Trigger

A. 4.36

Trigger Profile [lbs,inch]

Profile: SWS
 GunType: Rifle
 Make: Remington
 Note: C Schults 1/22/2009

Model: M/24
 Serial No: Form #F005
 Trigger: 4.0 lbs after 20 cycles+/- 1.0 lb




	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	4.426	0.055	0.030	0.027	0.101		Set Trigger
2	4.353	0.054	0.030	0.028	0.099		Set Trigger
3	4.307	0.054	0.030	0.028	0.097		Set Trigger
4	4.319	0.055	0.031	0.028	0.099		Set Trigger
5	4.309	0.054	0.031	0.028	0.098		Set Trigger

A-4.34

Trigger Profile [lbs,inch]

Profile SWS
 GunType: Rifle
 Make: Remington
 Note: C Schults 1/22/2009

Model: M/24
 Serial No: Form #F005
 Trigger: reset to 2.5 lbs +/- .50 lb for final test




Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
2.626	0.052	0.032	0.032	0.060		Set Trigger
2.636	0.053	0.033	0.032	0.060		Set Trigger
2.623	0.052	0.032	0.032	0.061		Set Trigger
2.591	0.052	0.032	0.032	0.059		Set Trigger
2.598	0.052	0.032	0.032	0.059		Set Trigger

A-2-61

Trigger Profile [lbs,inch]

Profile SWS
 GunType: Rifle
 Make: Remington
 Note: C Schults 1/22/2009

Model: M/24
 Serial No: Form #F005
 Trigger: set to 4.0 lbs +/- 1.0 lb for target & accuracy



	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	4.339	0.054	0.030	0.028	0.103		Set Trigger
2	4.236	0.052	0.029	0.028	0.097		Set Trigger
3	4.235	0.053	0.029	0.028	0.098		Set Trigger
4	4.312	0.054	0.029	0.028	0.101		Set Trigger
5	4.318	0.053	0.030	0.028	0.100		Set Trigger

A-4.28