C6348717

MODEL 700™ M24

Model SWS ™

Action

Barrel Length

Capacity

Order No. 5716

*Includes 1 in chamber.

Remington

M2400062249

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER

04/24/08 12:24:17

Arms Services Repair & Estimate System

File Add Repair Estimate Repair Expedite Repair Inquiry Repair Tools CSR Tools Reports Table Maintenance System Maintenance Help

Repair Inquiry

Repair Number: RE00144815

Verify Repair

Serial: C6348717 Model M24 SWS Center Fire
Caliber: 7.62 NATO

Repairman:

Status: Closed 4/24/2008 10:57:55 AM

Address Information

Customer: (Received From)		Return To: (Received From)	
Name:	B/210TH BSB		B/210TH BSB
Address 1:	2 BCT		2 BCT
Address 2:	10 TH MTN DIV	PO Box:	10 TH MTN DIV PO Box:
City:	FORT DRUM		FORT DRUM
State:	NY Zip Code: 13602 Country: US		State: NY Zip Code: 13602 Country: US

FFL:

Contact / Condition | Problems | Estimate | History / Status | Shipping / Billing

Contact Information

Phone: NN

Fax:

Email:

Comments:

Received Condition

Fair

Condition Notes:

CSR Notes:

Accessories Received

Code	Desc	Qty
A007	With Stud	3
A008	With Swivel	3
A010	Hard Case	1
A026	Scope	1
A057	Frt and Rear Sgt Base	1

nagletj 4/24/2008 12:24 PM NUM

Start | 4 Micros... | The Asso... | 2 Micros... | SAP Logo... | Arms Ser...

Serial Number: C6348717

Model: M24 SWS

RE00144815

SNIPER WEAPON SYSTEM - UNIQUE STATISTICAL INFOMATION

FIREARM SERIAL NUMBER / DATASET NAME: C6348717.__0
FILE DATE AND TIME: 05/27/2008 05:37

THE FOLLOWING DATA IS ALL REPORTED IN UNITS OF INCHES

The Average X Centroid of the Five Target Set:	-0.029
The Average Y Centroid of the Five Target Set:	-0.103
The Average Point of Impact of the Five Target Set:	0.107
The Average Mean Radius of the Five Target Set:	0.773
The Distance from POA to Centroid Target #1:	0.299
The Distance from Centroid Target #2 to Centroid Target #1:	0.340
The Distance from Centroid Target #3 to Centroid Target #1:	0.277
The Distance from Centroid Target #4 to Centroid Target #1:	0.235
The Distance from Centroid Target #5 to Centroid Target #1:	0.305

SERIAL NUMBER: C6348717.__0
TARGET NUMBER: 2
FILE DATE: 05/27/2008
FILE TIME: 05:37

X CENTROID:	-0.119
Y CENTROID:	-0.032
POA TO CENTROID:	0.123
HORZ SPREAD:	1.782
VERT SPREAD:	2.743
GROUP SPREAD:	2.991
MIN RADIUS:	0.270
MAX RADIUS:	1.702
MEAN RADIUS:	0.859
# IN 1 IN DIAMETER:	5
# IN 2 IN DIAMETER:	6
# in 3 IN DIAMETER:	9

POINT#	X	Y
1:	-0.549	-1.394
2:	-1.084	-1.434
3:	-0.273	-0.451
4:	0.698	-0.205
5:	-0.485	0.131
6:	0.603	1.036
7:	-0.448	1.309
8:	0.244	0.264
9:	-0.011	0.325
10:	0.115	0.103



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: C6348717.__0
TARGET NUMBER: 3
FILE DATE: 05/27/2008
FILE TIME: 05:37

X CENTROID:	0.020
Y CENTROID:	-0.016
POA TO CENTROID:	0.026
HORZ SPREAD:	1.417
VERT SPREAD:	1.710
GROUP SPREAD:	1.715
MIN RADIUS:	0.233
MAX RADIUS:	1.026
MEAN RADIUS:	0.561
# IN 1 IN DIAMETER:	5
# IN 2 IN DIAMETER:	9
# in 3 IN DIAMETER:	10

POINT#	X	Y
1:	0.266	-1.012
2:	-0.044	-0.427
3:	0.248	-0.067
4:	0.354	-0.017
5:	0.658	-0.034
6:	-0.443	-0.036
7:	-0.759	-0.166
8:	-0.006	0.360
9:	-0.198	0.546
10:	0.129	0.698



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: C6348717.__0
TARGET NUMBER: 4
FILE DATE: 05/27/2008
FILE TIME: 05:37

X CENTROID:	-0.057
Y CENTROID:	-0.119
POA TO CENTROID:	0.132
HORZ SPREAD:	1.861
VERT SPREAD:	1.388
GROUP SPREAD:	1.930
MIN RADIUS:	0.089
MAX RADIUS:	1.102
MEAN RADIUS:	0.705
# IN 1 IN DIAMETER:	3
# IN 2 IN DIAMETER:	9
# in 3 IN DIAMETER:	10

POINT#	X	Y
1:	0.705	-0.712
2:	0.328	-0.667
3:	0.691	-0.242
4:	0.394	0.628
5:	0.196	0.255
6:	-0.116	-0.053
7:	-0.404	-0.383
8:	-0.802	-0.496
9:	-1.156	-0.199
10:	-0.404	0.676



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: C6348717.__0
TARGET NUMBER: 5
FILE DATE: 05/27/2008
FILE TIME: 05:37

X CENTROID:	-0.111
Y CENTROID:	-0.075
POA TO CENTROID:	0.134
HORZ SPREAD:	2.046
VERT SPREAD:	1.350
GROUP SPREAD:	2.189
MIN RADIUS:	0.263
MAX RADIUS:	1.242
MEAN RADIUS:	0.706
# IN 1 IN DIAMETER:	3
# IN 2 IN DIAMETER:	9
# in 3 IN DIAMETER:	10

POINT#	X	Y
1:	-0.506	0.488
2:	-0.927	0.409
3:	-1.313	0.238
4:	0.560	0.406
5:	0.195	0.193
6:	0.733	-0.541
7:	0.420	-0.463
8:	-0.199	-0.337
9:	-0.129	-0.862
10:	0.057	-0.277



TARGET APPROX 1/2 SCALE

M-24 INSPECTION CHECKLIST
CONTRACT #: DAAE-20-02-C-0149

R & E NUMBER 144815
SERIAL NUMBER C6348717
LOG-IN DATE 4-24-08

OPERATION #	OPERATION NAME		DATE	INITIAL
500	DIS-ASSEMBLE GUN		4-28-08	RTZ
505	RE-BARREL			
560	ASSEMBLE		4-30-08	TRW
600	PROOF		4-30-08	TRW
605	CHECK HEADSPACE		4-30-08	TRW
610	DIS-ASSEMBLE GUN		4-30-08	S.A.D.
612	MAGNAFLUX	MAGNA - FLUX MAY 3 = 2008 OPERATOR	5/1/08	
510	DRILL AND TAP		5-1-08	TRW
615	ROLLMARK CALIBER		5-1-08	CW
618	ROTO-BLAST		5-1-08	DG
620	APPLY COATINGS		5-5-08	
625	FINAL ASSEMBLY		5-23-08	RTZ
640	FUNCTION TEST AND	(PASS) FAIL	5/23/08	SD
650	TARGET	(PASS) FAIL	5-23-08	SD
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION N/A		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION	5-23-08	RP
670	FINAL INSPECTION		5/28/08	FM
	A) HEADSPACE	(PASS) FAIL	5/28/08	FM
	B) TRIGGER PULL (+/- .5 LBS, MIN 2.50 LBS, MAX 4.0 LBS)	2.73 2.75 2.77 2.70 2.75	5-27-08	TRW
680	F) SAFETY ON FORCE (2 LBS MIN, 10 LBS MAX)	5 5 5	5/28/08	FM
	G) SAFETY OFF FORCE (2 LBS MIN)	2 2 2	5/28/08	FM
	I) FIRING PIN INDENT .020	.022 .021 .021	5/28/08	FM
690	PACK		5/28/08	FM



Serial Number: C634817

Model: M24 SWS

RE00092984

SNIPER WEAPON SYSTEM - UNIQUE STATISTICAL INFOMATION

FIREARM SERIAL NUMBER / DATASET NAME: C6348717.__0
FILE DATE AND TIME: 03/24/2005 09:04

THE FOLLOWING DATA IS ALL REPORTED IN UNITS OF INCHES

The Average X Centroid of the Five Target Set:	-0.088
The Average Y Centroid of the Five Target Set:	0.127
The Average Point of Impact of the Five Target Set:	0.154
The Average Mean Radius of the Five Target Set:	1.002
The Distance from POA to Centroid Target #1:	0.261
The Distance from Centroid Target #2 to Centroid Target #1:	0.455
The Distance from Centroid Target #3 to Centroid Target #1:	0.325
The Distance from Centroid Target #4 to Centroid Target #1:	0.665
The Distance from Centroid Target #5 to Centroid Target #1:	0.442

SERIAL NUMBER: C6348717.__0
TARGET NUMBER: 1
FILE DATE: 03/24/2005
FILE TIME: 09:04

X CENTROID:	-0.108
Y CENTROID:	-0.237
POA TO CENTROID:	0.261
HORZ SPREAD:	2.415
VERT SPREAD:	2.245
GROUP SPREAD:	2.674
MIN RADIUS:	0.302
MAX RADIUS:	1.553
MEAN RADIUS:	0.905
# IN 1 IN DIAMETER:	3
# IN 2 IN DIAMETER:	6
# in 3 IN DIAMETER:	9

POINT#	X	Y
1:	0.559	-1.206
2:	-0.161	-1.171
3:	0.984	0.096
4:	0.051	0.019
5:	-0.125	0.195
6:	-0.556	0.630
7:	-0.159	1.039
8:	-0.046	0.162
9:	-0.196	-1.086
10:	-1.431	-1.051



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: C6348717.__0
TARGET NUMBER: 2
FILE DATE: 03/24/2005
FILE TIME: 09:04

X CENTROID:	-0.147
Y CENTROID:	0.216
POA TO CENTROID:	0.262
HORZ SPREAD:	2.666
VERT SPREAD:	2.321
GROUP SPREAD:	2.688
MIN RADIUS:	0.827
MAX RADIUS:	1.603
MEAN RADIUS:	1.122
# IN 1 IN DIAMETER:	0
# IN 2 IN DIAMETER:	5
# in 3 IN DIAMETER:	8

POINT#	X	Y
1:	0.717	0.327
2:	1.339	0.816
3:	0.304	1.094
4:	-0.492	1.250
5:	-0.680	0.849
6:	-1.327	1.163
7:	-0.044	-0.833
8:	-0.288	-0.747
9:	-0.431	-0.687
10:	-0.573	-1.071



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: C6348717.__0
TARGET NUMBER: 3
FILE DATE: 03/24/2005
FILE TIME: 09:04

X CENTROID:	0.048
Y CENTROID:	0.048
POA TO CENTROID:	0.067
HORZ SPREAD:	1.312
VERT SPREAD:	2.184
GROUP SPREAD:	2.187
MIN RADIUS:	0.386
MAX RADIUS:	1.156
MEAN RADIUS:	0.764
# IN 1 IN DIAMETER:	1
# IN 2 IN DIAMETER:	8
# in 3 IN DIAMETER:	10

POINT#	X	Y
1:	0.822	-0.296
2:	0.491	-0.328
3:	0.022	-1.108
4:	-0.326	-0.672
5:	-0.281	-0.155
6:	-0.490	-0.076
7:	0.451	0.613
8:	0.297	0.979
9:	-0.101	1.076
10:	-0.410	0.445



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: C6348717.__0
TARGET NUMBER: 4
FILE DATE: 03/24/2005
FILE TIME: 09:04

X CENTROID:	-0.003
Y CENTROID:	0.419
POA TO CENTROID:	0.419
HORZ SPREAD:	2.588
VERT SPREAD:	2.622
GROUP SPREAD:	3.018
MIN RADIUS:	0.230
MAX RADIUS:	1.513
MEAN RADIUS:	1.104
# IN 1 IN DIAMETER:	1
# IN 2 IN DIAMETER:	3
# in 3 IN DIAMETER:	8

POINT#	X	Y
1:	1.161	0.117
2:	0.881	-0.809
3:	0.287	-0.095
4:	0.226	-0.815
5:	-0.585	-0.029
6:	-1.427	0.581
7:	-0.862	1.655
8:	0.175	1.579
9:	0.186	1.807
10:	-0.068	0.198



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: C6348717.__0
TARGET NUMBER: 5
FILE DATE: 03/24/2005
FILE TIME: 09:04

X CENTROID:	-0.230
Y CENTROID:	0.188
POA TO CENTROID:	0.297
HORZ SPREAD:	2.481
VERT SPREAD:	3.443
GROUP SPREAD:	4.153
MIN RADIUS:	0.526
MAX RADIUS:	2.565
MEAN RADIUS:	1.115
# IN 1 IN DIAMETER:	0
# IN 2 IN DIAMETER:	4
# in 3 IN DIAMETER:	8

POINT#	X	Y
1:	0.763	-0.608
2:	0.645	-1.138
3:	-0.156	-0.505
4:	-0.228	-0.338
5:	0.803	0.289
6:	0.247	0.487
7:	-0.145	0.822
8:	-1.204	0.683
9:	-1.352	-0.121
10:	-1.678	2.305



TARGET APPROX 1/2 SCALE

M-24 INSPECTION CHECKLIST

CONTRACT #: DAAE-20-02-D-0127

R & E NUMBER	92984		
SERIAL NUMBER	C6348717		
LOG-IN DATE	2-11-05		
INSPECT AND VERIFY:			
OPERATION #	OPERATION NAME	DATE	INITIAL
550	DIS-ASSEMBLE GUN	2-18-05	RTL
560 A	RE-BARREL	2-22-05	RTL
B	DRILL AND TAP	2-28-05	TRW
575	ASSEMBLE	2-23-05	RTL
600	PROOF	2-24-05	AC
605	CHECK HEADSPACE	2-24-05	AC
610	DIS-ASSEMBLE GUN	2-24-05	RTL
612	MAGNAFLUX		
615	ROLLMARK CALIBER	3-1-05	CW
618	ROTO-BLAST	3-3-05	LB
620	APPLY COATINGS	3/16/05	
625 A	FINAL ASSEMBLY	3-23-05	RTL
B	TRIGGER PULL TEST		
C	SAFETY "ON" FORCE	3-28-05	
D	SAFETY "OFF" FORCE	3-28-05	AC
E	FIRING PIN INDENT	3-28-05	AC
640	TARGET	3-24-05	TRW
655	FINAL INSPECT	3-28-05	AC
660	PACK	4-25-05	DA
		SHIP DATE	
	QAR INSPECTION DATE		

MAGNA-FLUX INSPECTED MAR 0 1 2005 OPERATOR

CONTRACT # DAAA21-87-C-0086

GUN SERIAL # C6348717

OP. #	OP. NAME	READINGS	DATE	INIT
575 & 580	Assemble Action and Stock	9 26	89	RW
600	Proof	9 26	89	RW
607	Check Headspace	9 26	89	RW
610	Dis-assemble Gun	9 26	89	RW
612	Magnaflux Barrel Action	9/29/89		KCR
	Magnaflux Bolt	9/29/89		KCR
615	Rollmark Caliber	9/29/89		LA
7	Drill and Tap Sight Holes	9 29	89	LB
618	Polish Barrel LB	9 29	89	BT
620	Apply Coatings (Barrel Action)		10-1-89	KJH
	Apply Coating (Bolt)		10-1-89	KJH
625	Final Assembly A) Clean inside of Bolt Assembly		10/12/89	RW
	B) Inspect Rear Firing Pin Hole for Chamfer in Bolt Head		10/12/89	RW
	C) Inspect Ejector Hole for Chamfer		10/12/89	RW
	D) Oil Firing Pin Ass'y		10/12/89	RW
	E) Adjust Trigger Pull to Min Setting and Stake		10/17/89	DB

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER

op. #	OP. NAME	READINGS					DATE	INIT
625 cont.	F) Safety On Force	6		6		6	10/17/89	JH
	G) Safety Off Force	3		3		3	10/17/89	JH
	H) Trigger Pull Test & Retainability						17Oct89	JSS
	I) Firing Pin Indent	.020		.022		.021	10/17/89	JH
	J) Assemble Stock						10/18/89	RW
	K) Assemble Swivel Studs						19Oct89	JSS
	L) Attach Front and Rear Sight Assemblies						12/11/89	RW
	M) Iron Sight Alignment						12/11/89	RW
	N) Detach Front & Rear Sights & place in numbered container						12/11/89	RW
	O) Attach Scope to Rifle						18Oct89	JSS
	P) Detach & Attach Scope 20 Times						18Oct89	JSS
640	Gallery Target & Test						10-18-89	DH
	A) Time						10-18-89	DH
	B) Malfunctions						10-18-89	DH
	C) Pierced Primers						10-18-89	DH
	D) Optical Clearity of Scope						10-18-89	DH
645	Inspect for Live Ammo						10-18-89	DH
655	Final Inspection A) Headspace						19Oct89	JSS
	B) Trigger Pull	258	259	245	253	247	19Oct89	JSS
	C) Function						19Oct89	JSS
660	Pack						15Dec89	JSS

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER

SWS TRIGGER PULL TEST

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS
2.50# ± .50#
3.00# ± .75#
4.00# ± 1.00#

SERIAL NO. 6348719

DATE 3-13-90

TESTER

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.50	2.29	2.46		MIN. SETTING,
PULL #2	2.54	2.55	2.45		NO AVG. OF 5
PULL #3	2.54	2.46	2.40		READINGS ACCEPT-
PULL #4	2.55	2.40	2.43		ABLE LESS THAN 2#
PULL #5	2.50	2.43	2.51		
TOTAL	12.63	12.13	12.25		
AVG.	2.526	2.426	2.45		

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.16	3.37		
PULL #2	3.44	3.50		
PULL #3	3.41	3.45		
PULL #4	3.40	3.47		
PULL #5	3.51	3.40		
TOTAL	16.92	17.19		
AVG.	3.384	3.438		

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.29	4.48		
PULL #2	4.31	4.40		
PULL #3	4.40	4.31		
PULL #4	4.46	4.31		
PULL #5	4.41	4.40		
TOTAL	21.87	21.90		
AVG.	4.374	4.382		

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER

CENTROIDAL DISTANCE CALCULATIONS
FOR RIFLE # C6348717
18 Oct 1989

CENTROIDAL DISTANCES

0	TO	1	.592611
1	TO	2	.316811
1	TO	3	.630451
1	TO	4	.291433
1	TO	5	.300613



THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: .511
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: -.076
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .516621

THE AMR FOR THIS RIFLE IS: .9772



PATTERN #	:	1		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	.938	.982	1.079
MINIMUM X	:	-1.328	-1.284	-1.187
MAXIMUM Y	:	1.481	.911	.786
MINIMUM Y	:	-1.164	-.999	-1.029
CENTROID X	:	.562	.518	.421
CENTROID Y	:	.188	.023	.148
POA TO CENTROID in.	:	.592	.518	.446
MIN RADIUS	:	.261	.297	.277
MEAN RADIUS	:	.962	.909	.843
MAX RADIUS	:	1.534	1.284	1.307
HORIZONTAL SPREAD	:	2.266	2.266	2.266
VERTICAL SPREAD	:	2.645	1.910	1.815
EXTREME SPREAD	:	2.666	2.463	2.336
NUMBER IN ONE INCH CIRCLE	=		2	
NUMBER IN TWO INCH CIRCLE	=		4	
NUMBER IN THREE INCH CIRCLE	=		9	

18 Oct 1989 FILE:/PATTERNING/CENTERFIRE_PATT/C6348717

CENTERFIRE PATTERNS # 2



OF SHOTS= 10

# IN CIR
1in = 3
2in = 8
3in = 8

HS= 2.759
VS= 2.212
GS= 3.536

PATTERN #	:	2		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.549	.676	.546
MINIMUM X	:	-1.210	-1.038	-.629
MAXIMUM Y	:	1.020	.732	.597
MINIMUM Y	:	-1.192	-1.079	-.660
CENTROID X	:	.307	.135	.265
CENTROID Y	:	.000	-.113	.022
POA TO CENTROID in.	:	.307	.176	.266
MIN RADIUS	:	.208	.389	.253
MEAN RADIUS	:	.751	.648	.501
MAX RADIUS	:	1.854	1.497	.708
HORIZONTAL SPREAD	:	2.759	1.714	1.175
VERTICAL SPREAD	:	2.212	1.811	1.257
EXTREME SPREAD	:	3.536	2.108	1.258
NUMBER IN ONE INCH CIRCLE	=		3	
NUMBER IN TWO INCH CIRCLE	=		8	
NUMBER IN THREE INCH CIRCLE	=		8	



PATTERN #	:	3		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	.899	.774	.631
MINIMUM X	:	-1.125	-1.144	-.631
MAXIMUM Y	:	1.204	1.257	1.154
MINIMUM Y	:	-1.118	-.984	-1.087
CENTROID X	:	.792	.917	1.060
CENTROID Y	:	-.399	-.533	-.430
POA TO CENTROID in.	:	.887	1.061	1.144
MIN RADIUS	:	.205	.165	.076
MEAN RADIUS	:	.882	.788	.675
MAX RADIUS	:	1.647	1.409	1.157
HORIZONTAL SPREAD	:	2.023	1.918	1.261
VERTICAL SPREAD	:	2.322	2.241	2.241
EXTREME SPREAD	:	2.762	2.398	2.242
NUMBER IN ONE INCH CIRCLE	=		3	
NUMBER IN TWO INCH CIRCLE	=		5	
NUMBER IN THREE INCH CIRCLE	=		9	



PATTERN #	:	4		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.429	1.123	1.139
MINIMUM X	:	-.873	-.714	-.698
MAXIMUM Y	:	1.095	1.206	1.017
MINIMUM Y	:	-1.627	-1.515	-.918
CENTROID X	:	.460	.301	.284
CENTROID Y	:	-.085	-.196	-.007
POA TO CENTROID in.	:	.468	.360	.285
MIN RADIUS	:	.855	.700	.724
MEAN RADIUS	:	1.107	1.006	.937
MAX RADIUS	:	1.749	1.520	1.141
HORIZONTAL SPREAD	:	2.302	1.837	1.837
VERTICAL SPREAD	:	2.721	2.721	1.985
EXTREME SPREAD	:	3.009	2.757	2.035
NUMBER IN ONE INCH CIRCLE	=		0	
NUMBER IN TWO INCH CIRCLE	=		6	
NUMBER IN THREE INCH CIRCLE	=		8	



PATTERN #	:	5		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.586	1.365	1.048
MINIMUM X	:	-1.989	-1.470	-1.300
MAXIMUM Y	:	.785	.779	.777
MINIMUM Y	:	-.815	-.821	-.823
CENTROID X	:	.434	.655	.485
CENTROID Y	:	-.084	-.078	-.076
POA TO CENTROID in.	:	.442	.660	.491
MIN RADIUS	:	.764	.785	.780
MEAN RADIUS	:	1.184	1.078	1.033
MAX RADIUS	:	1.990	1.506	1.340
HORIZONTAL SPREAD	:	3.575	2.835	2.348
VERTICAL SPREAD	:	1.600	1.600	1.600
EXTREME SPREAD	:	3.575	2.856	2.496
NUMBER IN ONE INCH CIRCLE	=		0	
NUMBER IN TWO INCH CIRCLE	=		3	
NUMBER IN THREE INCH CIRCLE	=		8	

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER

Remington®

DUPONT
REG. U.S. PAT. & TM. OFF.

VERY IMPORTANT: Instruction Book enclosed to assure safe use of this firearm.

MODEL 700™ M24

SERIAL NO.
C6348717

ORDER NO.
5716

MADE IN ILION, N.Y. U.S.A. Reg. U.S. Pat & Tm. Off, Marca Registrada Marque Deposee.

01

5716 C6348717

UPC
0 47700 25716 7

M2400062274