



G6784760

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase




owner registration sticker



ORDER NO.	86470
BARREL LENGTH	24"
CAPACITY	6

G6784700

UPC



BM FORM

INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL # G 6784700

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		9-8-08	SP
430	ASSEMBLE TO STOCK		9-8-08	SP
440	PROOF		9-8-08	SP
460	CHECK HEADSPACE		9-8-08	SP
470	DIS-ASSEMBLE ACTION		9-8-08	SP
472	SERIALIZE BOLT HANDLE	MAGNA - FLUX	9-9-08	RTZ
475	DRILL AND TAP SIGHT HOLES	SEP 10 2008	9-9-08	SP
480	MAGNAFLUX BBL ACTION	OPERATOR BHA	9-10-08	BHA
490	MAGNAFLUX BOLT		9/8/08	MR
500	ROLLMARK CALIBER		9/10/08	RT
520	GOFF BLAST BBL / REC		9/11/08	RG
542	APPLY COATINGS (BARREL ACTION)		9-11	
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		9-15-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		9-15-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		9-15-08	SP
	D) OIL FIRING PIN ASSEMBLY		9-17-08	RSA
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		

F004 REV 5/2006


560	F) SAFETY ON FORCE	2 LBS MIN 10 LBS MAX	<u>2.5</u> <u>2.5</u> <u>2.5</u>	9-25-08	TC
CONT.					
	G) SAFETY OFF FORCE	2 LBS MIN	<u>4.5</u> <u>4.5</u> <u>4.5</u>	9-25-08	TC
	H) TRIGGER PULL TEST AND RETAINABILITY				
	I) FIRING PIN INDENT	.020 MIN	<u>.020</u> <u>.020</u> <u>.020</u>	9-25-08	TC
	J) ASSEMBLE STOCK			9-17-08	BSN
	K) ASSEMBLE SWIVEL STUDS			9-25-08	TC
	L) ATTACH FRONT AND REAR SIGHT ASSY'S				
	M) IRON SIGHT ALIGNMENT				
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER				
640 & 650	FUNCTION TEST AND TARGET		<u>PASS</u> FAIL <u>PASS</u> FAIL	9-25-08	TRW
	MALFUNCTION	CORRECTION	N/A		
	MALFUNCTION	CORRECTION			
	MALFUNCTION	CORRECTION			
	MALFUNCTION	CORRECTION			
660	INSPECT FOR LIVE AMMO			9-25-08	L. D.
670	FINAL INSPECTION A) HEADSPACE			9-25-08	TC
	B) TRIGGER PULL	+/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>215</u> <u>224</u> <u>221</u> <u>231</u> <u>225</u>	9-25-08	L. D.
	C) FUNCTION			9-25-08	TC
690	PACK			12-9-08	TC

F004 REV 5/2006

Trigger Profile [lbs,inch]

Profile SWS
GunType: Rifle
Make: Remington
Note: R. Putch 9/8/08

Model: M/24
Serial No: Form #F005
Trigger: 2.5 lbs. ini. +/- .50 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	2.492	0.054	0.034	0.038	0.053		Set Trigger
2	2.580	0.054	0.034	0.038	0.054		Set Trigger
3	2.619	0.054	0.034	0.038	0.055		Set Trigger
4	2.582	0.054	0.034	0.038	0.054		Set Trigger
5	2.627	0.054	0.034	0.037	0.055		Set Trigger

Avg 2.58

Trigger Profile [lbs,inch]

Profile SWS
GunType: Rifle
Make: Remington
Note: R. Putch 9/8/08

Model: M/24
Serial No: Form #F005
Trigger: 2.5 lbs. after 50 cycles +/- .50 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	2.544	0.053	0.033	0.038	0.053		Set Trigger
2	2.620	0.053	0.033	0.038	0.054		Set Trigger
3	2.634	0.053	0.033	0.037	0.055		Set Trigger
4	2.655	0.052	0.032	0.038	0.053		Set Trigger
5	2.514	0.052	0.033	0.039	0.051		Set Trigger

Avg 2.59

Trigger Profile [lbs,inch]

Profile SWS
GunType: Rifle
Make: Remington
Note: R. Putch 9/8/08

Model: M/24
Serial No: Form #F005
Trigger: 3.0 lbs. ini. +/- .75 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	3.087	0.057	0.035	0.038	0.065		Set Trigger
2	3.134	0.056	0.036	0.038	0.066		Set Trigger
3	3.065	0.057	0.036	0.038	0.065		Set Trigger
4	3.171	0.056	0.036	0.038	0.066		Set Trigger
5	3.150	0.058	0.036	0.038	0.067		Set Trigger

Avg 3.12

Trigger Profile [lbs,inch]

Profile SWS
GunType: Rifle
Make: Remington
Note: R. Putch 9/8/08

Model: M/24
Serial No: Form #F005
Trigger: 3.0 lbs. after 20 cycles +/- .75 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	2.933	0.057	0.035	0.038	0.063		Set Trigger
2	2.926	0.057	0.035	0.038	0.062		Set Trigger
3	2.996	0.057	0.036	0.038	0.063		Set Trigger
4	3.007	0.056	0.036	0.038	0.063		Set Trigger
5	2.994	0.057	0.036	0.038	0.063		Set Trigger

Avg 2.97

Trigger Profile [lbs,inch]

Profile: SWS
 GunType: Rifle
 Make: Remington
 Note: R. Putch 9/8/08

Model: M/24
 Serial No: Form #F005
 Trigger: 4.0 lbs. ini. +/- 1.0 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	4.218	0.056	0.033	0.035	0.091		Set Trigger
2	4.099	0.057	0.033	0.035	0.090		Set Trigger
3	4.163	0.056	0.033	0.035	0.090		Set Trigger
4	4.209	0.056	0.033	0.035	0.091		Set Trigger
5	4.140	0.057	0.033	0.035	0.090		Set Trigger

Avrg 4.16

Trigger Profile [lbs,inch]

Profile SWS
GunType: Rifle
Make: Remington
Note: R. Putch 9/8/08

Model: M/24
Serial No: Form #F005
Trigger: 4.0 lbs. after 20 cycles +/- 1.0 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	4.172	0.057	0.033	0.035	0.091		Set Trigger
2	4.112	0.057	0.033	0.035	0.090		Set Trigger
3	4.043	0.058	0.033	0.035	0.091		Set Trigger
4	3.972	0.056	0.033	0.035	0.086		Set Trigger
5	3.991	0.057	0.033	0.035	0.088		Set Trigger

Avg 4.05

Trigger Profile [lbs,inch]

Profile SWS
GunType: Rifle
Make: Remington
Note: R. Putch 9/8/08

Model: M/24
Serial No: Form #F005
Trigger: reset to 2.5 lbs. +/- .50 lbs. for final test




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	2.707	0.055	0.035	0.038	0.053		Set Trigger
2	2.742	0.055	0.035	0.038	0.054		Set Trigger
3	2.736	0.055	0.035	0.038	0.054		Set Trigger
4	2.625	0.056	0.036	0.038	0.053		Set Trigger
5	2.705	0.056	0.036	0.038	0.054		Set Trigger

Avg 2.70

Trigger Profile [lbs,inch]

Profile SWS
GunType: Rifle
Make: Remington
Note: R. Putch 9/8/08

Model: M/24
Serial No: Form #F005
Trigger: set to 4.0 lbs. +/- 1.0 lbs. for target & accuracy



#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	4.312	0.056	0.033	0.035	0.090		Set Trigger
2	4.202	0.056	0.034	0.035	0.089		Set Trigger
3	4.235	0.056	0.033	0.035	0.089		Set Trigger
4	4.271	0.056	0.033	0.035	0.090		Set Trigger
5	4.304	0.057	0.033	0.035	0.091		Set Trigger

Avg 4.26