

G6794627

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

- INSTRUCTION BOOK 3518

proof of purchase



owner registration sticker



BM FORM


ORDER NO. **25716**

BARREL LENGTH **24"**

CAPACITY **6**

G6794627

UPC



INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL #

G 6794627

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		9-29-08	SPD
430	ASSEMBLE TO STOCK		9-29-08	SP
440	PROOF		9-29-08	SPD
460	CHECK HEADSPACE		9-24-08	SPD
470	DIS-ASSEMBLE ACTION		9-29-08	SPD
472	SERIALIZE BOLT HANDLE		9-30-08	RSW
475	DRILL AND TAP SIGHT HOLES		10/1/08	Fm
480	MAGNAFLUX BBL ACTION		10/2/08	(K)
490	MAGNAFLUX BOLT			
500	ROLLMARK CALIBER		10/2/08	RT
520	GOFF BLAST BBL / REC		10/2/08	DG
542	APPLY COATINGS (BARREL ACTION)		10-3	
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		10-3-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		10-3-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		10-3-08	SP
	D) OIL FIRING PIN ASSEMBLY		10-15-08	RSW
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		

F004 REV 5/2006

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>5.0</u> <u>5.0</u> <u>5.0</u>	10-27-08	L.D.
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>5.0</u> <u>5.0</u> <u>4.0</u>	10-27-08	R.N.
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.023</u> <u>.023</u> <u>.025</u>	10-27-08	R.N.
	J) ASSEMBLE STOCK		10-15-08	R.N.
	K) ASSEMBLE SWIVEL STUDS		10-27-08	L.D.
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 &	FUNCTION TEST AND	(PASS) J FAIL	10-23-08	R.N.
650	TARGET	(PASS) FAIL	10-23-08	R.N.
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		10-23-08	R.
670	FINAL INSPECTION A) HEADSPACE		10-27-08	L.D.
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.68</u> <u>2.68</u> <u>2.51</u> <u>2.60</u> <u>2.65</u>	10-27-08	L.D.
	C) FUNCTION		10-27-08	L.D.
690	PACK		10/29/08	Fm

F004 REV 5/2006

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)
3.00 LBS (plus or minus 0.75 LBS)
4.00 LBS (plus or minus 1.00 LBS)

DATE

10-10-08

TESTER

TAE

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS	COMMENTS
PULL #1	257	265	236	
PULL #2	259	246	236	
PULL #3	259	249	239	
PULL #4	264	253	239	
PULL #5	265	258	238	
TOTAL	1304	1271	124 1188	
AVERAGE	260	254	237	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES	COMMENTS
PULL #1	333	318	
PULL #2	330	319	
PULL #3	330	325	
PULL #4	328	334	
PULL #5	331	320	
TOTAL	1649	1616	
AVERAGE	329	323	

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	423	413		432
PULL #2	430	409		416
PULL #3	421	408		412
PULL #4	426	413		424
PULL #5	423	413		414
TOTAL	2123	2050 2098		2098
AVERAGE	424	411		419