

56794647

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

- INSTRUCTION BOOK 3518

BM FORM

proof of purchase



owner registration sticker




ORDER NO. **25716**

BARREL LENGTH **24"**

CAPACITY **6**

G6794647

UPC



INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL #

G6794647

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		10-27-08	SPD
430	ASSEMBLE TO STOCK		10-27-08	SP
440	PROOF		10-27-08	SPD
460	CHECK HEADSPACE		10-27-08	SPD
470	DIS-ASSEMBLE ACTION		10-27-08	SPD
472	SERIALIZE BOLT HANDLE		10-28-08	BSN
475	DRILL AND TAP SIGHT HOLES		10-28-08	SP
480	MAGNAFLUX BBL ACTION	(RB)	10/29/08	(RB)
490	MAGNAFLUX BOLT		10/27/08	NR
500	ROLLMARK CALIBER		10/29/08	RT
520	GOFF BLAST BBL / REC		10/29/08	DC
542	APPLY COATINGS (BARREL ACTION)		11-3	
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		11-4-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		11-4-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		11-4-08	SP
	D) OIL FIRING PIN ASSEMBLY		11-10-08	BSW
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

F004 REV 5/2006

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>4.0</u> <u>4.0</u> <u>4.0</u>	12-2-08	L.D.
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>5.0</u> <u>5.0</u> <u>4.0</u>	12-2-08	L.M.
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.024</u> <u>.024</u> <u>.025</u>	12-2-08	L.D.
	J) ASSEMBLE STOCK		11-10-08	RBN
	K) ASSEMBLE SWIVEL STUDS		12-2-08	L.D.
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	11-12-08	TC
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		11-12-08	JS
670	FINAL INSPECTION A) HEADSPACE		12-2-08	L.M.
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.42</u> <u>2.55</u> <u>2.55</u> <u>2.44</u> <u>2.37</u>	11-20-08	TC
	C) FUNCTION		12-2-08	L.M.
690	PACK		12-5-08	RBN

F004 REV 5/2006

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)
3.00 LBS (plus or minus 0.75 LBS)
4.00 LBS (plus or minus 1.00 LBS)

DATE 10-30-08

TESTER TAE

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	241	256		272	
PULL #2	265	246		257	
PULL #3	254	237		270	
PULL #4	254	245		266	
PULL #5	250	240		250	
TOTAL	1305	1264	1224	1309	
AVERAGE	252	224		261	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	339	368		
PULL #2	356	348		
PULL #3	352	355		
PULL #4	341	330		
PULL #5	339	336		
TOTAL	1727	1737		
AVERAGE	345	347		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	455	430		464
PULL #2	465	448		462
PULL #3	448	455		425
PULL #4	431	440		463
PULL #5	447	448		463
TOTAL	2246	2221		2277
AVERAGE	449	444		455