

G 679 4743

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)

BOLT ACTION CENTERFIRE RIFLE


24" BARREL 7.62 NATO

WITH BIPOD

proof of purchase



owner registration sticker




ORDER NO. **86470**

BARREL LENGTH **24"**

CAPACITY **6**

G6794743

UPC



BM FORM

INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL #

G 6794743

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		10-7-08	SP
430	ASSEMBLE TO STOCK		10-7-08	SP
440	PROOF		10-7-08	SP
460	CHECK HEADSPACE		10-7-08	SP
470	DIS-ASSEMBLE ACTION		10-7-08	SP
472	SERIALIZE BOLT HANDLE	MAGNA FLUX	10-8-08	RSN
475	DRILL AND TAP SIGHT HOLES		10-8-08	SP
480	MAGNAFLUX BBL ACTION	OPERATOR (14)	10/11/08	(14)
490	MAGNAFLUX BOLT		10/11/08	SP
500	ROLLMARK CALIBER		10/13/08	RT
520	GOFF BLAST BBL / REC		10/14/08	DG
542	APPLY COATINGS (BARREL ACTION)		10/15	
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		10-15-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		10-15-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		10-15-08	SP
	D) OIL FIRING PIN ASSEMBLY		10-16-08	RSN
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		
F004 REV 5/2006				

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>4.0</u> <u>4.0</u> <u>3.5</u>	12-8-08	RJ
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>4.0</u> <u>4.0</u> <u>4.0</u>	12-8-08	RJ
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.025</u> <u>.025</u> <u>.025</u>	12-8-08	RJ
	J) ASSEMBLE STOCK		10-17-08	RJ
	K) ASSEMBLE SWIVEL STUDS		12-8-08	RJ
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	11-24-08	TC
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		11-24-08	RJ
670	FINAL INSPECTION A) HEADSPACE		12-8-08	RJ
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>254</u> <u>256</u> <u>252</u> <u>257</u> <u>261</u>	12-8-08	RJ
	C) FUNCTION		12-8-08	RJ
690	PACK		1-13-09	TC

F004 REV 5/2006

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)
3.00 LBS (plus or minus 0.75 LBS)
4.00 LBS (plus or minus 1.00 LBS)

DATE 10-15-08

TESTER TAE

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	224	289		254	
PULL #2	248	272		253	
PULL #3	251	235		251	
PULL #4	275	266		243	
PULL #5	276	282		279	
TOTAL	1274	1344		1280	
AVERAGE	254	268		256	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	349	319		
PULL #2	343	357		
PULL #3	307	362		
PULL #4	315	353		
PULL #5	323	339		
TOTAL	1637	1730		
AVERAGE	327	346		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	419	425		461
PULL #2	430	423		435
PULL #3	408	434		445
PULL #4	431	439		426
PULL #5	446	445		445
TOTAL	2134 ^{TAE} 2134	2166		2212
AVERAGE	426	433		442