

36794759

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

- INSTRUCTION BOOK 3518

BM FORM

proof of purchase




owner registration sticker



ORDER NO.	25716
BARREL LENGTH	24"
CAPACITY	6

G6794759

UPC



INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL #

G 6794759

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		10-7-08	SP
430	ASSEMBLE TO STOCK		10-7-08	SP
440	PROOF		10-7-08	SP
460	CHECK HEADSPACE		10-7-08	SP
470	DIS-ASSEMBLE ACTION		10-7-08	SP
472	SERIALIZE BOLT HANDLE		10-8-08	BSW
475	DRILL AND TAP SIGHT HOLES		10-8-08	SP
480	MAGNAFLUX BBL ACTION		10/11/08	SP
490	MAGNAFLUX BOLT			
500	ROLLMARK CALIBER		10/13/08	RT
520	GOFF BLAST BBL / REC			
542	APPLY COATINGS (BARREL ACTION)		10-21	✓
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		10-21-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		10-21-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		10-21-08	SP
	D) OIL FIRING PIN ASSEMBLY		10-27-08	RT
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		

F004 REV 5/2006

M2400075191

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER
KINZER V. REMINGTON

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>4.0</u> <u>4.0</u> <u>3.0</u>	10-30-08	LJD
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>4.0</u> <u>4.0</u> <u>4.0</u>	10-30-08	LJD
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.023</u> <u>.023</u> <u>.023</u>	10-30-08	LJD
	J) ASSEMBLE STOCK		10-27-08	RTZ
	K) ASSEMBLE SWIVEL STUDS		10-30-08	LJD
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	10-29-08	LJD
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION <u>N/A</u>		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		10-29-08	TQE
670	FINAL INSPECTION A) HEADSPACE		10-30-08	LJD
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.75</u> <u>2.77</u> <u>2.96</u> <u>2.87</u> <u>2.85</u>	10-30-08	LJD
	C) FUNCTION		10-30-08	LJD
690	PACK		10/31/08	Fm

F004 REV 5/2006

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)
3.00 LBS (plus or minus 0.75 LBS)
4.00 LBS (plus or minus 1.00 LBS)

DATE 10-14-08

TESTER TAC

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	266	224		225	
PULL #2	266	246		213	
PULL #3	267	249		217	
PULL #4	270	240		209	
PULL #5	271	218		208	
TOTAL	1340	1177		1072	
AVERAGE	268	235		214	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	355	345		
PULL #2	330	341		
PULL #3	344	367		
PULL #4	329	357		
PULL #5	339	366		
TOTAL	1697	1770		
AVERAGE	339	354		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	495	411		430
PULL #2	434	440		422
PULL #3	429	421		446
PULL #4	436	406		441
PULL #5	412	413		441
TOTAL	2206	2091		2180
AVERAGE	441	418		436