


G 653 5432

ORDER 25716

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)

UPC




0 47700 25716 7

ORDER 25716

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)

UPC



0 47700 25716 7

SERIAL NO.



66535432

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

- INSTRUCTION BOOK 3518

DD FORM

proof of purchase



owner registration sticker



ORDER NO.

25716

BARREL LENGTH


24"

CAPACITY

6

G6535432

UPC



M-24
INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL # G653 5432

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420 & 430	ASSEMBLE ACTION ASSEMBLE TO STOCK		4-13-06	RTZ
440	PROOF		4-13-06	TRW
460	CHECK HEADSPACE		4-13-06	TRW
470	DIS-ASSEMBLE ACTION	INSPECTED	4-13-06	RTZ
480 & 490	MAGNAFLUX BBL ACTION MAGNAFLUX BOLT	APR 17 2006 L80	4/17/06	und
500	ROLLMARK CALIBER		4-18-06	CW
510	DRILL AND TAP SIGHT HOLES		4-17-06	TRW
520	GOFF BLAST BBL / REC		4-18-06	LB
530 & 540	APPLY COATINGS (BARREL ACTION)			
	(BOLT)		4/19/06	FB
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		4-21-06	S.P.D.
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		4-21-06	S.P.D.
	C) INSPECT EJECTOR HOLE FOR CHAMFER		4-21-06	S.P.D.
	D) OIL FIRING PIN ASSEMBLY		5-1-06	AC
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS	5-10-06	AC

REV-8405

SNIPER WEAPON SYSTEM - UNIQUE STATISTICAL INFORMATION

FIREARM SERIAL NUMBER / DATASET NAME: G6535432.___0
FILE DATE AND TIME: 05/04/2006 08:26

THE FOLLOWING DATA IS ALL REPORTED IN UNITS OF INCHES

The Average X Centroid of the Five Target Set:	0.022
The Average Y Centroid of the Five Target Set:	-0.004
The Average Point of Impact of the Five Target Set:	0.023
The Average Mean Radius of the Five Target Set:	0.612
The Distance from POA to Centroid Target #1:	0.117
The Distance from Centroid Target #2 to Centroid Target #1:	0.189
The Distance from Centroid Target #3 to Centroid Target #1:	0.235
The Distance from Centroid Target #4 to Centroid Target #1:	0.118
The Distance from Centroid Target #5 to Centroid Target #1:	0.214

SERIAL NUMBER: G6535432.___0

TARGET NUMBER: 1

FILE DATE: 05/04/2006

FILE TIME: 08:26

POINT#	X	Y
1:	0.569	-0.272
2:	0.104	-0.668
3:	0.460	0.220
4:	0.171	0.805
5:	-0.045	-0.210
6:	-0.156	0.008
7:	-0.290	0.139
8:	-0.345	-0.071
9:	-0.491	-0.290
10:	-0.954	0.982

X CENTROID: -0.098

Y CENTROID: 0.064

POA TO CENTROID: 0.117

HORZ SPREAD: 1.523

VERT SPREAD: 1.650

GROUP SPREAD: 1.973

MIN RADIUS: 0.081


MAX RADIUS: 1.255

MEAN RADIUS: 0.551

IN 1 IN DIAMETER: 4

IN 2 IN DIAMETER: 9

in 3 IN DIAMETER: 10




TARGET APPROX 1/2 SCALE

SERIAL NUMBER: G6535432. __0
TARGET NUMBER: 2
FILE DATE: 05/04/2006
FILE TIME: 08:26

X CENTROID: 0.053
Y CENTROID: -0.051
POA TO CENTROID: 0.073
HORZ SPREAD: 1.937
VERT SPREAD: 1.592
GROUP SPREAD: 2.103
MIN RADIUS: 0.245
MAX RADIUS: 1.261
MEAN RADIUS: 0.780
IN 1 IN DIAMETER: 2
IN 2 IN DIAMETER: 8
in 3 IN DIAMETER: 10

POINT#	X	Y
1:	0.911	-0.491
2:	0.557	-0.552
3:	0.149	-0.794
4:	-0.585	-0.600
5:	-0.661	-0.347
6:	0.986	0.798
7:	0.276	0.051
8:	0.100	0.409
9:	-0.254	0.506
10:	-0.951	0.514




TARGET APPROX 1/2 SCALE

SERIAL NUMBER: G6535432. __0
TARGET NUMBER: 3
FILE DATE: 05/04/2006
FILE TIME: 08:26

X CENTROID: 0.041
Y CENTROID: -0.126
POA TO CENTROID: 0.132
HORZ SPREAD: 0.862
VERT SPREAD: 1.539
GROUP SPREAD: 1.611
MIN RADIUS: 0.194
MAX RADIUS: 0.879
MEAN RADIUS: 0.546
IN 1 IN DIAMETER: 2
IN 2 IN DIAMETER: 10
in 3 IN DIAMETER: 10

POINT#	X	Y
1:	0.390	-0.932
2:	0.336	0.415
3:	-0.087	0.607
4:	-0.217	0.354
5:	0.113	0.428
6:	-0.472	-0.111
7:	0.010	-0.317
8:	0.232	-0.420
9:	0.185	-0.639
10:	-0.078	-0.641



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: G6535432.___0

TARGET NUMBER: 4

FILE DATE: 05/04/2006

FILE TIME: 08:26

POINT#	X	Y
1:	0.753	0.000
2:	0.495	0.286
3:	0.074	-0.991
4:	-0.007	-0.509
5:	0.118	0.452
6:	-0.353	0.492
7:	-0.521	0.293
8:	-0.381	0.059
9:	-0.188	-0.040
10:	0.009	-0.063

X CENTROID: 0.000

Y CENTROID: -0.002

POA TO CENTROID: 0.002

HORZ SPREAD: 1.274

VERT SPREAD: 1.483

GROUP SPREAD: 1.543

MIN RADIUS: 0.062


MAX RADIUS: 0.992

MEAN RADIUS: 0.514

IN 1 IN DIAMETER: 4

IN 2 IN DIAMETER: 10

in 3 IN DIAMETER: 10



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: G6535432. __0

TARGET NUMBER: 5

FILE DATE: 05/04/2006

FILE TIME: 08:26

POINT#	X	Y
1:	1.216	-0.046
2:	0.710	0.939
3:	0.408	0.027
4:	0.022	0.602
5:	-0.417	0.494
6:	-0.713	0.200
7:	-0.437	-0.056
8:	0.380	-0.333
9:	0.140	-0.432
10:	-0.167	-0.473

X CENTROID: 0.114

Y CENTROID: 0.092

POA TO CENTROID: 0.147

HORZ SPREAD: 1.929

VERT SPREAD: 1.412

GROUP SPREAD: 1.945

MIN RADIUS: 0.301


MAX RADIUS: 1.110

MEAN RADIUS: 0.669

IN 1 IN DIAMETER: 1

IN 2 IN DIAMETER: 8

in 3 IN DIAMETER: 10



TARGET APPROX 1/2 SCALE

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)
3.00 LBS (plus or minus 0.75 LBS)
4.00 LBS (plus or minus 1.00 LBS)

DATE 4/7/06

TESTER MFJ

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	258	245		249	
PULL #2	266	276		251	
PULL #3	255	246		240	
PULL #4	267	250		257	
PULL #5	268	263		257	
TOTAL	1314	1280		1254	
AVERAGE	262	256		250	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	311	303		
PULL #2	318	308		
PULL #3	313	304		
PULL #4	306	305		
PULL #5	309	306		
TOTAL	1557	1526		
AVERAGE	311	305		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	430	420		445
PULL #2	423	431		446
PULL #3	442	423		442
PULL #4	439	414		452
PULL #5	423	415		454
TOTAL	2157	2103		2239
AVERAGE	431	420		447