


Remington Arms
MayfieldQuality Manual 6-2
Appendix A
Form C-1036

First Article Inspection - Mayfield Results

Part Number
Part NameF300364
FollowerDrawing #
Rev. LevelD 300364
24Vendor
Date Received
Lot #PAR-4
7/6

(DSM - Cavity # 1)

SAMPLES						Average	Min	Max	
#	Feature Name	#1	#2	#3	#4	#5			
1	3.380 ± .005	3.385	3.386	3.385	3.386	3.384	#DIV/0!	0.0000	0.0000
2	.835 ± .005	.836	.836	.835	.836	.836	#DIV/0!	0.0000	0.0000
3	.150 ± .005	.149	.149	.150	.150	.149	#DIV/0!	0.0000	0.0000
4	.270 ± .005	.265	.268	.271	.274	.269	#DIV/0!	0.0000	0.0000
5	1.250 ± .005	1.254	1.250	1.253	1.253	1.254	#DIV/0!	0.0000	0.0000
6	1.020 ± .005	1.015	1.015	1.025	1.021	1.017	#DIV/0!	0.0000	0.0000
7	.327 ± .005	.318	.316	.317	.317	.318	#DIV/0!	0.0000	0.0000
8	.050 ± .005	.049	.050	.050	.049	.049	#DIV/0!	0.0000	0.0000
9	.525 ± .005	.518	.517	.519	.519	.517	#DIV/0!	0.0000	0.0000
10	.050 ± .005	.047	.046	.046	.045	.046	#DIV/0!	0.0000	0.0000
11	.200 ± .005	.205	.205	.205	.205	.205	#DIV/0!	0.0000	0.0000
12	.685 ± .005	.677	.678	.676	.677	.679	#DIV/0!	0.0000	0.0000
13	.760 ± .005	.764	.763	.764	.764	.765	#DIV/0!	0.0000	0.0000
14	PROFILE	R	R	R	R	R	#DIV/0!	0.0000	0.0000
15	2.775 ± .005	2.779	2.776	2.775	2.775	2.779	#DIV/0!	0.0000	0.0000
16	.075 ± .005	.070	.070	.070	.071	.070	#DIV/0!	0.0000	0.0000
17	1.285 ± .005	1.290	1.290	1.290	1.290	1.290	#DIV/0!	0.0000	0.0000
18	.398 ± .005	.380					#DIV/0!	0.0000	0.0000
19	.275	.253					#DIV/0!	0.0000	0.0000
20							#DIV/0!	0.0000	0.0000
21							#DIV/0!	0.0000	0.0000
22							#DIV/0!	0.0000	0.0000
23							#DIV/0!	0.0000	0.0000
24							#DIV/0!	0.0000	0.0000
25							#DIV/0!	0.0000	0.0000
26							#DIV/0!	0.0000	0.0000
27							#DIV/0!	0.0000	0.0000
28							#DIV/0!	0.0000	0.0000
29							#DIV/0!	0.0000	0.0000
30							#DIV/0!	0.0000	0.0000

Inspected
Approved By
Rejected By

Date
Date

7/7/00

Revised By: M. Goelmboski
Revision Date: 2/14/00

FirstArticleInspection

ET06280