

Remington Arms
MayfieldQuality Manual 6-2
Appendix A
Form C-1036

First Article Inspection - Mayfield Results

Part Number
Part NameF300364
FollowerDrawing #
Rev. Level0300364
24Vendor
Date Received
Lot #PAR-4
7/6

(DSM - cavity #2)

SAMPLES						Average	Min	Max	
#	Feature Name	#1	#2	#3	#4	#5			
1	3.380 ± .005	3.384	3.383	3.384	3.383	3.382	#DIV/0!	0.0000	0.0000
2	.835 ± .005	.840	.838	.836	.838	.838	#DIV/0!	0.0000	0.0000
3	.150 ± .005	.147	.149	.148	.147	.148	#DIV/0!	0.0000	0.0000
4	.270 ± .005	.265	.267	.269	.267	.269	#DIV/0!	0.0000	0.0000
5	1.250 ± .005	1.249	1.248	1.251	1.249	1.250	#DIV/0!	0.0000	0.0000
6	1.020 ± .005	1.025	1.025	1.023	1.026	1.021	#DIV/0!	0.0000	0.0000
7	.327 ± .005	.316	.316	.315	.317	.317	#DIV/0!	0.0000	0.0000
8	.050 ± .005	.051	.051	.052	.052	.051	#DIV/0!	0.0000	0.0000
9	.525 ± .005	.518	.518	.518	.518	.517	#DIV/0!	0.0000	0.0000
10	.050 ± .005	.046	.047	.045	.046	.047	#DIV/0!	0.0000	0.0000
11	.200 ± .005	.205	.205	.206	.208	.206	#DIV/0!	0.0000	0.0000
12	.685 ± .005	.674	.675	.673	.675	.675	#DIV/0!	0.0000	0.0000
13	.760 ± .005	.755	.755	.753	.754	.755	#DIV/0!	0.0000	0.0000
14	Profile	R	R	R	R	R	#DIV/0!	0.0000	0.0000
15	2.775 ± .005	2.774	2.771	2.771	2.771	2.772	#DIV/0!	0.0000	0.0000
16	.075 ± .005	.072	.072	.073	.074	.074	#DIV/0!	0.0000	0.0000
17	.700 ± .005	.704	.703	.704	.704	.701	#DIV/0!	0.0000	0.0000
18	1.285 ± .005	1.289	1.289	1.288	1.289	1.289	#DIV/0!	0.0000	0.0000
19	.388 ± .005	.385					#DIV/0!	0.0000	0.0000
20	R .275	.251					#DIV/0!	0.0000	0.0000
21							#DIV/0!	0.0000	0.0000
22							#DIV/0!	0.0000	0.0000
23							#DIV/0!	0.0000	0.0000
24							#DIV/0!	0.0000	0.0000
25							#DIV/0!	0.0000	0.0000
26							#DIV/0!	0.0000	0.0000
27							#DIV/0!	0.0000	0.0000
28							#DIV/0!	0.0000	0.0000
29							#DIV/0!	0.0000	0.0000
30							#DIV/0!	0.0000	0.0000

Inspected
Approved By
Rejected By

John Star

Date
Date

7/7/00

Revised By: M. Goelmboski
Revision Date: 2/14/00

First Article Inspection

ET06281