

EC76 1553

VERY IMPORTANT!
Instruction Book
enclosed to assure
safe use of this
firearm.

Remington®

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

Made in Ilion, NY Reg. U.S. Pat. & Tm. Off. Marca Registrada. Marque Déposée.

SERIAL NO. **E6761553**

ORDER NO. **25716**

46

14XV

5716 E6761553

ORDER 25716
MODEL 700™ M24
UPC



ORDER 25716
MODEL 700™ M24
UPC



SERIAL NO.





MODEL 700, M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

DOCUMENT ENVELOPE ASSEMBLY:

- INSTRUCTION BOOK
- PRODUCT OWNER'S CARD
- SAFETY BOOKLET

46 FORM 1444




ORDER NO. 25716

BARREL LENGTH 24"

CAPACITY 6

E6761553

UPC



CONTRACT #

GUN SERIAL # E60761553

OP #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK		9-24-01	AK
600	PROOF		9/25/01	AC
607	CHECK HEADSPACE	MAGNA - FLUX	9-25-01	AK
610	DIS-ASSEMBLE GUN	INSPECTED	9-25-01	AK
612	MAGNAFLUX BBL ACTION MAGNAFLUX BOLT	SEP 25 2001 OPERATOR <u>AK</u>		
615	ROLLMARK CALIBER		9/27	AK
617	DRILL AND TAP 9/28 SIGHT HOLES BWT	SEND TO NEXT OP	9/27	AK
620	APPLY COATINGS (BARREL ACTION)		10/3	HP
	(BOLT)		10/3	HP
625	FINAL ASSEMBLY		10-15-01	AK
	A) CLEAN INSIDE OF BOLT ASSEMBLY		10-15-01	AK
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		10-15-01	AK
	C) INSPECT EJECTOR HOLE FOR CHAMFER		10-15-01	AK
	D) OIL FIRING PIN ASSEMBLY		10-15-01	AK
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

CONTRACT # _____

GUN SERIAL # _____

OP #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK			
600	PROOF			
607	CHECK HEADSPACE			
610	DIS-ASSEMBLE GUN			
612	MAGNAFLUX BBL ACTION MAGNAFLUX BOLT			
615	ROLLMARK CALIBER			
617	DRILL AND TAP SIGHT HOLES			
620	APPLY COATINGS (BARREL ACTION)			
	(BOLT)			
625	FINAL ASSEMBLY			
	A) CLEAN INSIDE OF BOLT ASSEMBLY			
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD			
	C) INSPECT EJECTOR HOLE FOR CHAMFER			
	D) OIL FIRING PIN ASSEMBLY			
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

OP #	OPERATION NAME	READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>6.4</u> <u>5.5</u> <u>5.5</u>	10-17-01	DA
CONT.	G) SAFETY OFF FORCE 2 LBS MIN	<u>3.2</u> <u>3.2</u> <u>2.5</u>	10-17-01	DA
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.023</u> <u>.022</u> <u>.023</u>	10-17-01	DA
	J) ASSEMBLE STOCK			
	K) ASSEMBLE SWIVEL STUDS		11-6-01	Ac
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		11-6-01	RF
	M) IRON SIGHT ALIGNMENT		11-6-01	RF
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		11-6-01	RF
640	GALLERY TEST AND TARGET	PASS FAIL	10-16-01	RW
	A) MALFUNCTIONS	PASS FAIL	10-16-01	RW
	B) PIERCED PRIMERS	PASS FAIL	10-16-01	RW
645	INSPECT FOR LIVE AMMO		10-16-01	RW
655	FINAL INSPECTION A) HEADSPACE		11-6-01	Ac
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.66</u> <u>2.71</u> <u>2.58</u> <u>2.77</u> <u>2.54</u>	10-17-01	DA
	C) FUNCTION		11-6-01	Ac
660	PACK		12-4-01	DA

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# ± .50#
3.00# ± .75#
4.00# ± 1.00#

SERIAL NO. _____

DATE 10/1/01

TESTER DA

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.41	2.71		2.71	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.69	2.67		2.42	
PULL #3	2.54	2.66		2.39	
PULL #4	2.69	2.72		2.66	
PULL #5	2.69	2.76		2.56	
TOTAL	1302	1352		1274	
AVG.	2.60	2.70		2.54	

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.37	3.42		
PULL #2	3.23	3.37		
PULL #3	3.25	3.30		
PULL #4	3.13	3.32		
PULL #5	3.06	3.40		
TOTAL	1604	1681		
AVG.	3.20	3.36		

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.24	4.29		4.08
PULL #2	4.30	4.06		4.03
PULL #3	4.29	4.32		4.00
PULL #4	4.26	4.31		4.01
PULL #5	4.30	4.10		4.00
TOTAL	2139	2108		20.12
AVG.	4.27	4.21		4.02

Remington Test Lab, Ilion, N.Y.

Centroidal distance calculations for Rifle # e6761553
16 Oct 2001

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: -.1912
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: -.143
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .23876

THE AMR FOR THIS RIFLE IS: .8974

CENTROIDAL DISTANCES

0 TO 1	.432801
1 TO 2	.113
1 TO 3	.365242
1 TO 4	.207002
1 TO 5	.45937


5
3+ <----POA
4
2
1

PATTERN #: ☐ 1 ☐
 POA TO CENTROID: .433
 MIN RADIUS : .375
 MEAN RADIUS : .951
 MAX RADIUS : 2.373
 CENTROID X : -.231
 CENTROID Y : -.366

16 Oct 2001

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/EDIT e6761553

CENTERFIRE PATTERN # 1



OF SHOTS= 10

IN CIRCLE

HS= 1.84
 VS= 3.21
 GS= 3.49


3
 6
 9

PATTERN #: 2
 POA TO CENTROID: .354
 MIN RADIUS : .466
 MEAN RADIUS : .991
 MAX RADIUS : 1.847
 CENTROID X : -.246
 CENTROID Y : -.254

16 Oct 2001

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/EDIT e6761553

CENTERFIRE PATTERN # 2



OF SHOTS= 10

IN CIRCLE

HS= 2.52

1

VS= 2.01

7

GS= 2.77

8


PATTERN #: 3

POA TO CENTROID: .131
 MIN RADIUS : .307
 MEAN RADIUS : .784
 MAX RADIUS : 1.227
 CENTROID X : -.130
 CENTROID Y : -.015

16 Oct 2001

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/EDIT e6761553

CENTERFIRE PATTERN # 3



OF SHOTS= 10

IN CIRCLE

HS= 2.03

3

VS= 2.02

7

GS= 2.05

10

PATTERN #: 4

POA TO CENTROID: .281

MIN RADIUS : .382

MEAN RADIUS : 1.034

MAX RADIUS : 1.837


CENTROID X : -.232

CENTROID Y : -.159

16 Oct 2001

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/EDIT e6761553

CENTERFIRE PATTERN # 4



OF SHOTS= 10

IN CIRCLE

HS= 3.55

1

VS= 1.80

5

GS= 3.63

8

PATTERN #: 5

POA TO CENTROID: .141

MIN RADIUS : .028

MEAN RADIUS : .727

MAX RADIUS : 1.522


CENTROID X : -.117

CENTROID Y : .079

16 Oct 2001

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/EDIT e6761553

CENTERFIRE PATTERN # 5



OF SHOTS= 10

IN CIRCLE

HS= 1.14

2

VS= 2.48

9

GS= 2.50

9