

E 6798178

4

Remington®

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

VERY IMPORTANT!
Instruction Book
enclosed to assure
safe use of this
firearm.

SERIAL NO. **J**
E6790178

ORDER NO. **25716**

46

Made in Illinois, NY Reg. U.S. Pat. & Tel. Off. Marca Registrada Marke Deposee.

22BW

5716 E6790178

ORDER 25716

MODEL 700™ M24

UPC



ORDER 25716

MODEL 700™ M24

UPC



SERIAL NO.




MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

DOCUMENT ENVELOPE ASSEMBLY:

- INSTRUCTION BOOK
- PRODUCT OWNER'S CARD
- SAFETY BOOKLET

46 FORM 1444



ORDER NO.	25716
BARREL LENGTH	24"
CAPACITY	6

E6790178



CONTRACT #

GUN SERIAL # E6790178

OP #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK		11/5/01	Rep
600	PROOF		11/5/01	Rep
607	CHECK HEADSPACE	MAGNA - FLUX	11/5/01	Rep
610	DIS-ASSEMBLE GUN	INSPECTED	11/5/01	Rep
612	MAGNAFLUX BBL ACTION MAGNAFLUX BOLT	NOV 9 - 2001 OPERATOR <u>NRD</u>		
615	ROLLMARK CALIBER		11/9	(A)
617	DRILL AND TAP SIGHT HOLES		11-12	BWT
620	APPLY COATINGS (BARREL ACTION)		11-27	TA
	(BOLT)		11-27	TA
625	FINAL ASSEMBLY			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		12-17	Doug
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		12-17	Doug
	C) INSPECT EJECTOR HOLE FOR CHAMFER		12-17	Doug
	D) OIL FIRING PIN ASSEMBLY		12-17	Doug
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS		1-18-02	BM

CONTRACT # _____

GUN SERIAL # _____

OP #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK			
600	PROOF			
607	CHECK HEADSPACE			
610	DIS-ASSEMBLE GUN			
612	MAGNAFLUX BBL ACTION MAGNAFLUX BOLT			
615	ROLLMARK CALIBER			
617	DRILL AND TAP SIGHT HOLES			
620	APPLY COATINGS (BARREL ACTION)			
	(BOLT)			
625	FINAL ASSEMBLY A) CLEAN INSIDE OF BOLT ASSEMBLY			
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD			
	C) INSPECT EJECTOR HOLE FOR CHAMFER			
	D) OIL FIRING PIN ASSEMBLY			
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

OP #	OPERATION NAME	READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>5.75</u> <u>5.75</u> <u>5.50</u>	1/9/02	D.M.
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>3.50</u> <u>2.75</u> <u>3.50</u>	1/9/02	D.M.
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.023</u> <u>.024</u> <u>.024</u>	1/9/02	D.M.
	J) ASSEMBLE STOCK		1/5/02	EW
	K) ASSEMBLE SWIVEL STUDS		1-10-02	PH
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		1-10-02	PH
	M) IRON SIGHT ALIGNMENT		1-10-02	PH
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		1-10-02	PH
640	GALLERY TEST AND TARGET	PASS FAIL	1-8-02	A
	A) MALFUNCTIONS	PASS FAIL	1-8-02	A
	B) PIERCED PRIMERS	PASS FAIL	1-8-02	A
645	INSPECT FOR LIVE AMMO		1-8-02	A
655	FINAL INSPECTION A) HEADSPACE		1-10-02	PH
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.41</u> <u>2.87</u> <u>2.55</u> <u>2.38</u> <u>2.13</u>	1/9/02	D.M.
	C) FUNCTION		1-10-02	PH
660	PACK		1-19-02	W.A.

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# + .50#
3.00# + .75#
4.00# + 1.00#

SERIAL NO. E6790178

DATE 1/5/02

TESTER D.M.

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.60	2.32		2.49	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.57	2.53		2.49	
PULL #3	2.65	2.42		2.54	
PULL #4	2.50	2.46		2.53	
PULL #5	2.51	2.39		2.60	
TOTAL	12.83	12.12		12.65	
AVG.	2.57	2.42		2.53	


	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.23	3.07		
PULL #2	3.14	3.29		
PULL #3	3.09	3.08		
PULL #4	3.14	3.04		
PULL #5	3.04	3.23		
TOTAL	15.64	15.71		
AVG.	3.13	3.14		

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.15	3.90		4.32
PULL #2	4.08	3.85		4.34
PULL #3	4.04	3.82		4.37
PULL #4	4.06	3.89		4.36
PULL #5	4.02	3.86		4.35
TOTAL	20.35	19.32		21.74
AVG.	4.07	3.86		4.35

SERIAL NUMBER: E6790178. __0
TARGET NUMBER: 1
FILE DATE: 01/08/2002
FILE TIME: 02:54

POINT#	X	Y
1:	-0.677	0.856
2:	-0.451	0.843
3:	-0.435	0.303
4:	-0.241	0.269
5:	0.435	-0.561

X CENTROID: -0.274
Y CENTROID: 0.342
POA TO CENTROID: 0.438
HORZ SPREAD: 1.112
VERT SPREAD: 1.417
GROUP SPREAD: 1.801
MIN RADIUS: 0.080
MAX RADIUS: 1.148
MEAN RADIUS: 0.516
IN 1 IN DIAMETER: 2
IN 2 IN DIAMETER: 4
in 3 IN DIAMETER: 5




TARGET APPROX 1/2 SCALE

SERIAL NUMBER: E6790178. 0
TARGET NUMBER: 2
FILE DATE: 01/08/2002
FILE TIME: 02:54

POINT#	X	Y
1:	0.139	0.580
2:	0.166	0.283
3:	0.743	0.513
4:	-0.471	-0.277
5:	-0.636	-1.516

X CENTROID: -0.012
Y CENTROID: -0.083
POA TO CENTROID: 0.084
HORZ SPREAD: 1.379
VERT SPREAD: 2.096
GROUP SPREAD: 2.453
MIN RADIUS: 0.407
MAX RADIUS: 1.563
MEAN RADIUS: 0.822
IN 1 IN DIAMETER: 2
IN 2 IN DIAMETER: 4
in 3 IN DIAMETER: 4



TARGET APPROX 1/2 SCALE