

E6790229

Remington®

VERY IMPORTANT:
Instruction Book
enclosed to assure
safe use of this
firearm.

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

Made in Ilion, NY Reg. U.S. Pat. & tm. Off. Marca Registrada Marque Deposee.

SERIAL NO. **E6790229**

ORDER NO. **25716**

46



30BW

ORDER

25716

MODEL 700™ M24

UPC



ORDER

25716

MODEL 700™ M24

UPC



MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

DOCUMENT ENVELOPE ASSEMBLY:

- INSTRUCTION BOOK
- PRODUCT OWNER'S CARD
- SAFETY BOOKLET

46 FORM 1444




ORDER NO. 25716

BARREL LENGTH 24"

CAPACITY 6

E6790229



GUN SERIAL # E6790229


OP #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK		11-30-01	RPH
600	PROOF		11-30-01	RPH
607	CHECK HEADSPACE		11-30-01	RPH
610	DIS-ASSEMBLE GUN		11-30-01	RPH
612	MAGNAFLUX BBL ACTION MAGNAFLUX BOLT			AL
615	ROLLMARK CALIBER		12/5/01	LB
617	DRILL AND TAP SIGHT HOLES		12/6/01	BWT
620	APPLY COATINGS (BARREL ACTION)		12/7	HP
	(BOLT)			
625	FINAL ASSEMBLY		1/12/02	D.M.
	A) CLEAN INSIDE OF BOLT ASSEMBLY			
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		1/12/02	D.M.
	C) INSPECT EJECTOR HOLE FOR CHAMFER		1/12/02	D.M.
	D) OIL FIRING PIN ASSEMBLY		1/12/02	D.M.
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS	1-24-02	BA

OP #	OPERATION NAME	READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>4.25</u> <u>4.25</u> <u>4.25</u>	<u>1/23/02</u>	
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>3.25</u> <u>3.25</u> <u>3.25</u>	<u>1/23/02</u>	
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.025</u> <u>.025</u> <u>.023</u>	<u>1/23/02</u>	
	J) ASSEMBLE STOCK		<u>1/21/02</u>	<i>RW</i>
	K) ASSEMBLE SWIVEL STUDS		<u>1/23/02</u>	<i>RW</i>
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		<u>1/21/02</u>	<i>RW</i>
	M) IRON SIGHT ALIGNMENT		<u>1/21/02</u>	<i>RW</i>
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		<u>1/21/02</u>	<i>RW</i>
640	GALLERY TEST AND TARGET	PASS FAIL	<u>1-22-01</u>	<i>A</i>
	A) MALFUNCTIONS	PASS FAIL	<u>1-22-01</u>	<i>A</i>
	B) PIERCED PRIMERS	PASS FAIL	<u>1-22-01</u>	<i>A</i>
645	INSPECT FOR LIVE AMMO		<u>1-22-01</u>	<i>A</i>
655	FINAL INSPECTION A) HEADSPACE		<u>1/23/02</u>	<i>RW</i>
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.87</u> <u>2.89</u> <u>2.50</u> <u>2.35</u> <u>2.57</u>		
	C) FUNCTION		<u>1/23/02</u>	<i>RW</i>
660	PACK		<u>1-24-02</u>	<i>GA</i>

SERIAL NUMBER: E6790229. __0
TARGET NUMBER: 1
FILE DATE: 01/22/2002
FILE TIME: 02:45

POINT#	X	Y
1:	0.528	0.200
2:	1.024	-0.083
3:	-0.465	-0.179
4:	-1.208	0.053
5:	-1.235	1.470

X CENTROID: -0.271
Y CENTROID: 0.292
POA TO CENTROID: 0.399
HORZ SPREAD: 2.259
VERT SPREAD: 1.649
GROUP SPREAD: 2.741
MIN RADIUS: 0.509
MAX RADIUS: 1.522
MEAN RADIUS: 1.030
IN 1 IN DIAMETER: 0
IN 2 IN DIAMETER: 3
in 3 IN DIAMETER: 4




TARGET APPROX 1/2 SCALE

SERIAL NUMBER: E6790229. __0
TARGET NUMBER: 2
FILE DATE: 01/22/2002
FILE TIME: 02:45

X CENTROID: 0.076
Y CENTROID: 0.085
POA TO CENTROID: 0.114
HORZ SPREAD: 1.801
VERT SPREAD: 1.448
GROUP SPREAD: 1.913
MIN RADIUS: 0.119
MAX RADIUS: 1.239
MEAN RADIUS: 0.654
IN 1 IN DIAMETER: 3
IN 2 IN DIAMETER: 4
in 3 IN DIAMETER: 6

POINT#	X	Y
1:	0.000	-0.006
2:	0.347	-0.178
3:	-0.028	-0.286
4:	-0.187	-0.614
5:	-0.738	0.760
6:	1.063	0.834



TARGET APPROX 1/2 SCALE

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# ± .50#
3.00# ± .75#
4.00# ± 1.00#

SERIAL NO. E6790229

DATE 1/17/02

TESTER D.N.

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.65	2.45		2.54	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.48	2.23		2.67	
PULL #3	2.65	2.40		2.51	
PULL #4	2.39	2.39		2.15	
PULL #5	2.50	2.30		2.33	
TOTAL	12.67	11.77		12.20	
AVG.	2.53	2.35			

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.09	3.49		
PULL #2	3.41	3.33		
PULL #3	3.36	3.47		
PULL #4	3.23	3.19		
PULL #5	3.26	3.43		
TOTAL	16.35	16.91		
AVG.	3.27	3.38		

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.07	3.96		4.03
PULL #2	4.09	4.17		4.05
PULL #3	4.02	3.98		4.01
PULL #4	3.98	4.05		4.12
PULL #5	4.00	3.99		4.13
TOTAL	20.16	20.15		20.34
AVG.	4.03	4.03		4.07