

UPC



E6349863

ORDER NO. 25705

BARREL LENGTH 24"

CAPACITY * 6

*INCLUDES 1 IN CHAMBER

Do Not Use

SERIAL NO



E6349863

ORDER 25705
MODEL 700™ M24
UPC



Do Not Use

Remington®

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

Reg. U.S. Pat. & Tm. Off. Marca Registrada. Marque Deposee.

VERY IMPORTANT!
Instruction Book
enclosed to assure
safe use of this
firearm.

SERIAL NO
E6349863

46
ORDER NO.

25705

26WR



5705 E6349863

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

GREEN ENVELOPE CONTAINS:

- INSTRUCTION BOOK
- PRODUCT OWNER'S CARD
- MUSEUM/COUNTRY STORE FLIER
- REMINGTON AUTHORIZED GUNSMITHS

46 FORM

proof of purchase



0 47700 1 25705 1



E6349863

owner registration sticker



0 47700 1 25705 1



E6349863

Do Not

M-24

Truck No #4

ISRAELI GUNS

CONTRACT # DAAE20-97-C-0182

GUN SERIAL # E 6349863

OP. #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK			
600	PROOF			
607	CHECK HEADSPACE			
610	DIS-ASSEMBLE GUN			
612	MAGNAFLUX BARREL ACTION			
	MAGNAFLUX BOLT			
615	ROLLMARK CALIBER			
617	DRILL AND TAP SIGHT HOLES		3/24/97	WJT
618	POLISH BARREL		3/14/97	WJT
620	APPLY COATINGS (BARREL ACTION)			
	(BOLT)			
625	FINAL ASSEMBLY A) CLEAN INSIDE OF BOLT ASSEMBLY			
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD			
	C) INSPECT EJECTOR HOLE FOR CHAMFER			
	D) OIL FIRING PIN ASSEMBLY			
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE			

OP. #	OPERATION NAME	READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE	<u>3</u> <u>3</u> <u>3</u>	7-28-97	CK
CONT.	G) SAFETY OFF FORCE	<u>2⁵</u> <u>3</u> <u>3</u>	7-28-97	CK
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT	<u>.020</u> <u>.021</u> <u>.021</u>	7-28-97	CK
	J) ASSEMBLE STOCK		7-24-97	CK
	K) ASSEMBLE SWIVEL STUDS		8-15-97	CK
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		7-26-97	CK
	M) IRON SIGHT ALIGNMENT		7-24-97	CK
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		7-24-97	CK
640	GALLERY TEST AND TARGET	R56 L 94	8/8/97	KT
	A) MALFUNCTIONS		8/8/97	KT
	B) PIERCED PRIMERS		8/8/97	KT
645	INSPECT FOR LIVE AMMO		8/8/97	JW
655	FINAL INSPECTION A) HEADSPACE		8-15-97	CK
	B) TRIGGER PULL	<u>2.25</u> <u>2.25</u> <u>2.81</u> <u>2.66</u> <u>2.71</u>	8-14-97	CK
	C) FUNCTION		8-15-97	CK
660	PACK			

SWS TRIGGER PULL TEST

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# ± .50#

3.00# ± .75#

4.00# ± 1.00#

SERIAL NO. E6349863

DATE 7-21-97

TESTER TAD

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#	COMMENTS
PULL #1	2.78	1.96	2.29	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.72	1.95	2.26	
PULL #3	2.72	1.94	2.23	
PULL #4	2.70	1.96	2.22	
PULL #5	2.67	1.96	2.24	
TOTAL	13.59	9.77	11.24	
AVG.	2.71	1.95	2.24	

	3.00# INITIAL	3.00# AFTER 20 CYCLES	COMMENTS
PULL #1	3.05	3.16	
PULL #2	3.01	3.08	
PULL #3	3.03	3.08	
PULL #4	3.02	3.03	
PULL #5	3.13	3.10	
TOTAL	15.24	15.45	
AVG.	3.04	3.09	

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	3.86	3.75		3.89
PULL #2	3.85	3.83		3.91
PULL #3	3.78	3.52		3.67
PULL #4	3.76	3.84		3.70
PULL #5	3.77	3.85		4.00
TOTAL	19.02	18.79		19.17
AVG.	3.80	3.75		3.83

Remington Test Lab, Ilion, N.Y.

Centroidal distance calculations for Rifle # E6349863
8 Aug 1997

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: $-.180667$
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: $-.173667$
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: $.2506$

THE AMR FOR THIS RIFLE IS: 1.011

CENTROIDAL DISTANCES

0 TO 1	$.0640703$
1 TO 2	$.189169$
1 TO 3	1.09031

2
+1 <----POA

3

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: 1
 POA TO CENTROID: .064
 MIN RADIUS : .341
 MEAN RADIUS : .766
 MAX RADIUS : 1.113
 CENTROID X : .053
 CENTROID Y : .036

8 Aug 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6349863

CENTERFIRE PATTERN # 1



OF SHOTS= 5

IN CIRCLE

HS= 2.16

2

VS= 1.00

3

GS= 2.17

5

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: 2
 POA TO CENTROID: .235
 MIN RADIUS : .241
 MEAN RADIUS : 1.089
 MAX RADIUS : 2.204
 CENTROID X : .074
 CENTROID Y : .224

8 Aug 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6349863

CENTERFIRE PATTERN # 2



# OF SHOTS= 5	# IN CIRCLE
HS= 3.11	2
VS= 1.99	2
GS= 3.26	4

PATTERN #: 3

POA TO CENTROID: 1.029

MIN RADIUS : .510

MEAN RADIUS : 1.179

MAX RADIUS : 1.868


CENTROID X : -.669

CENTROID Y : -.781

8 Aug 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6349863

CENTERFIRE PATTERN # 3



OF SHOTS= 5

IN CIRCLE

HS= 1.38

0

VS= 3.33

2

GS= 3.34

3