


UPC



E6349937

ORDER NO. 25705

BARREL LENGTH 24"

CAPACITY * 6

*INCLUDES 1 IN CHAMBER

Remington Test Lab, Ilion, N.Y.

Centroidal distance calculations for Rifle # E6349937
15 Aug 1997

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: .333
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: .0406667
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .335474

THE AMR FOR THIS RIFLE IS: .8903

CENTROIDAL DISTANCES

Ø TO	1	.324918
1 TO	2	.0848999
1 TO	3	.238523

+ $\frac{1}{2}$ $\frac{1}{3}$ <----POA

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: 1
 POA TO CENTROID: .325
 MIN RADIUS : .341
 MEAN RADIUS : .738
 MAX RADIUS : 1.368
 CENTROID X : .296
 CENTROID Y : .134

15 Aug 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6349937

CENTERFIRE PATTERN # 1



OF SHOTS= 5

IN CIRCLE

HS= 1.41
 VS= 2.04
 GS= 2.25


3
 3
 5

PATTERN #: 2
 POA TO CENTROID: .279
 MIN RADIUS : .599
 MEAN RADIUS : .995
 MAX RADIUS : 1.274
 CENTROID X : .274
 CENTROID Y : .052

15 Aug 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6349937

CENTERFIRE PATTERN # 2



OF SHOTS= 5

IN CIRCLE

HS= 1.71

0

VS= 2.29

2

GS= 2.29

5

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: 3
 POA TO CENTROID: .434
 MIN RADIUS : .340
 MEAN RADIUS : .938
 MAX RADIUS : 1.336
 CENTROID X : .429
 CENTROID Y : -.064

15 Aug 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6349937

CENTERFIRE PATTERN # 3



OF SHOTS= 5

IN CIRCLE

HS= 1.86
 US= 2.27
 GS= 2.30

1
 2
 5

SWS TRIGGER PULL TEST

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50#+ .50#

3.00#+ .75#

4.00#+1.00#

SERIAL NO. 56349937

DATE 7-24-97

TESTER RW

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#	COMMENTS
PULL #1	2.33	2.31	2.32	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.49	2.34	2.41	
PULL #3	2.30	2.33	2.32	
PULL #4	2.42	2.19	2.30	
PULL #5	2.39	2.26	2.47	
TOTAL	11.93	11.43	11.82	
AVG.	2.37	2.29	2.36	

	3.00# INITIAL	3.00# AFTER 20 CYCLES	COMMENTS
PULL #1	3.07	3.25	
PULL #2	3.28	3.17	
PULL #3	3.22	2.95	
PULL #4	3.26	3.20	
PULL #5	3.22	3.17	
TOTAL	16.05	15.74	
AVG.	3.21	3.15	

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.15	4.17		4.06
PULL #2	4.11	4.13		4.15
PULL #3	4.03	4.17		3.92
PULL #4	4.09	4.17		3.91
PULL #5	4.03	3.96		3.91
TOTAL	20.41	20.60		19.95
AVG.	4.08	4.12		3.99

M-24

ISRAELI GUNS

CONTRACT # DAAE20-97-C-0182

GUN SERIAL # E6349937

OP. #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK			
600	PROOF			
607	CHECK HEADSPACE			
610	DIS-ASSEMBLE GUN			
612	MAGNAFLUX BARREL ACTION			
	MAGNAFLUX BOLT			
615	ROLLMARK CALIBER			
617	DRILL AND TAP SIGHT HOLES		3/18/97	WJT
618	POLISH BARREL		3/18/97	WJT
620	APPLY COATINGS (BARREL ACTION)			
	(BOLT)			
625	FINAL ASSEMBLY A) CLEAN INSIDE OF BOLT ASSEMBLY			
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD			
	C) INSPECT EJECTOR HOLE FOR CHAMFER			
	D) OIL FIRING PIN ASSEMBLY			
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE			

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER
KINZER V. REMINGTON

M2400123978

OP. #	OPERATION NAME	READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE	<u>4</u> <u>42</u> <u>45</u>	7-31-97	JW
CONT.	G) SAFETY OFF FORCE	<u>3</u> <u>3</u> <u>3</u>	7-31-97	JW
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT	<u>23</u> <u>22.5</u> <u>23.5</u>	7-31-97	JW
	J) ASSEMBLE STOCK		7-25-97	CK
	K) ASSEMBLE SWIVEL STUDS		8-21-97	CK
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		7-25-97	CK
	M) IRON SIGHT ALIGNMENT		7-25-97	CK
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		7-25-97	CK
640	GALLERY TEST AND TARGET	R 82 L 68	8-15-97	JW
	A) MALFUNCTIONS		8-25-97	JW
	B) PIERCED PRIMERS		8-15-97	JW
645	INSPECT FOR LIVE AMMO		8-15-97	KT
655	FINAL INSPECTION A) HEADSPACE		8-21-97	CK
	B) TRIGGER PULL	<u>2.36</u> <u>2.34</u> <u>2.45</u> <u>2.32</u> <u>2.45</u>	8-21-97	CK
	C) FUNCTION		8-21-97	CK
660	PACK			

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

- GREEN ENVELOPE CONTAINING:
- INSTRUCTION BOOK
 - PRODUCT OWNER'S CARD
 - MUSEUM/COUNTRY STORE FLIER
 - REMINGTON AUTHORIZED GUNSMITHS

46 FORM

proof of purchase



owner registration sticker



Do Not Use

SERIAL NO.



E6349937

ORDER 25705
MODEL 700™ M24
UPC



ORDER 25705
MODEL 700™ M24
UPC



Do Not Use

Remington®

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

Reg. U.S. Pat. & Tm. Off. Marca Registrada Marque Deposee.

VERY IMPORTANT!
Instruction Book
enclosed to assure
safe use of this
firearm.

SERIAL NO.
E6349937

46

ORDER NO.
25705

26WR

5705 E6349937