

UPC



01 47700 25705 1

E6350114

ORDER NO. 25705

BARREL LENGTH 24"

CAPACITY * 6

*INCLUDES 1 IN. CLAMP

Do Not Use

SERIAL NO.



E6350114

ORDER 25705
MODEL 700™ M24
UPC



011 47700 25705 1

Do Not Use

Remington®

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

Pat. U.S. Pat. & Tr. Off. Patco-Registered, Marquo Depasse

VERY IMPORTANT
Instruction Book
enclosed to assure
safe use of this
firearm

SERIAL NO.
E6350114

46 ORDER NO.
25705

18DR


5705 E6350114

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

GREEN ENVELOPE CONTAINING:

- INSTRUCTION BOOK
- PRODUCT OWNER'S CARD
- MUSEUM/COUNTRY STORE FLIER
- REMINGTON AUTHORIZED GUNSMITHS

46 FORM



Remington Test Lab, Ilion, N.Y.

Centroidal distance calculations for Rifle # E6350114
5 Sep 1997

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: $-.0783333$
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: $.189667$
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: $.205206$

THE AMR FOR THIS RIFLE IS: $.91$

CENTROIDAL DISTANCES

0 TO 1	$.0545711$
1 TO 2	$.495502$
1 TO 3	$.279331$

2

3 +1 <----POA


PATTERN #: 1

POA TO CENTROID: .055
 MIN RADIUS : .672
 MEAN RADIUS : .864
 MAX RADIUS : 1.074
 CENTROID X : .053
 CENTROID Y : .013

5 Sep 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6350114

CENTERFIRE PATTERN # 1



OF SHOTS= 5

IN CIRCLE

HS= 1.65

0

VS= 1.71

4

GS= 1.83

5


PATTERN #: ☐ 2 ☐

POA TO CENTROID: .499
 MIN RADIUS : .400
 MEAN RADIUS : 1.044
 MAX RADIUS : 1.556
 CENTROID X : -.066
 CENTROID Y : .494

5 Sep 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6350114

CENTERFIRE PATTERN # 2



OF SHOTS= 5

IN CIRCLE

HS= 2.13

1

VS= 2.30

2

GS= 2.37

3


PATTERN #: 3

POA TO CENTROID: .231
 MIN RADIUS : .284
 MEAN RADIUS : .822
 MAX RADIUS : 1.277
 CENTROID X : -.222
 CENTROID Y : .062

5 Sep 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6350114

CENTERFIRE PATTERN # 3



OF SHOTS= 5

IN CIRCLE

HS= 2.06

1

VS= 1.31

3

GS= 2.06

5

SWS TRIGGER PULL TEST

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# + .50#

3.00# + .75#

4.00# + 1.00#

SERIAL NO. E6350114

DATE 9-3-97

TESTER TM

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#	COMMENTS
PULL #1	2.37	2.51	2.40	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.39	2.53	2.47	
PULL #3	2.35	2.52	2.51	
PULL #4	2.39	2.50	2.49	
PULL #5	2.33	2.54	2.54	
TOTAL	11.83	12.60	12.41	
AVG.	2.366	2.520	2.482	

	3.00# INITIAL	3.00# AFTER 20 CYCLES	COMMENTS
PULL #1	3.06	3.04	
PULL #2	3.05	3.00	
PULL #3	2.99	3.02	
PULL #4	3.03	2.99	
PULL #5	3.08	3.00	
TOTAL	15.21	15.05	
AVG.	3.042	3.010	

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	3.99	4.09		3.93
PULL #2	4.09	3.99		4.13
PULL #3	3.98	4.02		3.99
PULL #4	3.96	3.98		3.89
PULL #5	3.98	3.90		3.90
TOTAL	20.00	19.98		19.84
AVG.	4.000	3.996		3.968

ISRAELI GUNS

CONTRACT # DAAE20-97-C-0182

GUN SERIAL # E6350114

OP. #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK			
600	PROOF			
607	CHECK HEADSPACE			
610	DIS-ASSEMBLE GUN			
612	MAGNAFLUX BARREL ACTION			
	MAGNAFLUX BOLT			
615	ROLLMARK CALIBER			
617	DRILL AND TAP SIGHT HOLES			
618	POLISH BARREL			
620	APPLY COATINGS (BARREL ACTION)			
	(BOLT)			
625	FINAL ASSEMBLY A) CLEAN INSIDE OF BOLT ASSEMBLY			
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD			
	C) INSPECT EJECTOR HOLE FOR CHAMFER			
	D) OIL FIRING PIN ASSEMBLY			
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE			

OP. #	OPERATION NAME	READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE	<u>5</u> <u>5</u> <u>5</u>	9-4-97	CK
CONT.	G) SAFETY OFF FORCE	<u>3</u> <u>2</u> <u>2</u>	9-4-97	CK
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT	<u>.022</u> <u>.021</u> <u>.022</u>	9-4-97	CK
	J) ASSEMBLE STOCK		9-3-97	CK
	K) ASSEMBLE SWIVEL STUDS		9-11-97	RW
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		9-3-97	CK
	M) IRON SIGHT ALIGNMENT		9-3-97	CK
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		9-3-97	CK
640	GALLERY TEST AND TARGET	L 20 R 80	9/5/97	KT
	A) MALFUNCTIONS		9/5/97	KT
	B) PIERCED PRIMERS		9/5/97	KT
645	INSPECT FOR LIVE AMMO		9/5/97	BWT
655	FINAL INSPECTION A) HEADSPACE		9-11-97	RW
	B) TRIGGER PULL	<u>2.49</u> <u>2.47</u> <u>2.54</u> <u>2.63</u> <u>2.60</u>	9/11/97	JM
	C) FUNCTION		9-11-97	RW
660	PACK			