



G6810448

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)  
BOLT ACTION CENTERFIRE RIFLE  
24" BARREL 7.62 NATO  
WITH BIPOD

proof of purchase



owner registration sticker




ORDER NO. **86470**

BARREL LENGTH 24"

CAPACITY 6

**G6810448**

**UPC**



BM FORM

M-24  
INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL #

G 6810 448

| OP # | OPERATION NAME                                                 | READINGS            | DATE     | INITIAL |
|------|----------------------------------------------------------------|---------------------|----------|---------|
| 420  | ASSEMBLE ACTION                                                |                     | 2-5-09   | SPD     |
| 430  | ASSEMBLE TO STOCK                                              |                     | 2-5-09   | SP      |
| 440  | PROOF                                                          |                     | 2-5-09   | SPD     |
| 460  | CHECK HEADSPACE                                                |                     | 2-5-09   | SPD     |
| 470  | DIS-ASSEMBLE ACTION                                            |                     | 2-5-09   | SPD     |
| 472  | SERIALIZE BOLT HANDLE                                          |                     | 2-6-09   | RT      |
| 475  | DRILL AND TAP<br>SIGHT HOLES                                   |                     | 2-6-09   | TC      |
| 480  | MAGNAFLUX BBL ACTION                                           | EJECTOR             | 2/7/09   | AS      |
| 490  | MAGNAFLUX BOLT                                                 |                     | 2/7/09   | MR      |
| 500  | ROLLMARK CALIBER                                               |                     | 2/9/09   | RT      |
| 520  | GOFF BLAST BBL / REC                                           |                     | 9 Feb 09 | SPD     |
| 542  | APPLY COATINGS<br>(BARREL ACTION)                              |                     | 2 11     |         |
| 545  | (BOLT)                                                         |                     |          |         |
| 560  | RE-ASSEMBLE ACTION                                             |                     |          |         |
|      | A) CLEAN INSIDE OF<br>BOLT ASSEMBLY                            |                     | 2-11-09  | SP      |
|      | B) INSPECT REAR FIRING<br>PIN HOLE FOR CHAMFER<br>IN BOLT HEAD |                     | 2-11-09  | SP      |
|      | C) INSPECT EJECTOR<br>HOLE FOR CHAMFER                         |                     | 2-11-09  | SP      |
|      | D) OIL FIRING PIN ASSEMBLY                                     |                     | 2-12-09  | RT      |
|      | E) ADJUST TRIGGER PULL<br>TO MIN. SETTING AND<br>STAKE         | 2.50 LBS +/- .5 LBS |          |         |

F004 REV 5/2006


| OP #         | OPERATION NAME                                                           | READINGS                                                    | DATE    | INITIAL |
|--------------|--------------------------------------------------------------------------|-------------------------------------------------------------|---------|---------|
| 560          | F) SAFETY ON FORCE <span>2 LBS MIN<br/>10 LBS MAX</span>                 | <u>4</u> <u>4.5</u> <u>4</u>                                | 2-27-09 | WV      |
| CONT.        |                                                                          |                                                             |         |         |
|              | G) SAFETY OFF FORCE <span>2 LBS MIN</span>                               | <u>3.5</u> <u>3.5</u> <u>4</u>                              | 2-27-09 | WV      |
|              | H) TRIGGER PULL TEST<br>AND RETAINABILITY                                |                                                             |         |         |
|              | I) FIRING PIN INDENT <span>.020 MIN</span>                               | <u>.025</u> <u>.024</u> <u>.025</u>                         | 2-27-09 | WV      |
|              | J) ASSEMBLE STOCK                                                        |                                                             | 2-12-09 | RTZ     |
|              | K) ASSEMBLE SWIVEL<br>STUDS                                              |                                                             | 2-27-09 | WV      |
|              | L) ATTACH FRONT AND<br>REAR SIGHT ASSY'S                                 |                                                             |         |         |
|              | M) IRON SIGHT<br>ALIGNMENT                                               |                                                             |         |         |
|              | N) DETACH FRONT AND<br>REAR SIGHTS AND PLACE<br>IN NUMBERED CONTAINER    |                                                             |         |         |
| 640 &<br>650 | FUNCTION TEST AND<br>TARGET                                              | <u>PASS</u> FAIL<br><u>PASS</u> FAIL                        | 2-19-09 | L.P.D.  |
|              | MALFUNCTION                                                              | CORRECTION                                                  |         |         |
|              | MALFUNCTION                                                              | CORRECTION                                                  |         |         |
|              | MALFUNCTION                                                              | CORRECTION                                                  |         |         |
|              | MALFUNCTION                                                              | CORRECTION                                                  |         |         |
| 660          | INSPECT FOR LIVE AMMO                                                    |                                                             | 2-19-09 | SP      |
| 670          | FINAL INSPECTION<br>A) HEADSPACE                                         |                                                             | 2-27-09 | WV      |
|              | B) TRIGGER PULL <span>+/- .5 LBS<br/>MIN 2.50 LBS<br/>MAX 4.0 LBS</span> | <u>2.55</u> <u>2.33</u> <u>2.31</u> <u>2.32</u> <u>2.41</u> | 2-20-09 | WV      |
|              | C) FUNCTION                                                              |                                                             | 2-27-09 | WV      |
| 690          | PACK                                                                     |                                                             | 3/2/09  | Fm      |

F004 REV 5/2006

# Trigger Profile [ lbs,inch ]

Profile: SWS  
 GunType: Rifle  
 Make: Remington  
 Note: C Schults 2/5/2009

Model: M/24  
 Serial No: Form #F005  
 Trigger: 2.5 lbs ini +/- .50 lb




| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 2.531      | 0.018             | 0.00            | 0.032      | 0.032             |           | Set Trigger |
| 2 | 2.404      | 0.018             | 0.00            | 0.032      | 0.031             |           | Set Trigger |
| 3 | 2.463      | 0.019             | 0.00            | 0.031      | 0.034             |           | Set Trigger |
| 4 | 2.601      | 0.018             | 0.00            | 0.031      | 0.034             |           | Set Trigger |
| 5 | 2.482      | 0.017             | 0.00            | 0.031      | 0.032             |           | Set Trigger |

A. 2-49

# Trigger Profile [ lbs,inch ]

Profile SWS  
 GunType: Rifle  
 Make: Remington  
 Note: C Schults 2/5/2009

Model: M/24  
 Serial No: Form #F005  
 Trigger: 2.5 lbs after 50 cycles+/- .50 lb




| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 2.349      | 0.018             | 0.00            | 0.033      | 0.031             |           | Set Trigger |
| 2 | 2.390      | 0.018             | 0.00            | 0.033      | 0.031             |           | Set Trigger |
| 3 | 2.364      | 0.018             | 0.00            | 0.032      | 0.031             |           | Set Trigger |
| 4 | 2.324      | 0.019             | 0.00            | 0.032      | 0.032             |           | Set Trigger |
| 5 | 2.415      | 0.018             | 0.00            | 0.032      | 0.032             |           | Set Trigger |

A-2.36

# Trigger Profile [ lbs,inch ]

Profile SWS  
GunType: Rifle  
Make: Remington  
Note: C Schults 2/5/2009

Model: M/24  
Serial No: Form #F005  
Trigger: 3.0 lbs ini +/- .75 lb




| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 3.441      | 0.020             | 0.00            | 0.029      | 0.049             |           | Set Trigger |
| 2 | 3.542      | 0.020             | 0.00            | 0.029      | 0.048             |           | Set Trigger |
| 3 | 3.480      | 0.020             | 0.00            | 0.029      | 0.049             |           | Set Trigger |
| 4 | 3.593      | 0.020             | 0.00            | 0.029      | 0.050             |           | Set Trigger |
| 5 | 3.456      | 0.020             | 0.00            | 0.029      | 0.047             |           | Set Trigger |

A B-50

# Trigger Profile [ lbs,inch ]

**Profile:** SWS  
**GunType:** Rifle  
**Make:** Remington  
**Note:** C Schults 2/5/2009

**Model:** M/24  
**Serial No:** Form #F005  
**Trigger:** 3.0 lbs after 20 cycles+/- .75 lb




| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 3.146      | 0.019             | 0.00            | 0.030      | 0.043             |           | Set Trigger |
| 2 | 3.230      | 0.020             | 0.00            | 0.030      | 0.045             |           | Set Trigger |
| 3 | 3.200      | 0.020             | 0.00            | 0.030      | 0.044             |           | Set Trigger |
| 4 | 3.294      | 0.020             | 0.00            | 0.030      | 0.046             |           | Set Trigger |
| 5 | 3.275      | 0.020             | 0.00            | 0.030      | 0.046             |           | Set Trigger |

A-3-22

# Trigger Profile [ lbs,inch ]

Profile SWS  
 GunType: Rifle  
 Make: Remington  
 Note: C Schults 2/5/2009

Model: M/24  
 Serial No: Form #F005  
 Trigger: 4.0 lbs ini +/- 1.0 lb




| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 4.438      | 0.021             | 0.00            | 0.027      | 0.062             |           | Set Trigger |
| 2 | 4.405      | 0.021             | 0.00            | 0.027      | 0.061             |           | Set Trigger |
| 3 | 4.366      | 0.021             | 0.00            | 0.027      | 0.061             |           | Set Trigger |
| 4 | 4.464      | 0.021             | 0.00            | 0.027      | 0.063             |           | Set Trigger |
| 5 | 4.604      | 0.021             | 0.00            | 0.027      | 0.065             |           | Set Trigger |

A. 4.45

# Trigger Profile [ lbs,inch ]

Profile SWS  
GunType: Rifle  
Make: Remington  
Note: C Schults 2/5/2009

Model: M/24  
Serial No: Form #F005  
Trigger: 4.0 lbs after 20 cycles+/- 1.0 lb




| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 4.472      | 0.020             | 0.00            | 0.027      | 0.061             |           | Set Trigger |
| 2 | 4.475      | 0.022             | 0.00            | 0.027      | 0.064             |           | Set Trigger |
| 3 | 4.469      | 0.022             | 0.00            | 0.027      | 0.066             |           | Set Trigger |
| 4 | 4.428      | 0.021             | 0.00            | 0.027      | 0.062             |           | Set Trigger |
| 5 | 4.504      | 0.023             | 0.00            | 0.027      | 0.067             |           | Set Trigger |

A. 4.47

## Trigger Profile [ lbs,inch ]

Profile SWS  
GunType: Rifle  
Make: Remington  
Note: C Schults 2/5/2009

Model: M/24  
Serial No: Form #F005  
Trigger: reset to 2.5 lbs +/- .50 lb for final test




| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 2.456      | 0.018             | 0.00            | 0.032      | 0.032             |           | Set Trigger |
| 2 | 2.577      | 0.018             | 0.00            | 0.032      | 0.033             |           | Set Trigger |
| 3 | 2.453      | 0.018             | 0.00            | 0.033      | 0.031             |           | Set Trigger |
| 4 | 2.478      | 0.017             | 0.00            | 0.033      | 0.031             |           | Set Trigger |
| 5 | 2.572      | 0.018             | 0.00            | 0.032      | 0.034             |           | Set Trigger |

A-250

# Trigger Profile [ lbs,inch ]

Profile: SWS  
 GunType: Rifle  
 Make: Remington  
 Note: C Schults 2/5/2009

Model: M/24  
 Serial No: Form #F005  
 Trigger: set to 4.0 lbs +/- 1.0 lb for target & accuracy



| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 4.202      | 0.021             | 0.00            | 0.027      | 0.058             |           | Set Trigger |
| 2 | 4.065      | 0.020             | 0.00            | 0.028      | 0.056             |           | Set Trigger |
| 3 | 4.207      | 0.021             | 0.00            | 0.028      | 0.059             |           | Set Trigger |
| 4 | 4.161      | 0.021             | 0.00            | 0.028      | 0.058             |           | Set Trigger |
| 5 | 4.107      | 0.021             | 0.00            | 0.027      | 0.057             |           | Set Trigger |

A: 4.14