

G6300642

VERY IMPORTANT! Instruction Book enclosed to assure safe use of this firearm.

Remington®

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

Made in Tilton, NY Reg. U.S. Pat. & Tm. Off. Marca Registrada. Marque Deposee.

SERIAL NO. J 66300642	ORDER NO. 25716
---------------------------------	---------------------------

24CX



5716 66300642

ORDER 25716
M/24 7.62 NATO S.W.S. (COMPLETE SYST

UPC



ORDER 25716
M/24 7.62 NATO S.W.S. (COMPLETE SYST

UPC



SERIAL NO.



M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO


- INSTRUCTION BOOK 3518

46 FORM

proof of purchase



owner registration sticker




ORDER NO. **25716**

BARREL LENGTH **24"**

CAPACITY **6**

G6300642

UPC



M-24
INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL # G 6300642

OP #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK		3-25-03	RTL
600	PROOF		3-25-03	RTL
607	CHECK HEADSPACE	MAGNA-FLUX INSPECTED	3-26-03	RTL
610	DIS-ASSEMBLE GUN	JAN 27 2003	3-26-03	RTL
612	MAGNAFLUX BBL ACTION MAGNAFLUX BOLT	OPERATOR <i>PR</i>		
615	ROLLMARK CALIBER		3/27/03	LB
617	DRILL AND TAP SIGHT HOLES		3-26-03	TRL
620	APPLY COATINGS (BARREL ACTION)		4-4	TA
	(BOLT)		4-4	TA
625	FINAL ASSEMBLY			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		4-9-03	DA
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		4-9-03	DA
	C) INSPECT EJECTOR HOLE FOR CHAMFER		4-9-03	DA
	D) OIL FIRING PIN ASSEMBLY		4-9-03	DA
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS		4-21-03	RTL

OP #	OPERATION NAME	READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>5.2</u> <u>5.5</u> <u>5.5</u>	4/21/03	DA
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>2.2</u> <u>2.2</u> <u>2.5</u>	4/21/03	DA
	H) TRIGGER PULL TEST AND RETAINABILITY		4-21-03	RTL
	I) FIRING PIN INDENT .020 MIN	<u>.024</u> <u>.023.5</u> <u>.023</u>	4/21/03	DA
	J) ASSEMBLE STOCK		4-9-03	RLW
	K) ASSEMBLE SWIVEL STUDS		4-21-03	RTL
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		4-21-03	RTL
	M) IRON SIGHT ALIGNMENT		4-21-03	RTL
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		4-21-03	RL
640	GALLERY TEST AND TARGET	PASS FAIL	4-14-03	TRLW
	MALFUNCTION	CORRECTION	4-14-03	TRLW
	MALFUNCTION	CORRECTION	4-14-03	TRLW
	MALFUNCTION	CORRECTION	4-14-03	TRLW
	MALFUNCTION	CORRECTION	4-14-03	TRLW
645	INSPECT FOR LIVE AMMO		4-14-03	TRLW
655	FINAL INSPECTION A) HEADSPACE		4-21-03	RTL
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.65</u> <u>2.86</u> <u>2.79</u> <u>2.75</u> <u>2.84</u>	4/21/03	DA
	C) FUNCTION		4-21-03	RL
660	PACK		4/22/03	DA

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS
2.50# + .50#
3.00# + .75#
4.00# + 1.00#

SERIAL NO. _____

DATE 11-22-02

TESTER TRW

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.68	2.47		2.79	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT ABLE LESS THAN
PULL #2	2.55	2.54		2.74	
PULL #3	2.56	2.52		2.57	
PULL #4	2.55	2.50		2.68	
PULL #5	2.53	2.50		2.64	
TOTAL	12.87	12.53		13.42	
AVG.	2.57	2.50		2.68	

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.23	3.05		
PULL #2	3.13	3.04		
PULL #3	3.11	3.06		
PULL #4	3.19	3.03		
PULL #5	3.10	3.05		
TOTAL	15.76	15.23		
AVG.	3.15	3.04		

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# & TARGET & ACCU
PULL #1	4.43	4.30		4.17
PULL #2	4.44	4.38		4.18
PULL #3	4.37	4.36		4.20
PULL #4	4.46	4.29		4.15
PULL #5	4.37	4.27		4.28
TOTAL	22.07	21.60		20.98
AVG.	4.41	4.32		4.19

SNIPER WEAPON SYSTEM - UNIQUE STATISTICAL INFORMATION

FIREARM SERIAL NUMBER / DATASET NAME: G6300642.__0
FILE DATE AND TIME: 04/15/2003 01:25

THE FOLLOWING DATA IS ALL REPORTED IN UNITS OF INCHES


ERROR - NOT POSSIBLE TO REPORT SWS STATS ON DATA
WHERE TOTAL TARGETS ARE NOT EQUAL TO FIVE

ave. mean .6935

SERIAL NUMBER: G6300642. __0
TARGET NUMBER: 1
FILE DATE: 04/15/2003
FILE TIME: 01:25

POINT#	X	Y
1:	0.107	-0.751
2:	-0.214	-0.359
3:	0.105	-0.325
4:	-0.479	0.997
5:	-0.006	1.283

X CENTROID: -0.097
Y CENTROID: 0.169
POA TO CENTROID: 0.195
HORZ SPREAD: 0.586
VERT SPREAD: 2.034
GROUP SPREAD: 2.037
MIN RADIUS: 0.534
MAX RADIUS: 1.118
MEAN RADIUS: 0.809
IN 1 IN DIAMETER: 0
IN 2 IN DIAMETER: 4
in 3 IN DIAMETER: 5




TARGET APPROX 1/2 SCALE

SERIAL NUMBER: G6300642.___0
TARGET NUMBER: 2
FILE DATE: 04/15/2003
FILE TIME: 01:25

POINT#	X	Y
1:	0.711	-0.569
2:	-0.676	-0.604
3:	-0.308	0.089
4:	-0.098	0.171
5:	0.092	0.514

X CENTROID: -0.056
Y CENTROID: -0.080
POA TO CENTROID: 0.097
HORZ SPREAD: 1.387
VERT SPREAD: 1.118
GROUP SPREAD: 1.387
MIN RADIUS: 0.254
MAX RADIUS: 0.910
MEAN RADIUS: 0.578
IN 1 IN DIAMETER: 2
IN 2 IN DIAMETER: 5
in 3 IN DIAMETER: 5



TARGET APPROX 1/2 SCALE