

PROJECT# 241095

TLW 0344

GUN	TRIGGER PULL	1	2	3	AVERAGE
A-1		4.75	5	4.5	4.75
A-2		4.75	4.75	4.75	4.75
A-3		5.5	5.25	5	5.25
A-4		5.5	5.5	5.25	5.42
A-5		6	5.75	5.75	5.83
A-6		4.75	4.25	4.75	4.58
A-7		4.75	5	5	4.92
A-8		5.5	5.5	6	5.67
A-9		6	5.25	5.5	5.58
A-10		4.75	4.5	4.75	4.67

CONFIRM PROPER FIT BETWEEN STOCK AND RECEIVER AND STOCK TO BARREL. NO SHIMS**GUN**

A-1 STOCK, BARREL AND RECEIVER GAPS NOT UNIFORM BUT NOT EXCESSIVE NO SHIMS
A-2 STOCK, BARREL AND RECEIVER GAPS NOT UNIFORM BUT NOT EXCESSIVE NO SHIMS
A-3 STOCK, BARREL AND RECEIVER GAPS NOT UNIFORM BUT NOT EXCESSIVE NO SHIMS
A-4 STOCK, BARREL AND RECEIVER GAPS NOT UNIFORM BUT NOT EXCESSIVE NO SHIMS
A-5 STOCK, BARREL AND RECEIVER GAPS NOT UNIFORM BUT NOT EXCESSIVE NO SHIMS
A-6 OK
A-7 OK
A-8 STOCK, BARREL AND RECEIVER GAPS NOT UNIFORM BUT NOT EXCESSIVE NO SHIMS
A-9 STOCK, BARREL AND RECEIVER GAPS NOT UNIFORM BUT NOT EXCESSIVE NO SHIMS
A-10 STOCK, BARREL AND RECEIVER GAPS NOT UNIFORM BUT NOT EXCESSIVE NO SHIMS

CONFIRM PERMANENT ATTACHMENT OF RECOIL LUG TO STOCK

RECOIL LUGS ON ALL 10 GUNS WERE PERMANENTLY GLUED TO THE STOCK.

GUN	HEAD SPACE	PROOF RDS	HEAD SPACE	HEAD SPACE AFTER 10 RDS.
A-1	MIN	1	0.001	0.002
A-2	0.001	1	0.003	0.003
A-3	0.002	1	0.002	0.003
A-4	MIN	1	0.002	0.002
A-5	0.001	1	0.002	0.002
A-6	0.001	1	0.002	0.002
A-7	0.001	1	0.002	0.002
A-8	0.001	1	0.002	0.002
A-9	0.001	1	0.002	0.002
A-10	0.001	1	0.002	0.002

Subject to Protective Order - Williams v. Remington

BARBER 5.30.06R0002523

ETE00002522