

CONFIDENTIAL

Remington Arms Company Inc.
RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

Method:

- Trigger pull is to be performed to the SAAMI standard; horizontal pull at the center of the finger radius of the trigger using the Test Lab apparatus designed for taking this measurement.
- Use the 1-10 lb. Chatillion Force digital force gauge.
- Force is measured parallel to the bore with the stock assembled to the action.
- Three pulls are to be taken on each sample rifle and the results averaged.
- The average force for the three trials must be between 4.0 lb. and 5.0 lb.

Data Required:

- Rifle Serial number
- All three data points for each trial rifle
- The average of the three measurements for each sample rifle

TLW0300K - Measure Safe On/Off Forces:

Using the Chatillion Digital force gauge and the wooden holding fixture used to take trigger pull readings, push the Safe from the "Safe On" to the "Safe Off" position on each test sample. Complete three trials. Record all three readings for each firearm. A minimum of 1 lb. force in "Safe On" to "Safe Off" direction will be assumed as the reference criteria.

Method:

- Use trigger pull apparatus to hold the rifle for this test.
- Use the Chatillion Digital Force gauge (0-10 lb. range) with the disc point or the "v" shaped point. Use the same tip on all subsequent trials.
- Make three trials in specified direction for each sample.
- Average the results of each of the three trials.

J.R.Snedeker

05/24/06

Page 14 of 50

10:07 AM

TLW0300

Remington Confidential

Revision # 3