## CONFIDENTIAL

Remington Arms Company Research & Development Technical Center 315 WEST Rins Road
Euzabethtown, KY 42701

- Tests shall be conducted with the trigger pull force set at the minimum force specified, with engagement set to the minimum specified, and with the firecontrol lubricated as in the owner's manual.
- The test shall be conducted with the magazine or clip fully loaded with dummy cartridges and inserted in the firearm
- Parts breakage or other damage as a result of drop testing does not constitute failure as long as the empty
  primed case does not fire and the firearm can be unloaded safely after each drop. More stocks or receiver
  inserts may be required than the amount of test guns to allow for breakage due to the drop testing. If a part
  cracks or breaks- replace before continuing test.

## Data required:

- Record whether or not the firearm fires an empty primed case of its designated cartridge when tested in accordance with this procedure.
- · Record round level

## TLW0300AL - SAAMI Jar-Off Test -- "System" (Includes the Scope and Mounting Rails):

The objective of the jar-off test is to simulate the abusive impacting (bumping) of the firearm against a hard surface with the firearm in a condition of maximum readiness. With the firearm in the ready to fire condition, the firearm shall be capable of withstanding a jar-off shock equivalent to being dropped from a height of 12" inches onto a 1" thick 83 Durometer (Shore A) rubber mat backed by concrete. Trigger Pull weight and engagement will be adjusted to minimum specification, 4 lbs. and .020 inch respectively. The test will be performed according to SAAMI Technical Committee procedures. Magazine will be loaded to maximum capacity with dummy rounds according to SAAMI procedures. A fresh primed case will be chambered prior to each drop. After each drop the primed case will be discharged to verify its validity. This test will be performed on a sample of six firearms of 30-06 caliber.

JR.Snedeker Page 41 of 50 10:08 AM

05/24/06

**TLW0300** 

Remington Confidential

Revision #3