CONFIDENTIAL

Remington Arms Company Research & Development Technical Center 315 West Ring Road Elizabethtown, KY 42701

The Standard Remington Jacks (using the heavy configuration) are to be used for this test.

Data Required:

- Rifle serial number
- · Tester's name
- The Test Jack Identification
- TLW#
- · Date of actual testing
- Headspace after the 400 round interval.
- Malfunctions per ammo type, breakage, and replacement parts used
- Any failure that requires the gun to be removed from testing completely.
- Notify management of any unusual events or malfunctions immediately.
- Any firing of the firearm without the trigger being pulled.
- Record ammunition lot code information as it is used throughout the test.
- Bullet type used for each 20 rounds of the test.

TLW0300AB - Clean Rifles and Inspect:

After 400 rounds of Extended Function & Endurance, unless other wise specified, each rifle will be disassembled, cleaned and thoroughly inspected.

A list of inspection points will be provided in the gun packet for check-off and sign-off by the inspector. The inspector will be looking for any signs of unusual wear, especially on critical components and surfaces as well as for anything such as cracks or deformed material that might present a safety concern. Photographs will be taken to document unusual wear, damage or other notable characteristics. Use the following checklist for inspection:

J.R.Snedeker Page 33 of 52

10:35 AM 9/21/00

TLW0300

Remington Confidential

Revision # 0