

SAFETY RULES

REMEMBER

READ THESE BASIC SAFETY RULES. Learn how to handle your firearm safely. Failure to obey these rules can result in serious personal injuries. Only you can prevent accidents.



KNOW YOUR FIREARM. To use it correctly and safely, read and follow the instructions in the enclosed firearms safety booklet and this instruction book.

TREAT EVERY FIREARM AS IF IT WERE LOADED. Don't rely on the safety switch. Use it as shown in this book.



NEVER MAKE ADJUSTMENTS. Do not make changes or alterations to any parts of a firearm. Use only REMINGTON parts. Never make an adjustment to the trigger, or change the shape or size of the sear, sear notch, or other parts.

WEAR EYE PROTECTION. Wear eye protection, such as glasses or sunglasses, when shooting. Wear ear protection, such as ear plugs or muffs, when target shooting or plinking. Repeated exposure to shooting noise can cause permanent hearing loss. Never drink alcoholic beverages before or during shooting.



KEEP YOUR FIREARM CLEAN. Keep the barrel clean and free of obstructions. Clean and have the firearm checked periodically to make sure it is mechanically correct. Worn, damaged or missing parts may be dangerous.

ALWAYS POINT THE MUZZLE. Always keep the firearm pointed in a safe direction.

LUBRICATION AND MAINTENANCE



LUBRICATION:

Over-lubrication should be avoided at all times. A thin coat of Remtm Oil is all that is needed to prevent the possibility of rusting. See note below.

When the firearm is to be stored, it should be carefully cleaned and thoroughly oiled. Outside surfaces should be wiped with a light coat of Remtm Oil occasionally.

When firearm is to be reused, all excess lubrication must be removed. The chamber and bore must be thoroughly wiped dry.

NOTE: Remington Remtm Oil with DuPont Teflon Wet Lubricant is available from your local dealer. If your dealer is out of stock, ask him to order Remtm Oil from his Remington distributor.

TO CLEAN THE BARREL

WARNING: Check the chamber and magazine to make sure there are no cartridges in the firearm.


1. Use the equipment provided in a good cleaning kit.
2. Remove the bolt assembly. See instructions on Page 5.

3. Select the correct caliber cleaning brush and attach the brush to the cleaning rod.
4. Put the cleaning brush into the gun cleaning solvent.

NOTE: Barrel should lay horizontally with the ejection port facing down during cleaning. Always clean the barrel from the chamber end to the muzzle.

5. Push the cleaning brush through the barrel several times.
6. Remove brush from rod, attach tip with patch, and push through the bore.
7. Repeat several times, using a new cleaning patch each time, until the patch is not dirty.
8. Push a clean patch saturated with Remtm Oil through the barrel.
9. Push a clean dry patch through the barrel to remove excess lubricant.
10. Apply a thin coat of Remtm Oil to the outside of the barrel with a soft clean cloth.
11. After cleaning the barrel, clean the receiver and the trigger assembly.

WARNING: This firearm should be checked periodically by the Remington Arms Company, Inc. or a REMINGTON RECOMMENDED GUNSMITH. This will insure proper inspection and any necessary replacement of worn or damaged parts.



NTBOOK278