

CONFIDENTIAL

Remington Arms Company Inc.
RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

TLW0300AD (@zero) - Group Size at 100 yards (System Stability Test, w/Bushnell Scope @ "zero" rounds

One hundred-yard accuracy testing will be completed utilizing standard factory ammunition. The test will consist of three, 5-shot groups. Guns will be cooled after every other group. Each firearm will be cleaned and fired with five fouling shots prior to beginning the accuracy work-up. Group sizes will be measured from actual targets and recorded. The same code of ammunition and same type of ammunition will be used for all group size test shots. Average group sizes must be $\leq 2.7"$ at 100 yards.

Method:

- Certify the ammunition selected for muzzle velocity and pressure.
- Fire three, 5-shot groups at 100 yards, for each ammunition type selected. Prior to beginning of the test, clean the bore and shoot 5 "fouling" shots to seat in the rifle.
- Cycle the safety from fire to safe every 5 rounds.
- Accuracy should be shot from a recording rest. Shoulder shooting is acceptable but not the preferred way.

Data Required:

- Measure group sizes center to center.
- Record takedown screw torque.
- Record make and identifier of scope.
- Record ammunition type used.
- Record ammunition lot numbers used during the test.
- Record and label any fail-to-fire ammunition.
- Record any malfunctions that occur during the test.

TLW0300AE (@100)- Group Size at 100 yards (System Stability Test, w/Bushnell Scope @ "100" rounds

J.R.Snedeker

Page 36 of 52

10:35 AM 9/21/00

TLW0300

Remington Confidential

Revision # 0

Subject to Protective Order - Williams v. Remington

BARBER 5.30.06R0002874

ETE00002793