

WAW

8.10.93

IF BOLT LOCK/BOLT STOP ARE
COMMON/INTER-RELATED PARTS,
THEN IT SHOULD BE DONE IN A
WAY THAT USER CAN ELECT
NOT TO HAVE BOLT ~~LOCK~~ LOCK
FUNCTION BUT RETAIN BOLT
STOP FUNCTION.

- e FACTORY
- e GUNSMITH
- e SELF

BEST WAY WOULD ~~XXX~~
INVOLVE ^{NOT} REMOVING A
PART

- COST/MISPLACED
IF THEN DIFFICULT TO
RESTORE OTHER MODE.

FOR MINIMUM (FLOOR) ON TRIGGER
ROLL :

- DUAL SPRING SYSTEM

- 1 FIXED MINIMUM PERMANENT INSTALLATION
C ASS'T.
- 1 ADDITIVE FOR ADJUSTMENT

- SINGLE SPRING WITH,
MINIMUM PRELOAD MAINTAINED
WHEN ADJUSTMENT IS COMPLETELY
TO MINIMUM EXTREME.

BROWNING BEA

- ACCESSIBLE WITHOUT
RIFLE DISASSEMBLY
- ACCESSIBLE ONLY WITH
RIFLE DISASSEMBLY.